

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: EXSITE 24 A (111624-KA)

Recommended Use of the

Chemical and Restrictions on

Use

Plastic materials.

Supplier: Ixom Central Pacific Ltd

Company Number: 1030

Street Address: Lots 3&4 Wailada Industrial Estate

Lami Fiji

Telephone Number: +67 9 336 1144

Facsimile: +67 9 336 1500 Emergency Telephone: +61 3 96632130

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Non hazardous component(s)	-	100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice. If molten material should contact the skin and adhere, cool quickly with running water - do not attempt to remove. Seek immediate medical assistance.

Product Name: EXSITE 24 A (111624-KA)

Substance No: 000000053184

Issued: 30/03/2016 Version: 1



Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. For contact with the molten material treat as for skin burns.

Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Never give anything by the mouth to an unconscious patient. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Unsuitable Extinguishing Media:

Water jet.

Specific hazards arising from the substance or mixture:

Combustible solid.

Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon, oxides of nitrogen. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in dust. Avoid handling which leads to dust formation.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for particulates:

Dusts not otherwise classified: 8hr TWA = 10 mg/m³

Product Name: EXSITE 24 A (111624-KA) Issued: 30/03/2016 Substance No: 000000053184

Version: 1



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.









Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

When handling melt, or where there is a risk of being splashed with molten material: Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots.

9. PHYSICAL AND CHEMICAL PROPERTIES

Pellets Physical state: Not specified Colour: Odour: Characteristic Solubility: Insoluble in water. Specific Gravity: Not available Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): Not available Flash Point (°C): Not available Flammability Limits (%): Not available Autoignition Temperature (°C): Not available

Product Name: EXSITE 24 A (111624-KA)

Substance No: 000000053184

Issued: 30/03/2016 Version: 1



Melting Point/Range (°C): >90

pH: Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No information available.

Chemical stability: No information available.

Possibility of hazardous

reactions:

None known.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame. Avoid dust

generation.

Incompatible materials: None known.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: No adverse effects expected, however, large amounts may cause nausea and

vomiting.

Eye contact: May be an eye irritant. Exposure to the dust may cause discomfort due to

particulate nature. May cause physical irritation to the eyes. Contact with the hot

material can result in pain, thermal burns, and permanent injury.

Skin contact: Contact with skin may result in irritation. Contact with hot material may cause skin

burns.

Inhalation: Breathing in dust may result in respiratory irritation. Vapour and processing fumes

may cause irritation to mucous membranes of the respiratory tract, headache and

nausea.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Substance No: 000000053184

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Product Name: EXSITE 24 A (111624-KA) Issued: 30/03/2016

Version: 1



Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail: NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air: NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule (SUSMP): None allocated.

16. OTHER INFORMATION

Supplier Safety Data Sheet; 09/2015.

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage. assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: EXSITE 24 A (111624-KA) Issued: 30/03/2016 Substance No: 000000053184

Version: 1