

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DSP 014

Recommended Use of the Chemical Mineral flotation collector. and Restrictions on Use

Supplier: Ixom Operations Ptv Ltd

51 600 546 512 ABN:

Street Address: Level 8, 1 Nicholson Street

East Melbourne Victoria 3002

Australia

+61 3 9906 3000 **Telephone Number:**

Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Corrosion - Sub-category 1B Eye Damage - Category 1

SIGNAL WORD: DANGER



Hazard Statement(s):

H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P260 Do not breathe mist, vapours, spray. P264 Wash hands thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P363 Wash contaminated clothing before re-use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P405 Store locked up.

Product Name: DSP 014 Issued: 11/02/2020 Substance No: 000000006326



Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Other Hazards:

AUH031 Contact with acids liberates toxic gas.

Poisons Schedule (SUSMP): S5 Caution.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Phosphorodithioic acid, O,O-bis(1-methylethyl)ester,	27205-99-8	10-<30%	H314
sodium salt			
Phosphorodithioic acid, O,O-diethyl ester, sodium	3338-24-7	10-<30%	H314
salt			
Sodium hydroxide	1310-73-2	<5%	H290 H314 H318 H335
Ethyl alcohol	64-17-5	<5%	H225 H319
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Product Name: DSP 014 Issued: 11/02/2020 Substance No: 000000006326



Unsuitable Extinguishing Media:

Water jet.

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the chemical:

Combustible liquid. On burning will emit toxic fumes, including those of oxides of carbon, oxides of sulfur, and oxides of phosphorus. May form flammable vapour mixtures with air. Avoid all ignition sources. Corrosive chemical.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Take precautionary measures against static discharges. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Ethyl alcohol: 8hr TWA = $1880 \text{ mg/m}^3 (1000 \text{ ppm})$ Sodium hydroxide: Peak Limitation = 2 mg/m³

Product Name: DSP 014 Issued: 11/02/2020 Substance No: 000000006326



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

Peak Limitation - a maximum or peak airborne concentration of a particular substance determined over the shortest analytically practicable period of time which does not exceed 15 minutes.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.













Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Yellow to Dark Brown Colour:

Odour: Pungent

Miscible with water. Solubility:

Specific Gravity: Not available Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): Not available Flash Point (°C): Not available Not available Flammability Limits (%):

Product Name: DSP 014 Issued: 11/02/2020 Substance No: 000000006326



Autoignition Temperature (°C): Not available Boiling Point/Range (°C): Not available

:Ha 10-13

10. STABILITY AND REACTIVITY

Contact with acids liberates toxic gas. Reactivity:

Chemical stability: No information available.

Possibility of hazardous

reactions:

Reacts with mineral acids evolving flammable and toxic hydrogen sulfide gas.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame.

Incompatible materials: Incompatible with acids, oxidising agents, metals, organic chemicals.

Hazardous decomposition

products:

Oxides of carbon. Oxides of sulfur. Oxides of phosphorus.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and

chemical burns to the gastrointestinal tract.

A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Eye contact:

Contamination of eyes can result in permanent injury.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin

burns.

Breathing in vapour may produce respiratory irritation. Inhalation:

Acute toxicity: No LD50 data available for the product.

Skin corrosion/irritation: Corrosive. The product has not been tested; the classification is based on the

components of the mixture.

Corrosive. The product has not been tested; the classification is based on the Serious eye damage/irritation:

components of the mixture.

Respiratory or skin

sensitisation:

No information available.

Chronic effects: No information available for the product.

Aspiration hazard: No information available.

This product may liberate carbon disulfide on contact with moist skin. Chronic exposure to carbon disulfide may produce central and peripheral nervous system, cardiovascular, gastrointestinal, kidney, and eye disorders.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Product Name: DSP 014 Issued: 11/02/2020 Substance No: 000000006326



No information available. Persistence/degradability:

No information available. Bioaccumulative potential:

Mobility in soil: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No: 1719

Transport Hazard Class: 8 Corrosive

Packing Group: Ш

Proper Shipping Name or

CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID, O,O-BIS(1-METHYLETHYL)ESTER, SODIUM SALT AND SODIUM DIETHYL

DITHIOPHOSPHATE)

Hazchem or Emergency Action 2R

Code:

Marine Transport

Technical Name:

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1719

Transport Hazard Class: 8 Corrosive

Packing Group: Ш

Proper Shipping Name or CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID. **Technical Name:** O,O-BIS(1-METHYLETHYL)ESTER, SODIUM SALT AND SODIUM DIETHYL

DITHIOPHOSPHATE)

F-A **IMDG EMS Fire: IMDG EMS Spill:** S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1719

Transport Hazard Class: 8 Corrosive

Packing Group: Ш

Substance No: 000000006326

Product Name: DSP 014 Issued: 11/02/2020



Proper Shipping Name or Technical Name:

CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID, O,O-BIS(1-METHYLETHYL)ESTER, SODIUM SALT AND SODIUM DIETHYL

DITHIOPHOSPHATE)

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Corrosion - Sub-category 1B Eye Damage - Category 1

Hazard Statement(s):

H314 Causes severe skin burns and eye damage.

Poisons Schedule (SUSMP): S5 Caution.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason(s) for Issue:

5 Yearly Revised Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: DSP 014 Issued: 11/02/2020 Substance No: 000000006326 Version: 6

Page 7 of 7