

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** C5 / C9 PETROLEUM RESIN

Recommended Use of the Chemical Paints, adhesives, rubber, printing ink. and Restrictions on Use

Supplier: Ixom Operations Pty Ltd

ABN: 51 600 546 512

Street Address: Level 8, 1 Nicholson Street

East Melbourne Victoria 3002

Australia

+61 3 9906 3000 **Telephone Number:** 

**Emergency Telephone:** 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

### 2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS CHEMICAL.

Poisons Schedule (SUSMP): None allocated.

# 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Petroleum resins	64742-16-1	100%	-

# 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

#### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

#### **Skin Contact:**

If skin contact occurs, remove contaminated clothing and wash skin with soap and water. If irritation occurs, seek medical advice.

#### **Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Product Name: C5 / C9 PETROLEUM RESIN Issued: 25/05/2018 Substance No: 000000008669

Version: 2



Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES

#### Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

#### Specific hazards arising from the chemical:

Combustible solid.

#### Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## 6. ACCIDENTAL RELEASE MEASURES

#### **Emergency procedures/Environmental precautions:**

Shut off all possible sources of ignition. If contamination of sewers or waterways has occurred advise local emergency services.

#### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling:

Avoid skin and eye contact and breathing in dust. Wash hands thoroughly after handling. Launder contaminated clothing before reuse.

#### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store below 40°C. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for particulates:

#### Appropriate engineering controls:

Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Product Name: C5 / C9 PETROLEUM RESIN

Substance No: 00000008669

Issued: 25/05/2018 Version: 2



Version: 2

#### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.









Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Granular or Flakes

Colour: Yellow

Odour: Characteristic Insoluble in water.

Specific Gravity: 1.05-1.10
Relative Vapour Density (air=1): Not available
Vapour Pressure (20 °C): Not available
Flash Point (°C): 260 min
Flammability Limits (%): Not available
Autoignition Temperature (°C): Not available

Melting Point/Range (°C): 95-150 (Softening point)

pH: Not applicable

## 10. STABILITY AND REACTIVITY

**Reactivity:** No information available.

**Chemical stability:** Stable under normal conditions of use.

Possibility of hazardous

reactions:

No hazardous reactions when stored and handled correctly.

**Conditions to avoid:** Avoid exposure to heat, sources of ignition, and open flame.

**Incompatible materials:** Incompatible with strong oxidising agents.

**Hazardous decomposition** 

products:

Oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Product Name: C5 / C9 PETROLEUM RESIN Issued: 25/05/2018

Substance No: 00000008669



No adverse effects expected, however, large amounts may cause nausea and Ingestion:

vomiting.

**Eve contact:** May be an eye irritant. Exposure to the dust may cause discomfort due to

particulate nature. May cause physical irritation to the eyes.

Repeated or prolonged skin contact may lead to irritation. Skin contact:

Inhalation: Material may be irritant to the mucous membranes of the respiratory tract

(airways).

Acute toxicity:

Oral LD50 (rat): >5000 mg/kg

Chronic effects: No information available for the product.

Not classified. **Aspiration hazard:** 

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

# 13. DISPOSAL CONSIDERATIONS

#### Disposal methods:

Refer to Waste Management Authority. Normally suitable for incineration by an approved agent.

# 14. TRANSPORT INFORMATION

#### **Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

#### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

#### **Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

# 15. REGULATORY INFORMATION

### Classification:

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS CHEMICAL.

None allocated. Poisons Schedule (SUSMP):

This material is listed on the Australian Inventory of Chemical Substances (AICS).

### 16. OTHER INFORMATION

Product Name: C5 / C9 PETROLEUM RESIN Issued: 25/05/2018 Substance No: 000000008669

Version: 2



This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

#### Reason(s) for Issue:

Reissue of an obsolete SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: C5 / C9 PETROLEUM RESIN
Substance No: 00000008669
Issued: 25/05/2018
Version: 2