

SAFETY DATA SHEET



Revision date: 07-Oct-2022

Revision Number 2

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name WEST COAST 00189AA

Product Code(s) 000000025793

Other means of identification

UN number 1266

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Fragrances.

Uses advised against No information available.

Supplier

Ixom Operations Pty Ltd (Bronson & Jacobs division) - incorporated in Australia
ABN:51 600 546 512
70 Marple Avenue
Villawood NSW 2163
Australia

Telephone Number: +61 2 8717 2929

Facsimile: +61 2 9755 9611

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

Skin sensitization	Category 1B
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

SIGNAL WORD

Warning

Label elements

Flame

Exclamation mark

Environment

**Hazard statements**

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Avoid breathing dust / fume / gas / mist / vapours / spray

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting equipment

Use only non-sparking tools

Take action to prevent static discharges

Wash hands thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves / protective clothing / eye protection / face protection

Avoid release to the environment

Precautionary Statements - Response

Specific treatment (see First aid on this SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off immediately all contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Collect spillage

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

Toxic to aquatic life

May be harmful if swallowed

General Hazards

Poisons Schedule (SUSMP)

None allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Chemical name	CAS No.	Weight-%
Naphthalene, 2-acetyl-1,2,3,4,6,7,8-octahydro-2,3,8,8-tetramethyl-	54464-57-2	10-<30
3-Methyl butyl acetate	123-92-2	10-<30
1,6-Octadien-3-ol, 3,7-dimethyl- (Linalool)	78-70-6	10-<30
Diethyl phthalate	84-66-2	1-<10
Isobutyl acetate	110-19-0	1-<10
Cyclohexanol, 4-(1,1-dimethylethyl)-, acetate	32210-23-4	1-<10
Ethyl acetate	141-78-6	1-<10
Oxiranecarboxylic acid, 3-methyl-3-phenyl-, ethyl ester	77-83-8	1-<10
Methyl amyl ketone	110-43-0	1-<10
2-Propenoic acid, 3-phenyl-, methyl ester	103-26-4	1-<10
Ingredients determined not to be hazardous	-	to 100

4. FIRST AID MEASURES**Description of first aid measures****General advice**

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.

Inhalation

Remove to fresh air. Call a physician if symptoms occur.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation or rash occurs: Get medical advice/attention.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed**Symptoms**

Irritation. May cause redness and tearing of the eyes. May cause allergic skin reaction. Redness. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed**Note to physicians**

May cause sensitization by skin contact. Treat symptomatically.

5. FIRE FIGHTING MEASURES**Suitable Extinguishing Media****Suitable Extinguishing Media**

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Flammable. On burning will emit toxic fumes, including those of oxides of carbon. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Environmentally hazardous. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Oxides of carbon.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3Y

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes, and clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. Do not touch or walk through spilled material. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Shut off ignition sources. Clear area of all unprotected personnel. Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not allow to enter into soil/subsoil. Prevent product from entering drains. Refer to protective measures listed in Sections 7 and 8. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Remove ignition sources. Provide adequate ventilation. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Slippery when spilt. Avoid accidents, clean up immediately. Dam up. Soak up with inert absorbent material. Use non-sparking tools. Pick up and transfer to properly labelled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes, and clothing. Avoid breathing vapors or mists. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep in an area equipped with sprinklers. Take off contaminated clothing and wash before reuse. Wash thoroughly after handling. Use personal protection equipment. Use according to package label instructions.

General hygiene considerations Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes, and clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not store near combustible materials. Keep in an area equipped with sprinklers. Protect from direct sunlight. Keep in properly labelled containers. Store in accordance with local regulations. Store away from incompatible materials described in Section 10. Keep container closed when not in use.

Incompatible materials Oxidizing agents.

Poisons Schedule (SUSMP) None allocated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Diethyl phthalate: 8hr TWA = 5 mg/m³

Ethyl acetate: 8hr TWA = 720 mg/m³ (200 ppm), 15 min STEL = 1440 mg/m³ (400 ppm)

Isoamyl acetate (Isopentyl acetate): 8hr TWA = 270 mg/m³ (50 ppm), 15 min STEL = 541 mg/m³ (100 ppm)

Isobutyl acetate: 8hr TWA = 713 mg/m³ (150 ppm)

n-Amyl ketone (2-heptanone): 8hr TWA = 233 mg/m³ (50ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Apply technical measures to

comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.



Eye/face protection

Goggles.

Skin and body protection

Wear suitable protective clothing. Antistatic boots. Overalls.

Hand protection

Impervious gloves.

Respiratory protection

If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls

No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Clear
Color	Pale Yellow to Yellow
Odor	Fruity , Floral , Sweet , Musk
Odor threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash point	39 °C	CC (closed cup)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.937 - 0.957 @20°C	None known

Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information**10. STABILITY AND REACTIVITY**Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions Heating can cause expansion or decomposition of the material, which can lead to the containers exploding.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Static discharge (electrostatic discharge). Avoid contact with combustible substances. Direct sunlight.

Incompatible materials

Incompatible materials Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

11. TOXICOLOGICAL INFORMATIONAcute toxicityInformation on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation.

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation. May cause sensitization by skin contact.

Ingestion May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhoea.

Symptoms

Irritation. May cause redness and tearing of the eyes. May cause allergic skin reaction. Redness. Rashes. Hives.

Numerical measures of toxicity - Product Information

ATEmix (oral) >2000 mg/kg (calculated, based on data from components)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
3-Methyl butyl acetate	= 16600 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Diethyl phthalate	= 8600 mg/kg (Rat)	> 11200 mg/kg (Rat)	> 4.64 mg/L (Rat) 6 h
Isobutyl acetate	= 15400 mg/kg (Rat)	> 17400 mg/kg (Rabbit)	-
Ethyl acetate	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit) > 20 mL/kg (Rabbit)	= 4000 ppm (Rat) 4 h
Oxiranecarboxylic acid, 3-methyl-3-phenyl-, ethyl ester	= 5470 mg/kg (Rat)	-	-
Methyl amyl ketone	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12.6 mL/kg (Rabbit) = 12600 µL/kg (Rabbit)	2000 - 4000 ppm (Rat) 6 h
2-Propenoic acid, 3-phenyl-, methyl ester	= 2610 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Skin corrosion/irritation**

Causes skin irritation. Classification is based on mixture calculation methods based on component data.

Serious eye damage/eye irritation

Causes serious eye irritation. Classification is based on mixture calculation methods based on component data.

Respiratory or skin sensitization

May cause sensitization by skin contact. Classification is based on mixture calculation methods based on component data.

Germ cell mutagenicity

No information available.

Carcinogenicity

No information available.

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

No information available.

Aspiration hazard

No information available.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Ecotoxicity**

Toxic to aquatic life with long lasting effects. Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphthalene, 2-acetyl-1,2,3,4,6,7,8-octahydro-2,3,8,8-tetramethyl-	EC50 (72 h) - Scenedesmus subspicatus - 2.6 mg/L NOEC (72 h) - Scenedesmus subspicatus - 2.6 mg/L (1)	LC50 (96 h) - Lepomis macrochirus - 1.3 mg/L NOEC (30 days) - Danio rerio - 0.16 mg/L (1)	-	EC50 (48 h) - Daphnia magna - 1.38 mg/L NOEC (21 days) - Daphnia magna - 0.044 mg/L(1)
Diethyl phthalate	EC50: =23mg/L (72h, Desmodesmus subspicatus) EC50: =21mg/L (96h, Desmodesmus subspicatus) EC50: 42 - 255mg/L (72h, Pseudokirchneriella subcapitata) EC50: 2.11 - 4.29mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =17mg/L (96h, Pimephales promelas) LC50: =16.8mg/L (96h, Pimephales promelas) LC50: =22mg/L (96h, Lepomis macrochirus) LC50: =16.7mg/L (96h, Lepomis macrochirus) LC50: =12mg/L (96h, Oncorhynchus mykiss)	-	EC50: 36 - 74mg/L (48h, Daphnia magna) EC50: =86mg/L (48h, Daphnia magna)
Isobutyl acetate	-	LC50: =17mg/L (96h, Oryzias latipes) LC50: =101mg/L (48h, Leuciscus idus melanotus) LC50: 101 - 123mg/L (48h, Leuciscus idus melanotus)	-	EC50: =168mg/L (24h, Daphnia magna)
Cyclohexanol, 4-(1,1-dimethylethyl)-, acetate	-	LC50: =8.6mg/L (96h, Cyprinus carpio) LC50: =15.5mg/L (48h, Leuciscus idus)	-	EC50: =9.6mg/L (24h, Daphnia magna)
Ethyl acetate	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss)	-	EC50: =560mg/L (48h, Daphnia magna)
Oxiranecarboxylic acid, 3-methyl-3-phenyl-, ethyl ester	-	LC50: =4.2mg/L (96h, Oncorhynchus mykiss)	-	-
Methyl amyl ketone	-	LC50: 126 - 137mg/L (96h, Pimephales promelas)	-	-
2-Propenoic acid, 3-phenyl-, methyl ester	-	LC50: =2.76mg/L (96h, Danio rerio)	-	-

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
---------------	-----------------------

1,6-Octadien-3-ol, 3,7-dimethyl- (Linalool)	2.84 - 3.1
Diethyl phthalate	2.35
Isobutyl acetate	1.72
Methyl amyl ketone	1.98

Mobility

Mobility in soil No information available.

Other adverse effects**Endocrine Disruptor Information**

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Endocrine disrupting potential
Diethyl phthalate	Group III Chemical	-	-

13. DISPOSAL CONSIDERATIONS**Waste treatment methods**

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. TRANSPORT INFORMATION**ADG**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number 1266
Proper shipping name PERFUMERY PRODUCTS
Hazard class 3
Packing group III
Environmental hazard Yes
Special Provisions 223, 163
Hazchem code •3Y

IATA

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 1266
UN proper shipping name PERFUMERY PRODUCTS
Transport hazard class(es) 3
Packing group III

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 1266
UN proper shipping name PERFUMERY PRODUCTS
Transport hazard class(es) 3
Packing group III
IMDG EMS Fire F-E
IMDG EMS Spill S-D
Marine pollutant Yes

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III

Threshold quantity (T)

50 000

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
3-Methyl butyl acetate - 123-92-2	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Isobutyl acetate - 110-19-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Ethyl acetate - 141-78-6	10 tonne/yr Threshold category 1
Methyl amyl ketone - 110-43-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories**AIC**

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.

Legend:

AIC - Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Reason(s) For Issue: 5 Yearly Revised Primary SDS

Issuing Date: 07-Oct-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 Japan GHS Classification
 Australian Industrial Chemicals Introduction Scheme (AICIS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 RTECS (Registry of Toxic Effects of Chemical Substances)
 World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Bronson & Jacobs representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Bronson and Jacobs incorporating the businesses of Woods and Woods and Keith Harris and Australian Botanical Products.

End of Safety Data Sheet