

SAFETY DATA SHEET



Revision date: 25-Nov-2020

Revision Number 1

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name BLUEBERRY FLAVOUR NAT DC E49191 (FABLU49191)

Product Code(s) 000000026440

Other means of identification

Proper shipping name EXTRACTS, FLAVOURING, LIQUID

UN number 1197

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Flavour.

Uses advised against No information available.

Supplier

Ixom Operations Pty Ltd (Bronson & Jacobs division) - incorporated in Australia

ABN:51 600 546 512

70 Marple Avenue

Villawood NSW 2163

Australia

Telephone Number: +61 2 8717 2929

Facsimile: +61 2 9755 9611

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids

Category 3 - (H226)

SIGNAL WORD

Warning

Label elements

Flame



Hazard statements

H226 - Flammable liquid and vapor

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical, ventilating, lighting equipment

Wear protective gloves / protective clothing / eye protection / face protection

Precautionary Statements - Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Poisons Schedule (SUSMP) None allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%
Propylene glycol	57-55-6	>60
Ethyl acetate	141-78-6	0.1-<1
Isobutyl acetate	110-19-0	0.1-<1
Non-hazardous ingredients	Proprietary	Balance

4. FIRST AID MEASURES

Description of first aid measures

Emergency telephone number

Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Inhalation

Remove to fresh air. Call a physician if symptoms occur.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

	eye wide open while rinsing. Do not rub affected area. Get medical attention if symptoms occur.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention if symptoms occur.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code 3Y

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information	Ventilate the area.
For emergency responders	Use personal protection recommended in Section 8.
<u>Environmental precautions</u>	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
<u>Methods and material for containment and cleaning up</u>	
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
Incompatible materials	Oxidizing agents.
Poisons Schedule (SUSMP)	None allocated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits	No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):
------------------------	--

Chemical name	Australia	ACGIH TLV
Propylene glycol 57-55-6	8hr TWA = 474 mg/m ³ (150 ppm) 8hr TWA = 10 mg/m ³ (particulates only)	
Ethyl acetate 141-78-6	8hr TWA = 720 mg/m ³ (200 ppm) 15 min STEL = 1440 mg/m ³ (400 ppm)	

Isobutyl acetate 110-19-0	8hr TWA: 713 mg/m ³ (150 ppm)	STEL: 150 ppm TWA: 50 ppm
------------------------------	--	------------------------------

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls

Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



Eye/face protection

Glasses.

Skin and body protection

Wear suitable protective clothing. Antistatic boots. Overalls.

Hand protection

Impervious gloves.

Respiratory protection

If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls

No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available.
Color	Colourless to Pale Yellow
Odor	Sweet Blueberry
Odor threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash point	55 °C	CC (closed cup)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.0126 - 1.0526	@ 20 °C
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

10. STABILITY AND REACTIVITY

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information	No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:
Inhalation	May cause irritation of respiratory tract. Specific test data for the substance or mixture is not available.
Eye contact	May cause irritation. Specific test data for the substance or mixture is not available.
Skin contact	May cause irritation. Specific test data for the substance or mixture is not available.
Ingestion	May cause gastrointestinal discomfort if consumed in large amounts. Specific test data for the substance or mixture is not available.
Symptoms	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5,000 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propylene glycol	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
Ethyl acetate	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit) > 20 mL/kg (Rabbit)	= 4000 ppm (Rat) 4 h
Isobutyl acetate	= 15400 mg/kg (Rat)	> 17400 mg/kg (Rabbit)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Propylene glycol	EC50: =19000mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =51600mg/L (96h, Oncorhynchus mykiss) LC50: 41 - 47mL/L (96h, Oncorhynchus mykiss) LC50: =51400mg/L (96h, Pimephales promelas) LC50: =710mg/L (96h, Pimephales promelas)	-	EC50: >1000mg/L (48h, Daphnia magna) EC50: >10000mg/L (24h, Daphnia magna)
Ethyl acetate	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss)	-	EC50: =560mg/L (48h, Daphnia magna)
Isobutyl acetate	-	LC50: =17mg/L (96h, Oryzias latipes) LC50: =101mg/L (48h, Leuciscus idus melanotus) LC50: 101 - 123mg/L (48h, Leuciscus idus melanotus)	-	EC50: =168mg/L (24h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient
Ethyl acetate	0.6
Isobutyl acetate	1.72

Mobility

Mobility in soil No information available.

Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

ADG

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number	1197
Proper shipping name	EXTRACTS, FLAVOURING, LIQUID
Hazard class	3
Packing group	III
Hazchem code	3Y

IATA

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number	1197
UN proper shipping name	EXTRACTS, FLAVOURING, LIQUID
Transport hazard class(es)	3
Packing group	III

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number	1197
UN proper shipping name	EXTRACTS, FLAVOURING, LIQUID
Transport hazard class(es)	3
Packing group	III
IMDG EMS Fire	F-E
IMDG EMS Spill	S-D

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III

Threshold quantity (T)
50 000

Chemical name	National pollutant inventory
Propylene glycol - 57-55-6	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Ethyl acetate - 141-78-6	10 tonne/yr Threshold category 1
Isobutyl acetate - 110-19-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AICS

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.

Legend:

- Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Reason(s) For Issue: First Issue Primary SDS

Issuing Date: 25-Nov-2020

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australian Industrial Chemicals Introduction Scheme (AICIS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
RTECS (Registry of Toxic Effects of Chemical Substances)
World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Bronson & Jacobs representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Bronson and Jacobs incorporating the businesses of Woods and Woods and Keith Harris.

End of Safety Data Sheet