

SAFETY DATA SHEET



Revision date: 19-Apr-2022

Revision Number 1

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name FRAGRANCE BRAZIL (FAIA01292AB)

Product Code(s) 000000026770

Other means of identification

UN number 3082

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Fragrances.

Uses advised against No information available.

Supplier

Ixom Operations Pty Ltd (Bronson & Jacobs division) - incorporated in Australia
ABN:51 600 546 512
70 Marple Avenue
Villawood NSW 2163
Australia

Telephone Number: +61 2 8717 2929

Facsimile: +61 2 9755 9611

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

| | |
|-----------------------------------|------------|
| Flammable liquids | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Skin sensitization | Category 1 |
| Acute aquatic toxicity | Category 2 |
| Chronic aquatic toxicity | Category 2 |

SIGNAL WORD

Warning

Label elements

Environment

Exclamation mark

**Hazard statements**

H227 - Combustible liquid

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Avoid breathing dust / fume / gas / mist / vapours / spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves / protective clothing / eye protection / face protection

Wash hands thoroughly after handling

Avoid release to the environment

Precautionary Statements - Response

Specific treatment (see First aid on this SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Take off contaminated clothing and wash it before reuse

In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Collect spillage

Precautionary Statements - Storage

Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to aquatic life with long lasting effects

May be harmful if swallowed

Poisons Schedule (SUSMP)

None allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Chemical name | CAS No. | Weight-% |
|---|------------|----------|
| 3-Buten-2-one, 3-methyl-4-(2,6,6-trimethyl-2-cyclohexen-1-yl)- (Isomethyl-.alpha.-ionone) | 127-51-5 | 10-<30 |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 1-<10 |
| Galaxolide | 1222-05-5 | 1-<10 |
| Benzyl salicylate | 118-58-1 | 1-<10 |
| 1,6-Octadien-3-ol, 3,7-dimethyl- (Linalool) | 78-70-6 | 1-<10 |
| 2,6-ditertbutylhydroxytoluene | 128-37-0 | 1-<10 |
| .alpha.-Hexylcinnamaldehyde | 101-86-0 | 1-<10 |
| Orange, sweet, extract | 8028-48-6 | 1-<10 |
| 1,3-Benzodioxole-5-carboxaldehyde (Heliotropine) | 120-57-0 | 1-<10 |
| Ingredients determined not to be hazardous | - | to 100 |

4. FIRST AID MEASURES**Description of first aid measures**

| | |
|-----------------------|---|
| General advice | For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. |
| Inhalation | Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Call a physician if symptoms occur. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms occur. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation or rash occurs: Get medical advice/attention. |
| Ingestion | Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Consult a physician if necessary. |

Most important symptoms and effects, both acute and delayed

| | |
|-----------------|--|
| Symptoms | Irritation. May cause redness and tearing of the eyes. May cause allergic skin reaction. Redness. Rashes. Hives. |
|-----------------|--|

Indication of any immediate medical attention and special treatment needed

| | |
|---------------------------|---|
| Note to physicians | May cause sensitization by skin contact. Treat symptomatically. |
|---------------------------|---|

5. FIRE FIGHTING MEASURES**Suitable Extinguishing Media**

| | |
|-------------------------------------|---|
| Suitable Extinguishing Media | Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used. |
|-------------------------------------|---|

| | |
|---------------------------------------|---------------------------|
| Unsuitable extinguishing media | No information available. |
|---------------------------------------|---------------------------|

Specific hazards arising from the chemical

Specific hazards arising from the chemical Combustible liquid. On burning will emit toxic fumes, including those of oxides of carbon. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Oxides of carbon.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3Z

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid contact with skin, eyes, and clothing. Use personal protective equipment as required. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Shut off ignition sources. Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Remove ignition sources. Provide adequate ventilation. Do not touch or walk through spilled material. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid contact with skin, eyes, and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Handle in accordance with good industrial hygiene and safety practice. Use according to package label instructions.

General hygiene considerations Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes, and clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Store away from incompatible materials described in Section 10. Keep container closed when not in use.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Incompatible materials Strong acids. alkalis. Oxidizing agents.

Poisons Schedule (SUSMP) None allocated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

2,6-Di-tert-butyl-p-cresol: 8hr TWA = 10 mg/m³
Dipropylene glycol, methyl ether: 8hr TWA = 308 mg/m³ (50 ppm), Sk

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

`Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. The exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.



| | |
|--|--|
| Eye/face protection | Goggles. |
| Skin and body protection | Wear suitable protective clothing. Overalls. Boots. |
| Hand protection | Impervious gloves. |
| Respiratory protection | If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. |
| Environmental exposure controls | No information available. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|-----------------------|--------------------------------|
| Physical state | Liquid |
| Appearance | Clear free from sedimentation |
| Color | Pale Yellow to Yellow |
| Odor | Citrus , Floral , Sweet , Musk |
| Odor threshold | No information available. |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|---|----------------------|-------------------------|
| pH | No data available | None known |
| pH (as aqueous solution) | No data available | None known |
| Melting point / freezing point | No data available | None known |
| Boiling point / boiling range | No data available | None known |
| Flash point | 85 °C | CC (closed cup) |
| Evaporation rate | No data available | None known |
| Flammability (solid, gas) | No data available | None known |
| Flammability Limit in Air | | None known |
| Upper flammability or explosive limits | No data available | |
| Lower flammability or explosive limits | No data available | |
| Vapor pressure | No data available | None known |
| Vapor density | No data available | None known |
| Relative density | 0.9920- 1.0120 @20°C | None known |
| Water solubility | No data available | None known |
| Solubility(ies) | No data available | None known |
| Partition coefficient | No data available | None known |
| Autoignition temperature | No data available | None known |
| Decomposition temperature | No data available | None known |
| Kinematic viscosity | No data available | None known |
| Dynamic viscosity | No data available | None known |

Other information

| | |
|-------------------------|-----------------------|
| Refractive Index | 1.4809 - 1.5009 @20°C |
|-------------------------|-----------------------|

10. STABILITY AND REACTIVITY

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Static discharge (electrostatic discharge). Direct sunlight.

Incompatible materials

Incompatible materials Strong acids. alkalis. Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation.

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation. May cause sensitization by skin contact.

Ingestion May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms Irritation. May cause redness and tearing of the eyes. May cause allergic skin reaction. Redness. Rashes. Hives.

Numerical measures of toxicity - Product Information

ATEmix (oral) >2000 mg/kg

ATEmix (dermal) >5000 mg/kg

Numerical measures of toxicity - Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------|-----------|-------------|-----------------|
|---------------|-----------|-------------|-----------------|

| | | | |
|---|----------------------|-------------------------|----------------------|
| 3-Buten-2-one, 3-methyl-4-(2,6,6-trimethyl-2-cy clohexen-1-yl)- (Isomethyl-.alpha.-ionone) | > 5000 mg/kg (Rat) | > 5000 mg/kg (Rabbit) | - |
| Dipropylene glycol monomethyl ether | = 5350 mg/kg (Rat) | = 9500 mg/kg (Rabbit) | - |
| Galaxolide | > 3250 mg/kg (Rat) | > 3250 mg/kg (Rabbit) | - |
| Benzyl salicylate | = 2227 mg/kg (Rat) | > 5000 mg/kg (Rabbit) | - |
| 1,6-Octadien-3-ol, 3,7-dimethyl- (Linalool) | = 2790 mg/kg (Rat) | = 5610 mg/kg (Rat) | - |
| 2,6-ditertbutylhydroxytoluene | > 890 mg/kg (Rat) | > 2000 mg/kg (Rat) | - |
| .alpha.-Hexylcinnamaldehyde | = 3100 mg/kg (Rat) | > 3000 mg/kg (Rabbit) | > 5 mg/L (Rat) 4 h |
| 1,3-Benzodioxole-5-carboxalde hyde (Heliotropine) | = 2700 mg/kg (Rat) | > 5000 mg/kg (Rat) | - |

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|--|--|
| Skin corrosion/irritation | Causes skin irritation. Classification is based on mixture calculation methods based on component data. |
| Serious eye damage/eye irritation | Causes serious eye irritation. Classification is based on mixture calculation methods based on component data. |
| Respiratory or skin sensitization | May cause sensitization by skin contact. Classification is based on mixture calculation methods based on component data. |
| Germ cell mutagenicity | No information available. |
| Carcinogenicity | No information available. |
| Reproductive toxicity | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Aspiration hazard | No information available. |

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Toxic to aquatic life with long lasting effects. Keep out of waterways.

| Chemical name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea |
|---|------------------------------------|---|----------------------------|--------------------------------------|
| Dipropylene glycol monomethyl ether | - | LC50: >10000mg/L (96h, Pimephales promelas) | - | LC50: =1919mg/L (48h, Daphnia magna) |
| Benzyl salicylate | - | LC50: =1.03mg/L (96h, Danio rerio) | - | - |
| 1,6-Octadien-3-ol, 3,7-dimethyl- (Linalool) | EC50: =88.3mg/L (96h, Desmodesmus) | LC50: =27.8mg/L (96h, Oncorhynchus mykiss) | - | EC50: =20mg/L (48h, Daphnia magna) |

| | | | | |
|--|--|---|---|---|
| | subspicatus) | LC50: 22 - 46mg/L (96h, Leuciscus idus) | | |
| 2,6-diterbutylhydroxytoluene | EC50: =6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >0.42mg/L (72h, Desmodium subspicatus) | LC50: =5mg/L (48h, Oryzias latipes) | - | - |
| 1,3-Benzodioxole-5-carboxaldehyde (Heliotropine) | - | LC50: =2.5mg/L (96h, Cyprinus carpio) | - | - |

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

| Chemical name | Partition coefficient |
|---|-----------------------|
| Dipropylene glycol monomethyl ether | -0.064 |
| 1,6-Octadien-3-ol, 3,7-dimethyl- (Linalool) | 2.84 - 3.1 |
| 2,6-diterbutylhydroxytoluene | 4.17 |

Mobility

Mobility in soil No information available.

Other adverse effects**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION**ADG**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number 3082
Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS GALAXOLIDE AND BUTYLATED HYDROXYTOLUENE)
Hazard class 9
Packing group III
Environmental hazard Yes
Special Provisions 274, 331, 335, 375, AU01
Hazchem code •3Z

IATA

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations

for transport by air; DANGEROUS GOODS.

UN number 3082
UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS GALAXOLIDE AND BUTYLATED HYDROXYTOLUENE)
Transport hazard class(es) 9
Packing group III

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 3082
UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS GALAXOLIDE AND BUTYLATED HYDROXYTOLUENE)
Transport hazard class(es) 9
Packing group III
IMDG EMS Fire F-A
IMDG EMS Spill S-F
Marine pollutant Yes

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

National pollutant inventory

Subject to reporting requirement

| Chemical name | National pollutant inventory |
|--|---|
| Dipropylene glycol monomethyl ether - 34590-94-8 | 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total |

International Inventories

AIIC All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.

Legend:

AIIIC - Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION**Reason(s) For Issue:** First Issue Primary SDS**Issuing Date:** 19-Apr-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

| | | | |
|---------|-----------------------------|------|----------------------------------|
| TWA | TWA (time-weighted average) | STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value | * | Skin designation |
| C | Carcinogen | | |

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 Japan GHS Classification
 Australian Industrial Chemicals Introduction Scheme (AICIS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 RTECS (Registry of Toxic Effects of Chemical Substances)
 World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Bronson & Jacobs representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Bronson and Jacobs incorporating the businesses of Woods and Woods and Keith Harris and Australian Botanical Products.

End of Safety Data Sheet