SAFETY DATA SHEET

Revision date: 13-Jul-2022

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier		
Product Name	CARAMEL ADDICTION NATURAL E47942 (FACAR47942)	
Product Code(s)	00000038563	
Other means of identification		
UN number	1197	
Recommended use of the chemical	and restrictions on use	
Recommended use	Flavour.	
Uses advised against	No information available.	
Supplier Ixom Operations Pty Ltd (Bronson & Jacobs division) - incorporated in Australia ABN:51 600 546 512 70 Marple Avenue Villawood NSW 2163 Australia Telephone Number: +61 2 8717 2929 Facsimile: +61 2 9755 9611		
Emergency telephone number		

Emergency telephone number 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 3
Serious eye damage/eye irritation	Category 2

SIGNAL WORD Warning



Label elements



Hazard statements H226 - Flammable liquid and vapor H319 - Causes serious eye irritation

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical, ventilating, lighting equipment Use only non-sparking tools Take precautionary measures against static discharge Wash hands thoroughly after handling Wear protective gloves / protective clothing / eye protection / face protection **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.
Precautionary Statements - Storage
Store in a well-ventilated place. Keep cool
Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

. . . .

Other hazards which do not result in classification Causes mild skin irritation

Poisons Schedule (SUSMP) None allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>

Contains propylene glycol.

Chemical name	CAS No.	Weight-%
Ethyl alcohol (Ethanol)	64-17-5	10-<30
Aromatic aldehyde(s)	-	1-<10
Aliphatic acid(s)	-	0.1-<1
Flavour ingredients at non-hazardous	-	to 100
concentrations		

4. FIRST AID MEASURES

Description of first aid measures

General advice	For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor.	
Inhalation	Remove to fresh air. Call a physician if symptoms occur.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. Get medical attention if symptoms occur.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician if symptoms occur.	
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention if symptoms occur.	
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	Irritation. May cause redness and tearing of the eyes.	
Indication of any immediate medicate	al attention and special treatment needed	
Note to physicians	Treat symptomatically.	
5. FIRE FIGHTING MEASURES		
Suitable Extinguishing Media		
Suitable Extinguishing Media Suitable Extinguishing Media	Foam. Carbon dioxide (CO2). Dry chemical.	
Suitable Extinguishing Media	Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient.	
Suitable Extinguishing Media Unsuitable extinguishing media	Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient.	
Suitable Extinguishing Media Unsuitable extinguishing media <u>Specific hazards arising from the c</u> Specific hazards arising from the	Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient. hemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local	
Suitable Extinguishing Media Unsuitable extinguishing media <u>Specific hazards arising from the c</u> Specific hazards arising from the chemical	 Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient. hemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Oxides of carbon. 	
Suitable Extinguishing Media Unsuitable extinguishing media <u>Specific hazards arising from the c</u> Specific hazards arising from the chemical Hazardous combustion products	 Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient. hemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Oxides of carbon. 	
Suitable Extinguishing Media Unsuitable extinguishing media <u>Specific hazards arising from the c</u> Specific hazards arising from the chemical Hazardous combustion products <u>Special protective actions for fire-f</u> Special protective equipment for	Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient. hemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Oxides of carbon. ighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout	
Suitable Extinguishing Media Unsuitable extinguishing media <u>Specific hazards arising from the c</u> Specific hazards arising from the chemical Hazardous combustion products <u>Special protective actions for fire-f</u> <u>Special protective equipment for</u> fire-fighters	Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient. hemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Oxides of carbon. ighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. 3Y	
Suitable Extinguishing Media Unsuitable extinguishing media Specific hazards arising from the constraints of the second s	Foam. Carbon dioxide (CO2). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient. hemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. In the event of fire, cool tanks with water spray. Runoff may create fire or explosion hazard. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Oxides of carbon. ighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. 3Y	

Personal precautions

	adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.	
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.	
For emergency responders	Shut off ignition sources. Clear area of all unprotected personnel. Use personal protection recommended in Section 8.	
Environmental precautions		
Environmental precautions	Prevent further leakage or spillage if safe to do so. Refer to protective measures listed in Sections 7 and 8. Prevent product from entering drains.	
Methods and material for containment and cleaning up		
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.	
Methods for cleaning up	Slippery when spilt. Avoid accidents, clean up immediately. Take precautionary measures against static discharges. Use non-sparking tools. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.	

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.
Conditions for safe storage, includ	ing any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Protect from direct sunlight. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
Incompatible materials	Oxidizing agents.
Poisons Schedule (SUSMP)	None allocated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Ethyl alcohol (Ethanol): 8hr TWA = 1880 mg/m³ (1000 ppm) Propane-1,2-diol (propylene glycol) (total: vapour & particulates): 8hr TWA = 474 mg/m³ (150 ppm); (particulates only): 8hr TWA = 10 mg/m³

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

 Engineering controls
 Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

 If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Eye/face protection	Goggles.
Skin and body protection	Wear suitable protective clothing. Antistatic boots. Overalls.
Hand protection	Impervious gloves.
Respiratory protection	If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.
Environmental exposure controls	No information available.

Revision Number 4

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state
Appearance
Color
Odor
Odor threshold

Values Property pН No data available pH (as aqueous solution) No data available Melting point / freezing point No data available Boiling point / boiling range No data available Flash point 36 °C **Evaporation rate** No data available Flammability (solid, gas) No data available Flammability Limit in Air Upper flammability or explosive No data available limits Lower flammability or explosive No data available limits Vapor pressure No data available Vapor density No data available **Relative density** 0.9976 - 1.0176 @ 20°C Water solubility No data available Solubility(ies) Miscible in water Partition coefficient No data available Autoignition temperature No data available No data available **Decomposition temperature** Kinematic viscosity No data available Dynamic viscosity No data available

Liquid Clear Pale Yellow to Yellow Characteristic Caramel No information available.

None known None known None known None known CC (closed cup) None known None known

None known

None known

Remarks • Method

Other information

10. STABILITY AND REACTIVITY

Reactivity		
Reactivity	No information available.	
Chemical stability		
Stability	Stable under normal conditions.	
Explosion data Sensitivity to mechanical impact None.		
Sensitivity to static discharge	Yes.	
Possibility of hazardous reactions		
Possibility of hazardous reactions	Heating can cause expansion or decomposition of the material, which can lead to the containers exploding.	
Conditions to avoid		
Conditions to avoid	Heat, flames and sparks. Static discharge (electrostatic discharge). Avoid contact with	

combustible substances. Direct sunlight.

Incompatible materials

Incompatible materials Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information	No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:
Inhalation	May cause irritation.
Eye contact	Causes serious eye irritation.
Skin contact	Causes mild skin irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. May cause gastrointestinal discomfort if consumed in large amounts.
Symptoms	Irritation. May cause redness and tearing of the eyes.
Numerical measures of toxicity - Product Information	

ATEmix (oral) >5,000 mg/kg (calculated, based on data from components)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl alcohol (Ethanol)	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	Causes serious eye irritation. Classification is based on mixture calculation methods based on component data.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.

STOT - repeated exposure

No information available.

Aspiration hazard

No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity

Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethyl alcohol (Ethanol)	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)		LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna) EC50: =10800mg/L (24h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation

No information available.

Component Information

Chemical name	Partition coefficient
Ethyl alcohol (Ethanol)	-0.32

Mobility

Mobility in soil No information available.

Other adverse effects

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

<u>ADG</u>

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and

Revision Number 4

Rail; DANGEROUS GOODS.	
UN number	1197
Proper shipping name	EXTRACTS, FLAVOURING, LIQUID
Hazard class	3
Packing group	III
Special Provisions	223
Hazchem code	3Y

<u>IATA</u>

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number	1197
UN proper shipping name	EXTRACTS, FLAVOURING, LIQUID
Transport hazard class(es)	3
Packing group	III

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number	1197
UN proper shipping name	EXTRACTS, FLAVOURING, LIQUID
Transport hazard class(es)	3
Packing group	III
IMDG EMS Fire	F-E
IMDG EMS Spill	S-D

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

Major hazard (accident/incident planning) regulation

Verify that license requirements are met <u>Hazardous chemical</u> Liquids that meet the criteria for Class 3 Packing Group II or III

Threshold quantity (T) 50 000

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Ethyl alcohol (Ethanol) - 64-17-5	10 tonne/yr Threshold category 1

International Inventories

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals or are regulated through the Food Standards Australia New Zealand (FSANZ).

Legend:

AIIC - Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Reason(s) For Issue: 5 Yearly Revised Primary SDS

Issuing Date: 13-Jul-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Sect	ion 8: EXPOSURE CONTROLS/PERSONAL	_ PROTECTION	
TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
С	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s)) U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act U.S. Environmental Protection Agency High Production Volume Chemicals Food Research Journal Hazardous Substance Database International Uniform Chemical Information Database (IUCLID) Japan GHS Classification Australian Industrial Chemicals Introduction Scheme (AICIS) NIOSH (National Institute for Occupational Safety and Health) National Library of Medicine's ChemID Plus (NLM CIP) National Library of Medicine's PubMed database (NLM PUBMED) National Toxicology Program (NTP) New Zealand's Chemical Classification and Information Database (CCID) Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program Organization for Economic Co-operation and Development Screening Information Data Set RTECS (Registry of Toxic Effects of Chemical Substances) World Health Organization

<u>Disclaimer</u>

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and

control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Bronson & Jacobs representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Bronson and Jacobs incorporating the businesses of Woods and Woods and Keith Harris and Australian Botanical Products.

End of Safety Data Sheet