SAFETY DATA SHEET



Revision date: 30-Oct-2023

Revision Number 3

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name STEPANQUAT 65

Product Code(s) 000000050145

Other means of identification

UN number 3286

Recommended use of the chemical and restrictions on use

Recommended use Surfactant.

For industrial use only.

Uses advised against No information available

Supplier

Ixom Operations Pty Ltd ABN: 51 600 546 512 Level 8, 1 Nicholson Street Melbourne 3000 Australia

Telephone Number: +61 3 9906 3000

Emergency telephone number

Emergency telephone number 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 3
Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 2
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1

SIGNAL WORD

Danger

Label elements

Flame

Skull and crossbones

Corrosion

Environment



Hazard statements

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H330 - Fatal if inhaled

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Do not breathe mist, vapours, spray.

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves / protective clothing / eye protection / face protection

Wear respiratory protection

Avoid release to the environment

Precautionary Statements - Response

Specific treatment is urgent (see First aid on this SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Collect spillage

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

General Hazards

Poisons Schedule (SUSMP) 6

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%
Quaternary ammonium compounds,	63449-41-2	30-60
benzyl-C8-18-alkyldimethyl, chlorides		
Ethyl alcohol (Ethanol)	64-17-5	1-<10
Non hazardous component(s)	-	to 100

4. FIRST AID MEASURES

Description of first aid measures

General advice For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New

Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. Do not

use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Immediate medical attention is required.

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Get

immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms Irritation/Corrosion. May cause redness and tearing of the eyes. Erythema (skin redness).

Burning.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. Can cause corneal burns. Probable mucosal damage may

contraindicate the use of gastric lavage.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal

protein foam can be used.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Corrosive. Flammable. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Pay attention to flashback.

Vapors may form explosive mixture with air. Environmentally hazardous.

Hazardous combustion products

Carbon monoxide. Carbon dioxide (CO2). Low molecular weight hydrocarbons.

Special protective actions for fire-fighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

Hazchem code •3WE

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Attention! Corrosive material. Avoid contact with skin, eyes, and clothing. Do not breathe vapor or mist. Do not touch or walk through spilled material. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Evacuate personnel to safe areas. Pay attention to flashback. Stop leak if you can do it without risk. Use personal protective equipment as required. Wash thoroughly after handling. Wear protective gloves/protective

clothing and eye/face protection.

For emergency responders

Personal precautions

Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Dike far ahead of liquid spill for later disposal. Stop leak if you can do it without risk.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use only non-sparking tools. After cleaning, flush

away traces with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes, and clothing. Do not breathe vapor or mist. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond all lines and equipment associated with product system. All equipment should be

non-sparking. All equipment may need to be explosion-proof based on a risk assessment.

Take precautionary measures against static discharges. Keep in an area equipped with sprinklers. Use personal protection equipment. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from foodstuffs and sources of heat or ignition. Keep container closed when not in use.

This material is a Scheduled Poison and must be stored, maintained and used in

accordance with the relevant regulations.

Incompatible materials Strong oxidizing agents. Anionic surfactants.

Poisons Schedule (SUSMP) 6

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace

Exposure Standard(s) for constituent(s):

Ethyl alcohol (Ethanol): 8hr TWA = 1880 mg/m³ (1000 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls

Ensure that eyewash stations and safety showers are close to the workstation location. Apply technical measures to comply with the occupational exposure limits. Ventilation systems.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, RUBBER BOOTS, AIR MASK, GLOVES (Long), APRON.











Eye/face protection

Tight sealing safety goggles. If splashes are likely to occur:. Face protection shield.

Skin and body protection

Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.

Overalls.

Hand protection Elbow-length impervious gloves.

Respiratory protection If determined by a risk assessment an inhalation risk exists, wear an air supplied respirator

meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available Color No information available No information available Odor **Odor threshold** No information available

Property Values Remarks • Method

6.2-8 (10% in water) pН

No data available pH (as aqueous solution) None known

Melting point / freezing point No data available Boiling point / boiling range No data available

Flash point 56.1 °C Pensky-Martens Closed Cup (PMCC)

Evaporation rate No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available None known Vapor density >1 (estimated) (air=1) None known

0.97 @25°C Relative density Water solubility No data available

Solubility(ies) No data available None known Partition coefficient None known No data available **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** 60 cP @25°C None known

Other information

Pour Point -3.89°C

10. STABILITY AND REACTIVITY

Reactivity

Reactivity Non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials

Incompatible materials Strong oxidizing agents. Anionic surfactants.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO2). Low molecular weight hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this

Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the

chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation. Fatal if inhaled.

Eye contact Corrosive to the eyes and may cause severe damage including blindness.

Skin contact Causes severe burns.

Ingestion Can burn mouth, throat, and stomach. Harmful if swallowed.

Symptoms Irritation/Corrosion. May cause redness and tearing of the eyes. Erythema (skin redness).

Burning.

Numerical measures of toxicity - Product Information

On basis of test data

 Oral LD50
 > 500 mg/kg (rat)

 Dermal LD50
 > 2000 mg/kg (rabbit)

 Inhalation LC50
 0.054-0.51 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Ethyl alcohol (Ethanol)	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4h	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes severe burns.

Serious eye damage/eye irritation Causes serious eye damage.

000000050145 - STEPANQUAT 65

Revision date: 30-Oct-2023 Revision Number 3

Respiratory or skin sensitization Not a respiratory sensitizer.

Germ cell mutagenicity No information available.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

(OSHA - Occupational Safety and Health Administration) (IARC - International Agency for Research on Cancer)

(NTP - National Toxicology Program).

Reproductive toxicity No information available.

STOT - single exposure

Not classified.

STOT - repeated exposure

Not classified.

Aspiration hazard

Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Keep out of waterways. Very toxic to aquatic life with long lasting effects.

EC50 Algae 0.063 mg/L 72 hours EC50 Daphnia 0.016 mg/L, 48 hours LC50 Fish 0.028 mg/L, 96 hours.

Persistence and degradability

Persistence and degradability Readily biodegradable.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Ethyl alcohol (Ethanol)	-0.32

Mobility

Mobility in soil No information available.

Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packagingDo not reuse empty containers. Empty containers pose a potential fire and explosion

hazard. Do not cut, puncture or weld containers. Empty containers should be taken to an

approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

ADG

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and

Rail; DANGEROŬS GOODS.

UN number 3286

Proper shipping name FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (CONTAINS ETHANOL AND

ALKYLDIMETHYLBENZYL AMMONIUM CHLORIDE)

Hazard class 3
Subsidiary hazard class 6.1
Subsidiary hazard class 2
Packing group II
Hazchem code •3WE

<u>IATA</u>

UN number 3286

UN proper shipping name FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (CONTAINS ETHANOL AND

ALKYLDIMETHYLBENZYL AMMONIUM CHLORIDE)

Transport hazard class(es) 3
Subsidiary hazard class 6.1
Subsidiary hazard class 2
Packing group

IMDG

UN number 3286

UN proper shipping name FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (CONTAINS ETHANOL AND

ALKYLDIMETHYLBENZYL AMMONIUM CHLORIDE) MARINE POLLUTANT

Transport hazard class(es)

Subsidiary hazard class

Subsidiary hazard class 2

Packing group

IMDG EMS Fire

IMDG EMS Spill

S-C

Marine pollutant

S 3

6.1

8

6.2

8

F-E

MCG EMS Spill

S-C

Yes

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule (SUSMP) 6

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Ethyl alcohol (Ethanol) - 64-17-5	10 tonne/yr Threshold category 1

International Inventories

All the constituents of this material are listed on the Australian Inventory of Industrial

Chemicals.

Legend:

AIIC- Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Supplier Safety Data Sheet 06/2023

STEPANQUAT is a registered trademark of Stepan Company

Reason(s) For Issue: Reissue of an obsolete SDS

Change to Product Name

Issuing Date: 30-Oct-2023

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
TWA TWA (time-weighted average) STEL

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

C Carcinogen

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian Industrial Chemicals Introduction Scheme (AICIS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set RTECS (Registry of Toxic Effects of Chemical Substances)
World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet