

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DSP 2015

Recommended Use of the Chemical and Restrictions on Use Reagent - oxide flotation.

Supplier: Ixom Operations Pty Ltd
ABN: 51 600 546 512
Street Address: Level 8, 1 Nicholson Street
East Melbourne Victoria 3002
Australia

Telephone Number: +61 3 9906 3000
Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Corrosion - Sub-category 1C
Eye Damage - Category 1

SIGNAL WORD: DANGER



Hazard Statement(s):

H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P260 Do not breathe mist, vapours, spray.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P363 Wash contaminated clothing before re-use.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310 Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P405 Store locked up.

Product Name: DSP 2015
Substance No: 000000050162

Issued: 18/03/2019
Version: 3

Safety Data Sheet

**Disposal:**

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Di-(2-ethylhexyl) phosphate	298-07-7	30-60%	H312 H314
Mono-(2-ethylhexyl) phosphate	1070-03-7	to 100%	H314

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder). Water or foam may cause frothing.

Hazchem or Emergency Action Code: 2X

Specific hazards arising from the chemical:

Combustible liquid.

Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of phosphorus. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Product Name: DSP 2015
Substance No: 000000050162

Issued: 18/03/2019
Version: 3

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Shut off all possible sources of ignition. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. For large amounts, pump off product.

7. HANDLING AND STORAGE

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet



Physical state:	Clear Liquid
Colour:	Light Yellow or Yellow
Odour:	Faint Fruity
Specific Gravity:	ca. 0.96
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	>150
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
Solubility in water (g/L):	Not available
Boiling Point/Range (°C):	Not available
pH:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	Reacts with metals.
Chemical stability:	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions:	Corrosive to metals liberating flammable hydrogen gas.
Conditions to avoid:	Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with most metals .
Hazardous decomposition products:	Oxides of phosphorus.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
Eye contact:	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
Skin contact:	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.
Inhalation:	Material may be irritant to the mucous membranes of the respiratory tract (airways).
Acute toxicity:	No LD50 data available for the product.
Respiratory or skin sensitisation:	No information available.
Chronic effects:	No information available for the product.
Aspiration hazard:	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
Persistence/degradability:	No information available.
Bioaccumulative potential:	No information available.
Mobility in soil:	No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No:	3265
Transport Hazard Class:	8 Corrosive
Packing Group:	III
Proper Shipping Name or Technical Name:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS DI-(2-ETHYLHEXYL) PHOSPHATE AND MONO-(2-ETHYLHEXYL) PHOSPHATE)
Hazchem or Emergency Action Code:	2X

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No:	3265
Transport Hazard Class:	8 Corrosive
Packing Group:	III
Proper Shipping Name or Technical Name:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS DI-(2-ETHYLHEXYL) PHOSPHATE AND MONO-(2-ETHYLHEXYL) PHOSPHATE)
IMDG EMS Fire:	F-A
IMDG EMS Spill:	S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No:	3265
---------------	------

Safety Data Sheet



Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS DI-(2-ETHYLHEXYL) PHOSPHATE AND MONO-(2-ETHYLHEXYL) PHOSPHATE)

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Corrosion - Sub-category 1C

Eye Damage - Category 1

Hazard Statement(s):

H314 Causes severe skin burns and eye damage.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason(s) for Issue:

5 Yearly Revised Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.