

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:

DSP 672

Recommended Use of the Chemical Mineral flotation collector. **and Restrictions on Use**

Supplier: ABN: Street Address:	Ixom Operations Pty Ltd 51 600 546 512 Level 8, 1 Nicholson Street East Melbourne Victoria 3002 Australia
Telephone Number:	+61 3 9906 3000
Emergency Telephone:	1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Corrosion - Sub-category 1B Eye Damage - Category 1

SIGNAL WORD: DANGER



Hazard Statement(s): H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P260 Do not breathe mist, vapours, spray.P264 Wash hands thoroughly after handling.P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P363 Wash contaminated clothing before re-use.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310 Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P405 Store locked up. Product Name: DSP 672 Substance No: 00000050186

Issued: 12/02/2020 Version: 3



Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Phosphorothioic acid, O,O-bis(2-methylpropyl)ester, sodium salt	53378-52-2	42% min	H314
Other ingredient(s)	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the chemical:

Combustible liquid.

Special protective equipment and precautions for fire-fighters:

Decomposes on heating emitting toxic fumes, including those of sulfur dioxide, oxides of phosphorus, and hydrogen sulfide. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

Product Name: DSP 672 Substance No: 00000050186



6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. If the product is frozen allow it to thaw. Stir well before use.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Colour: Odour: Liquid Yellow to Amber - Brown Sulfur

Product Name: DSP 672 Substance No: 00000050186



Solubility: Specific Gravity: Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): Flash Point (°C): Flammability Limits (%): Autoignition Temperature (°C): **Boiling Point/Range (°C):** pH:

Miscible with water. 1.12~1.16 Not available >93 (Closed cup) Not available Not available <100 13.0~13.7

10. STABILITY AND REACTIVITY

Reactivity:	Reacts with acids. Corrosive to aluminium, tin, and zinc. Reacts with ammonium salts liberating ammonia gas.
Chemical stability:	Stable.
Possibility of hazardous reactions:	Reacts with acids liberating hydrogen sulfide, a highly flammable, toxic gas. Hazardous polymerisation will not occur.
Conditions to avoid:	None known.
Incompatible materials:	Incompatible with strong acids , aluminium , brass , tin , zinc , ammonium salts .
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Oxides of phosphorus.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
Eye contact:	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
Skin contact:	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.
Inhalation:	Breathing in vapour may produce respiratory irritation.
Acute toxicity: Oral LD50 (rat): >5000 mg/kg Dermal LD50 (rabbit): >2000 mg/kg Inhalation LC50 (rat): >20 mg/L/4hr	
Skin corrosion/irritation:	Corrosive. The product has not been tested; the classification is based on the components of the mixture.
Serious eye damage/irritation:	Corrosive. The product has not been tested; the classification is based on the components of the mixture.
Respiratory or skin sensitisation:	No information available.



Chronic effects: No information available for the product.

Aspiration hazard: No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
Persistence/degradability:	No information available.
Bioaccumulative potential:	No information available.
Mobility in soil:	No information available.
Aquatic toxicity:	Harmful to aquatic organisms. May cause long lasting harmful effects to aquatic life.
96hr LC50 (rainbow trout): 96hr LC50 (bluegill sunfish):	30 mg/L 42 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No:1719Transport Hazard Class:8 CorrosivePacking Group:IIProper Shipping Name or
Technical Name:CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID,
0,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT)Hazchem or Emergency Action
Code:2R

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No:	1719
Transport Hazard Class:	8 Corrosive
Packing Group:	II
Proper Shipping Name or	CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID,
Technical Name:	O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT)
IMDG EMS Fire:	F-A

Product Name: DSP 672 Substance No: 00000050186



IMDG EMS Spill: S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No:
Transport Hazard Class:
Packing Group:
Proper Shipping Name or
Technical Name:

8 Corrosive II CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT)

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

1719

Classification of the chemical:

Skin Corrosion - Sub-category 1B Eye Damage - Category 1

Hazard Statement(s):

H314 Causes severe skin burns and eye damage.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason(s) for Issue:

5 Yearly Revised Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.