

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** **DSF 442**

**Recommended Use of the Chemical and Restrictions on Use** Frother.

**Supplier:** Ixom Operations Pty Ltd  
**ABN:** 51 600 546 512  
**Street Address:** Level 8, 1 Nicholson Street  
East Melbourne Victoria 3002  
Australia

**Telephone Number:** +61 3 9906 3000  
**Emergency Telephone:** **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

## 2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

### Classification of the chemical:

Skin Irritation - Category 2  
Eye Damage - Category 1

**SIGNAL WORD:** DANGER



### Hazard Statement(s):

H315 Causes skin irritation.  
H318 Causes serious eye damage.

### Precautionary Statement(s):

#### Prevention:

P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves / protective clothing / eye protection / face protection.

#### Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P362 Take off contaminated clothing and wash before reuse.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor/physician.

#### Storage:

No storage statements.

Product Name: DSF 442  
Substance No: 000000050788

Issued: 07/01/2016  
Version: 2

# Safety Data Sheet

**Disposal:**

No disposal statements.

**Poisons Schedule (SUSMP):** None allocated.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
2-Ethyl hexanol	104-76-7	10-<30%	H227 H315 H319 H332 H335 H402
2-(2-(2-butoxyethoxy)ethoxy)ethanol	143-22-6	<10%	H318
Non hazardous component(s)	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

**Inhalation:**

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:**

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

**Eye Contact:**

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

**Ingestion:**

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

**Indication of immediate medical attention and special treatment needed:**

Treat symptomatically. No known specific antidote. Can cause corneal burns.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:**

Normal foam, dry agent (carbon dioxide, dry chemical powder).

**Specific hazards arising from the chemical:**

Combustible liquid. May form flammable vapour mixtures with air.

**Special protective equipment and precautions for fire-fighters:**

On burning will emit toxic fumes, including those of oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## 6. ACCIDENTAL RELEASE MEASURES

# Safety Data Sheet



## Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

## Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

### Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Take precautionary measures against static discharges.

### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** No value assigned for this specific material by Safe Work Australia.

2-Ethyl hexanol: 8hr TWA = 200 ppm (recommended standard)

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.


If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

# Safety Data Sheet



Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator or an air supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Colour:</b>	Dark Yellow
<b>Odour:</b>	Faint Specific
<b>Solubility:</b>	Insoluble in water.
<b>Specific Gravity:</b>	ca. 0.9
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	>93
<b>Flammability Limits (%):</b>	Not available
<b>Autoignition Temperature (°C):</b>	Not available
<b>Boiling Point/Range (°C):</b>	Not available
<b>pH:</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	No information available.
<b>Chemical stability:</b>	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
<b>Possibility of hazardous reactions:</b>	Reacts with strong oxidising agents .
<b>Conditions to avoid:</b>	Avoid exposure to heat, sources of ignition, and open flame.
<b>Incompatible materials:</b>	Incompatible with strong oxidising agents.
<b>Hazardous decomposition products:</b>	Oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	No adverse effects expected, however, large amounts may cause nausea and vomiting.
<b>Eye contact:</b>	A severe eye irritant. Contamination of eyes can result in permanent injury.
<b>Skin contact:</b>	Contact with skin will result in irritation.

# Safety Data Sheet



**Inhalation:** Breathing in vapour may produce respiratory irritation.

**Acute toxicity:** No LD50 data available for the product.

**Chronic effects:** No information available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

**Disposal methods:**

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

## 14. TRANSPORT INFORMATION

**Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

**Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

**Air Transport**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

**Classification:**

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

**Classification of the chemical:**

Skin Irritation - Category 2

Eye Damage - Category 1

**Hazard Statement(s):**

H315 Causes skin irritation.

H318 Causes serious eye damage.

**Poisons Schedule (SUSMP):** None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

# Safety Data Sheet



## **Reason(s) for Issue:**

Revised Primary SDS

Alignment to GHS requirements

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.