# SAFETY DATA SHEET



Revision date: 30-Nov-2020

**Revision Number** 3

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name TOXIMUL 3473F

**Product Code(s)** 000000051749

Other means of identification

UN number 3082

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Surfactant.

For industrial use only.

**Uses advised against** No information available.

Supplier

Ixom Operations Pty Ltd ABN: 51 600 546 512 Level 8, 1 Nicholson Street Melbourne 3000 Australia

Telephone Number: +61 3 9906 3000

### Emergency telephone number

Emergency telephone number 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

### 2. HAZARDS IDENTIFICATION

### **GHS Classification**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

E	T <sub>a</sub>
Flammable liquids	Category 4
Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2

Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 3

#### SIGNAL WORD

Warning

#### Label elements

Environment

Health hazard Exclamation mark

#### **Hazard statements**

H227 - Combustible liquid

H302 - Harmful if swallowed

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

H401 - Toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Avoid breathing dust / fume / gas / mist / vapours / spray

Wash hands thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves / protective clothing / eye protection / face protection

Use personal protective equipment as required

Avoid release to the environment

### **Precautionary Statements - Response**

Specific treatment (see First aid on this SDS)

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eve irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet for extinction.

Collect spillage

**Precautionary Statements - Storage** 

Store in a well-ventilated place. Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

**Precautionary Statements - Disposal** 

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification
Poisons Schedule (SUSMP)
None allocated

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Chemical name	CAS No.	Weight-%
Anionic/nonionic surfactant blend	-	60-80%
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	10-<30%
1-Hexanol	111-27-3	1-<3%
Naphthalene	91-20-3	1-<3%
Propylene glycol	57-55-6	1-<3%

### 4. FIRST AID MEASURES

#### **Description of first aid measures**

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

**Inhalation** Remove to fresh air. Call a physician if symptoms occur.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present

and easy to do. Continue rinsing. Call a physician immediately.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Call a physician if symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Use personal protective equipment as required. Avoid contact with skin, eyes, and clothing.

See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Irritation.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal

protein foam can be used.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Combustible material. Product may ignite and burn at temperatures exceeding the flash

point. Environmentally hazardous.

Hazardous combustion products Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

Hazchem code •3Z

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid

contact with skin, eyes, and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. See section 8 for

more information.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**Environmental precautions** 

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far

ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal.

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled

containers. Never return spill or leaks to original containers for re-use. After cleaning, flush

away traces with water.

### 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin, eyes, and clothing. Avoid

breathing vapors or mists. Handle in accordance with good industrial hygiene and safety

practice. Take precautionary measures against static discharges.

General hygiene considerations Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes, and clothing. Wear suitable gloves and

eye/face protection.

#### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight.

Store away from sources of heat or ignition. Keep in an area equipped with sprinklers. Keep

container closed when not in use.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and

transport requirements.

Incompatible materials Strong oxidizing agents.

Poisons Schedule (SUSMP) None allocated

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace

Exposure Standard(s) for constituent(s):

Propane-1,2-diol (propylene glycol) (total: vapour & particulates): 8hr TWA = 474 mg/m $^3$  (150 ppm); (particulates only): 8hr TWA = 10 mg/m $^3$ 

Naphthalene: 8hr TWA = 52 mg/m³ (10 ppm), 15 min STEL = 79 mg/m³ (15 ppm), Carcinogen Category 2

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

Carcinogen Category 2 - substances suspected of having carcinogenic potential. The available information is not adequate for making a satisfactory assessment.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Appropriate engineering controls

**Engineering controls** Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

#### Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.











Eye/face protection Goggles.

**Skin and body protection** Wear suitable protective clothing. Boots. Overalls.

Hand protection Impervious gloves.

Respiratory protection If determined by a risk assessment an inhalation risk exists, wear an organic

vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

None known

**Environmental exposure controls** No information available.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available.

**Color** Amber

Odor No information available.
Odor threshold No information available.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** 5-7 (5% 50:50 IPA:H2O) None known

Melting point / freezing point No data available

Boiling point / boiling range >93.89°C

Flash point69.4°CSeta Closed CupEvaporation rateNo data availableNone knownFlammability (solid, gas)No data availableNone known

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressureNo data availableVapor densityNo data availableRelative density1.018 @ 25°CWater solubilityDispersibleSolubility(ies)No data available

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone known

Autoignition temperature No data available

Decomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosity312 cP @25°CNone known

Other information

Pour Point 1.11°C

### 10. STABILITY AND REACTIVITY

Reactivity

**Reactivity** Non-reactive under normal conditions of use, storage and transport.

**Chemical stability** 

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions 
None under normal processing.

**Conditions to avoid** 

Conditions to avoid Heat, flames and sparks. Direct sunlight.

**Incompatible materials** 

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

### 11. TOXICOLOGICAL INFORMATION

### **Acute toxicity**

### Information on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this

Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the

chemical is mishandled and overexposure occurs are:

**Inhalation** Irritating to respiratory system.

**Eye contact** Causes serious eye irritation.

**Skin contact** Irritating to skin.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms Irritation.

#### Numerical measures of toxicity - Product Information

No information available.

**Component Information** 

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, heavy aromatic	> 5000 mg/kg (Rat)	> 2 mL/kg(Rabbit)	> 590 mg/m³ (Rat) 4 h
1-Hexanol	= 3210 mg/kg (Rat)	1500 - 2000 mg/kg (Rabbit)	> 21 mg/L (Rat) 1 h

	= 720 mg/kg (Rat)		
Naphthalene	= 490 mg/kg(Rat) = 1110 mg/kg(Rat)	= 1120 mg/kg ( Rabbit ) > 20 g/kg ( Rabbit )	> 340 mg/m³(Rat)1 h
Propylene glycol	= 20 g/kg(Rat)	= 20800 mg/kg ( Rabbit )	-

See section 16 for terms and abbreviations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Classification is based on mixture calculation methods based on

component data.

Serious eye damage/eye irritation Causes serious eye irritation. Classification is based on mixture calculation methods based

on component data.

**Respiratory or skin sensitization** No information available.

Germ cell mutagenicity No information available.

**Carcinogenicity** Suspected of causing cancer.

Chemical name	Australia
Naphthalene - 91-20-3	Carc. 2

Reproductive toxicity No information available.

**STOT - single exposure** May cause respiratory irritation.

STOT - repeated exposure Not classified.

Aspiration hazard Not classified.

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

**Ecotoxicity** Keep out of waterways. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Solvent naphtha,	EC50: =2.5mg/L (72h,	LC50: =19mg/L (96h,	-	EC50: =0.95mg/L (48h,
petroleum, heavy	Skeletonema costatum)	Pimephales promelas)		Daphnia magna)
aromatic		LC50: =2.34mg/L (96h,		-
		Oncorhynchus mykiss)		
		LC50: =1740mg/L (96h,		
		Lepomis macrochirus)		
		LC50: =45mg/L (96h,		
		Pimephales promelas)		
		LC50: =41mg/L (96h,		
		Pimephales promelas)		
1-Hexanol	-	LC50: 89.7 - 106mg/L	-	EC50: =201mg/L (24h,
		(96h, Pimephales		Daphnia magna)
		promelas) LC50:		-
		=144mg/L (96h,		
		Brachydanio rerio)		
Naphthalene	EC50: =0.4mg/L (72h,	LC50: 5.74 - 6.44mg/L	-	LC50: =2.16mg/L (48h,
	Skeletonema costatum)	(96h, Pimephales		Daphnia magna) EC50:

		promelas) LC50:		=1.96mg/L (48h, Daphnia
		=1.6mg/L (96h,		magna) EC50: 1.09 -
		Oncorhynchus mykiss)		3.4mg/L (48h, Daphnia
		LC50: 0.91 - 2.82mg/L		magna)
		(96h, Oncorhynchus		<b>.</b>
		mykiss) LC50: =1.99mg/L		
		(96h, Pimephales		
		promelas) LC50:		
		=31.0265mg/L (96h,		
		Lepomis macrochirus)		
Propylene glycol	EC50: =19000mg/L (96h,	LC50: =51600mg/L (96h,	-	EC50: >1000mg/L (48h,
	Pseudokirchneriella	Oncorhynchus mykiss)		Daphnia magna) EC50:
	subcapitata)	LC50: 41 - 47mL/L (96h,		>10000mg/L (24h,
	. ,	Oncorhynchus mykiss)		Daphnia magna)
		LC50: =51400mg/L (96h,		. 5 ,
		Pimephales promelas)		
		LC50: =710mg/L (96h,		
		Pimephales promelas)		

Persistence and degradability

Persistence and degradability Readily biodegradable.

Bioaccumulative potential

**Bioaccumulation** No information available.

**Component Information** 

Chemical name		Partition coefficient
	Solvent naphtha, petroleum, heavy aromatic	2.9 - 6.1
	1-Hexanol	2.03
	Naphthalene	3.6

Mobility

Mobility in soil No information available.

Other adverse effects

### 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

3082

### 14. TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail: DANGEROUS GOODS.

**UN number** 

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Proper shipping name

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC)

**Hazard class** 

Packing group III Hazchem code •3Z

#### **IATA**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC)

Transport hazard class(es) 9
Packing group III

#### **IMDG**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC)

Transport hazard class(es)

Packing group

IMDG EMS Fire

F-A

IMDG EMS Spill

S-F

Marine pollutant

9

III

F-A

Yes

### 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

### **National regulations**

#### Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

#### National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Solvent naphtha, petroleum, heavy aromatic - 64742-94-5	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/vr Threshold category 2b total

1-Hexanol - 111-27-3	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total
Naphthalene - 91-20-3	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total
Propylene glycol - 57-55-6	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total

#### **International Inventories**

AICS All the constituents of this material are listed on the Australian Inventory of Industrial

Chemicals.

#### Legend:

- Australian Inventory of Industrial Chemicals

#### **International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

# **16. OTHER INFORMATION**

Supplier Safety Data Sheet 08/2018

Reason(s) For Issue: 5 Yearly Revised Primary SDS

Change to Transport Information Change from non-DG to DG

Issuing Date: 30-Nov-2020

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

#### **Revision Note:**

The symbol (\*) in the margin of this SDS indicates that this line has been revised.

### Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

C Carcinogen

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian Industrial Chemicals Introduction Scheme (AICIS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

#### <u>Disclaimer</u>

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**End of Safety Data Sheet**