

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DSF 905

Recommended Use of the Chemical Frother. and Restrictions on Use

Supplier: Ixom Operations Pty Ltd

ABN: 51 600 546 512

Street Address: Level 8, 1 Nicholson Street

East Melbourne Victoria 3002

Australia

Telephone Number: +61 3 9906 3000

Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Flammable liquids - Category 4
Skin Irritation - Category 2
Eye Irritation - Category 2A
Acute Inhalation Toxicity - Category 4
Specific target organ toxicity (single exposure) - Category 3
Acute Aquatic Toxicity - Category 3
Chronic Aquatic Toxicity - Category 3

SIGNAL WORD: WARNING



Hazard Statement(s):

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.

P261 Avoid breathing mist, vapours, spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P273 Avoid release to the environment.

Product Name: DSF 905

Substance No: 000000053049

Issued: 30/06/2015 Version: 1



Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P370+P378 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
2-Ethyl hexanol	104-76-7	>60%	H227 H315 H319 H332 H335 H402
Non hazardous component(s)	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

Product Name: DSF 905 Issued: 30/06/2015 Substance No: 000000053049



5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Unsuitable Extinguishing Media:

Water jet.

Specific hazards arising from the chemical:

Combustible liquid. May form flammable vapour mixtures with air.

Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

2-Ethyl hexanol: 8hr TWA = 200 ppm (recommended standard)

Product Name: DSF 905 Issued: 30/06/2015 Substance No: 000000053049



TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.









Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Colour: Colourless Odour: Mild

Solubility: Slightly miscible with water.

Specific Gravity: ca. 0.84 Relative Vapour Density (air=1): >1

Vapour Pressure (20 °C): Not available

Flash Point (°C): >75

Flammability Limits (%): 0.88-9.7 (main component) **Autoignition Temperature (°C):** 288 (main component)

Boiling Point/Range (°C): Not available **Decomposition Point (°C):** Not available Not available pH:

10. STABILITY AND REACTIVITY

Product Name: DSF 905 Issued: 30/06/2015 Substance No: 000000053049



No information available. Reactivity:

This material is considered stable. Chemical stability:

Possibility of hazardous

reactions:

Hazardous polymerisation will not occur.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame.

Incompatible materials: Incompatible with strong oxidising agents.

Hazardous decomposition

products:

Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: No adverse effects expected, however, large amounts may cause nausea and

vomiting.

An eye irritant. **Eve contact:**

Skin contact: Contact with skin will result in irritation. Will have a degreasing action on the skin.

Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Inhalation: Breathing in vapour will produce respiratory irritation.

Acute toxicity: No LD50 data available for the product. However, for the major constituent:

Oral LD50 (rat): >2000 mg/kg Dermal LD50 (rabbit): >2000 mg/kg Inhalation LC50 (rat): 1.45 mg/L/4h

Skin corrosion/irritation: Irritant (rabbit). Serious eye damage/irritation: Irritant (rabbit).

Chronic effects: No information available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Harmful to aquatic organisms. May cause long lasting harmful effects to aquatic **Aquatic toxicity:**

life.

96hr LC50 (golden orfe): 17.1 mg/L (main component)

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Product Name: DSF 905 Issued: 30/06/2015 Substance No: 000000053049



Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail: NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Flammable liquids - Category 4 Skin Irritation - Category 2 Eye Irritation - Category 2A Acute Inhalation Toxicity - Category 4 Specific target organ toxicity (single exposure) - Category 3 Acute Aquatic Toxicity - Category 3 Chronic Aquatic Toxicity - Category 3

Hazard Statement(s):

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

None allocated. Poisons Schedule (SUSMP):

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

First Issue Primary SDS

Product Name: DSF 905 Issued: 30/06/2015 Substance No: 000000053049



This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: DSF 905 Issued: 30/06/2015 Substance No: 000000053049