

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: ULTRAMID B3WGM24 BLACK 23228 POLYAMIDE

Recommended Use of the Chemical Polymer.

and Restrictions on Use For industrial processing only.

Supplier: Ixom Operations Pty Ltd

**ABN:** 51 600 546 512

Street Address: Level 8, 1 Nicholson Street

East Melbourne Victoria 3002

Australia

**Telephone Number:** +61 3 9906 3000

Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

### 2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS CHEMICAL.

Poisons Schedule (SUSMP): None allocated.

# 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Non hazardous component(s)	ı	100%	-

# 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

#### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

#### **Skin Contact:**

If skin contact occurs, remove contaminated clothing and wash skin with soap and water. If irritation occurs, seek medical advice. If molten material should contact the skin and adhere, cool quickly with running water - do not attempt to remove. Seek immediate medical assistance.

### **Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. For contact with the molten material treat as for skin burns.

Product Name: ULTRAMID B3WGM24 BLACK 23228 POLYAMIDE Issued: 15/11/2017

Substance No: 000000053058

Version: 1



### Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

### Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

#### Specific hazards arising from the chemical:

Combustible solid.

### Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon, tetrahydrofuran. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

# 6. ACCIDENTAL RELEASE MEASURES

### **Emergency procedures/Environmental precautions:**

If contamination of sewers or waterways has occurred advise local emergency services.

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

# 7. HANDLING AND STORAGE

### Precautions for safe handling:

Avoid skin and eye contact and breathing in dust. Avoid handling which leads to dust formation. Take precautionary measures against static discharges.

### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Protect from moisture. Keep containers closed when not in use - check regularly for spills.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Mica: 8hr TWA = 2.5 mg/m<sup>3</sup>

Product Name: ULTRAMID B3WGM24 BLACK 23228 POLYAMIDE Issued: 15/11/2017 Substance No: 000000053058

Version: 1



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. In general, ventilation should be provided at compounding and converting areas and at fabricating work stations which involve heating the plastic. Local exhaust hoods may be used over die-heads of extrusion equipment or in the vicinity of thermoforming and moulding machines, where practicable. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.









Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Granules

Colour: Natural, Black, or Coloured

Odourless

Solubility: Insoluble in water.

Specific Gravity: 1.10-1.60 @ 20°C

Relative Vapour Density (air=1): Not available

Vapour Pressure (20 °C): Not available

Flash Point (°C): Not available

Flammability Limits (%): Not available

Autoignition Temperature (°C): >400
Melting Point/Range (°C): ca. 220
Decomposition Point (°C): >320

Product Name: ULTRAMID B3WGM24 BLACK 23228 POLYAMIDE

Substance No: 000000053058

Issued: 15/11/2017 Version: 1





# 10. STABILITY AND REACTIVITY

**Reactivity:** No information available.

**Chemical stability:** This material is chemically stable.

Possibility of hazardous

reactions:

None known.

**Conditions to avoid:** Avoid dust generation. Avoid exposure to moisture. Avoid temperatures above 320

°C

**Incompatible materials:** None known.

**Hazardous decomposition** 

products:

Oxides of carbon. Ammonia. Caprolactam. Hydrogen cyanide.

# 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** No adverse effects expected, however, large amounts may cause nausea and

vomiting.

**Eye contact:** May be an eye irritant. Exposure to the dust may cause discomfort due to

particulate nature. May cause physical irritation to the eyes. Contact with the hot

material can result in pain, thermal burns, and permanent injury.

**Skin contact:** Contact with skin may result in irritation. Contact with hot material may cause skin

burns.

**Inhalation:** Breathing in dust may result in respiratory irritation. Vapour and processing fumes

may cause irritation to mucous membranes of the respiratory tract, headache and

nausea.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.

**Aspiration hazard:** No aspiration hazard expected.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

# 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

# 14. TRANSPORT INFORMATION

Product Name: ULTRAMID B3WGM24 BLACK 23228 POLYAMIDE Issued: 15/11/2017

Substance No: 000000053058 Version: 1



### **Road and Rail Transport**

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail: NON-DANGEROUS GOODS.

### **Marine Transport**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air: NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

#### Classification:

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS CHEMICAL.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

Supplier Safety Data Sheet; 07/2015.

ULTRAMID is a registered trademark of BASF.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

#### Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Ptv Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: ULTRAMID B3WGM24 BLACK 23228 POLYAMIDE Issued: 15/11/2017 Substance No: 000000053058

Version: 1