

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DSP 230

Recommended Use of the Chemical and Restrictions on Use Collector for the mining industry.

Supplier: Ixom Operations Pty Ltd
ABN: 51 600 546 512
Street Address: Level 8, 1 Nicholson Street
East Melbourne Victoria 3002
Australia

Telephone Number: +61 3 9906 3000
Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Corrosion - Sub-category 1C
Skin Sensitisation - Category 1
Eye Damage - Category 1
Carcinogenicity - Category 2

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Aquatic Toxicity - Category 1
Chronic Aquatic Toxicity - Category 1

SIGNAL WORD: DANGER



Hazard Statement(s):

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

Precautionary Statement(s):

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist, vapours, spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P281 Use personal protective equipment as required.

Product Name: DSP 230
Substance No: 000000053154

Issued: 17/02/2016
Version: 1

Safety Data Sheet



Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P363 Wash contaminated clothing before re-use.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310 Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
O-Isopropyl ethyl thiocarbamate	141-98-0	>60%	H317 H412
1-Dodecanethiol	112-55-0	30-60%	H314 H317 H410
Isopropyl alcohol	67-63-0	<2%	H225 H319 H336
1,3-Diethyl thiourea	105-55-5	<2%	H302 H317 H318 H351 H335 H412
Other ingredient(s)	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Seek immediate medical assistance.

Safety Data Sheet



Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Unsuitable Extinguishing Media:

Water jet.

Hazchem or Emergency Action Code: 2X

Specific hazards arising from the chemical:

Combustible liquid. On burning will emit toxic fumes, including those of oxides of carbon .

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Do not allow container or product to get into drains, sewers, streams or ponds. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Precautions for safe handling:

Avoid eye contact and repeated or prolonged skin contact. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Isopropyl alcohol: 8hr TWA = 983 mg/m³ (400 ppm), 15 min STEL = 1230 mg/m³ (500 ppm)

Safety Data Sheet



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear an air supplied respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Yellow to Light Red
Odour:	Offensive
Specific Gravity:	ca. 0.9
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	>93

Product Name: DSP 230
Substance No: 00000053154

Issued: 17/02/2016
Version: 1

Safety Data Sheet



Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
Solubility in water (g/L):	Not available
Boiling Point/Range (°C):	Not available
pH:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	No information available.
Chemical stability:	Stable at ambient temperatures.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	None known.
Incompatible materials:	Incompatible with strong oxidising agents , strong acids , copper , brass .
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
Eye contact:	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
Skin contact:	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
Inhalation:	Breathing in vapour may produce respiratory irritation.
Acute toxicity:	No LD50 data available for the product.
Chronic effects:	A component of this product is a suspected human carcinogen.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
Aquatic toxicity:	Very toxic to aquatic organisms. May cause long lasting harmful effects to aquatic life.
48hr EC50 (algae):	<1 mg/L

13. DISPOSAL CONSIDERATIONS

Safety Data Sheet



Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No: 1760
Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CORROSIVE LIQUID, N.O.S. (CONTAINS 1-DODECANETHIOL)
Hazchem or Emergency Action Code: 2X

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1760
Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CORROSIVE LIQUID, N.O.S. (CONTAINS 1-DODECANETHIOL)

IMDG EMS Fire: F-A
IMDG EMS Spill: S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1760
Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CORROSIVE LIQUID, N.O.S. (CONTAINS 1-DODECANETHIOL)

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Safety Data Sheet

**Classification of the chemical:**

Skin Corrosion - Sub-category 1C
Skin Sensitisation - Category 1
Eye Damage - Category 1
Carcinogenicity - Category 2

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Aquatic Toxicity - Category 1
Chronic Aquatic Toxicity - Category 1

Hazard Statement(s):

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

Poisons Schedule (SUSMP): None allocated.

16. OTHER INFORMATION

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.