

## **1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Product Name:

### **VORANOL CP 450 POLYOL**

**Recommended Use of the Chemical** For the manufacture of urethane polymers. For industrial use. **and Restrictions on Use** 

Supplier: ABN: Street Address:	Ixom Operations Pty Ltd 51 600 546 512 Level 8, 1 Nicholson Street East Melbourne Victoria 3002 Australia
Telephone Number:	+61 3 9906 3000
Emergency Telephone:	<b>1 800 033 111 (ALL HOURS)</b>

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

### 2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS CHEMICAL.

Poisons Schedule (SUSMP): None allocated.

# **3. COMPOSITION AND INFORMATION ON INGREDIENTS**

Components	CAS Number	Proportion	Hazard Codes
Polyether polyol	25791-96-2	>99%	-

### 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

#### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

#### Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

#### Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

#### Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.



#### Indication of immediate medical attention and special treatment needed:

Treat symptomatically. No known specific antidote.

### **5. FIRE FIGHTING MEASURES**

#### Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

#### Unsuitable Extinguishing Media:

Solid water jet/stream may scatter and spread the fire.

#### Specific hazards arising from the chemical:

Combustible liquid. Containers may rupture or explode in heat of fire.

#### Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of carbon dioxide . Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

#### **Emergency procedures/Environmental precautions:**

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

#### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Wash area down with excess water.

### 7. HANDLING AND STORAGE

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

#### Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour.

#### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Storage temperature: 15-35°C. Shelf life: Use within 24 months. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** No value assigned for this specific material by Safe Work Australia.

#### Appropriate engineering controls:

Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.



#### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Colourless
Odour:	Mild
Solubility:	Miscible in water.
Specific Gravity:	1.05 @25°C (calculated)
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Negligible
Flash Point (°C):	199 (PMCC)
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
Melting Point/Range (°C):	-45 (Pour point)
Boiling Point/Range (°C):	Decomposes before boiling
pH:	6-8
Viscosity:	300-360 cSt @25°C

### **10. STABILITY AND REACTIVITY**

Reactivity:	Reacts with isocyanates.
Chemical stability:	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions:	Generation of gas during decomposition can cause pressure in closed systems.
Conditions to avoid:	Avoid exposure to heat.
Incompatible materials:	Incompatible with strong acids, strong bases, oxidising agents, isocyanates.
Hazardous decomposition products:	Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Ketones. Polymer fragments.

## **11. TOXICOLOGICAL INFORMATION**



No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing may result in nausea, vomiting, and abdominal pain.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin may result in irritation.
Inhalation:	Breathing in vapour may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product. For this family of materials: Oral LD50 (rat): >2000 mg/kg Dermal LD50 (rabbit): >2000 mg/kg

Chronic effects: In vitro genetic toxicity studies were negative.

### **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Avoid contaminating waterways.

### **13. DISPOSAL CONSIDERATIONS**

#### Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

### **14. TRANSPORT INFORMATION**

#### Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

#### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

#### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

### **15. REGULATORY INFORMATION**

#### Classification:

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS CHEMICAL.

Poisons Schedule (SUSMP): None allocated.

This material is listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION



Supplier Material Safety Data Sheet; 09/ 2013. VORANOL is a trademark.

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

#### Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.