

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DSP 050

Recommended Use of the Chemical Mineral flotation collector. and Restrictions on Use

Supplier: Ixom Operations Ptv Ltd

51 600 546 512 ABN:

Street Address: Level 8, 1 Nicholson Street

East Melbourne Victoria 3002

Australia

+61 3 9906 3000 **Telephone Number:**

Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Flammable liquids - Category 3 Skin Corrosion - Sub-category 1B Skin Sensitisation - Category 1

Specific target organ toxicity (repeated exposure) - Category 2

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Oral Toxicity - Category 5 Acute Aquatic Toxicity - Category 2 Chronic Aquatic Toxicity - Category 2

SIGNAL WORD: DANGER









Hazard Statement(s):

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

Product Name: DSP 050 Issued: 04/10/2017 Substance No: 000000053472



Precautionary Statement(s):

Prevention:

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground or bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist, vapours, spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P363 Wash contaminated clothing before re-use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Carbamothioic acid, 2-propenyl-, O-(2-methylpropyl)ester	86329-09-1	30-60%	H302 H315 H317 H373 H411
Phosphorodithioic acid, O,O-bis(1-methylethyl)ester, sodium salt	27205-99-8	10-30%	H314
Methyl isobutyl carbinol	108-11-2	<10%	H226 H335
Non hazardous component(s)	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Product Name: DSP 050 Issued: 04/10/2017 Substance No: 000000053472



Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

Hazchem or Emergency Action Code: · 3W

Specific hazards arising from the chemical:

Flammable liquid.

Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon, oxides of phosphorus. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Do not allow container or product to get into drains, sewers, streams or ponds. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

Product Name: DSP 050 Issued: 04/10/2017 Substance No: 000000053472



8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Methyl isobutyl carbinol: 8hr TWA = 104 mg/m³ (25 ppm), 15 min STEL = 167 mg/m³ (40 ppm), Sk

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

`Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.













Wear overalls, chemical goggles, full face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Use with adequate ventilation. If determined by a risk assessment an inhalation risk exists, wear an air-supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

Product Name: DSP 050 Issued: 04/10/2017 Substance No: 000000053472



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Colour: Not specified Odour: Not specified Solubility: Miscible in water. **Specific Gravity:** Not available

Relative Vapour Density (air=1): >1

Vapour Pressure (20 °C): Not available Flash Point (°C): 42.4 (MIBC) Not available Flammability Limits (%): **Autoignition Temperature (°C):** Not available Boiling Point/Range (°C): Not available Not available pH:

10. STABILITY AND REACTIVITY

No information available. Reactivity:

Stable under normal conditions of use. Chemical stability:

Possibility of hazardous

reactions:

None known.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame.

Incompatible with strong acids, strong alkalis, oxidising agents. Incompatible materials:

Hazardous decomposition

products:

Oxides of carbon. Oxides of phosphorus.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and Ingestion:

chemical burns to the gastrointestinal tract.

A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Eye contact:

Contamination of eyes can result in permanent injury.

Contact with skin will result in severe irritation. Corrosive to skin - may cause skin Skin contact:

burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic

contact dermatitis.

Inhalation: Breathing in vapour may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product.

Chronic effects: May cause damage to organs through prolonged or repeated exposure.

12. ECOLOGICAL INFORMATION

Product Name: DSP 050 Issued: 04/10/2017 Substance No: 000000053472



Ecotoxicity Avoid contaminating waterways.

Aquatic toxicity: Toxic to aquatic organisms. May cause long lasting harmful effects to aquatic life.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No: 2920

Transport Hazard Class: 8 Corrosive

Subrisk 1: 3 Flammable Liquid

Packing Group:

Proper Shipping Name or CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS

Technical Name: PHOSPHORODITHIOIC ACID, O,O-BIS(1-METHYLETHYL)ESTER, SODIUM

SALT AND METHYL ISOBUTYL CARBINOL)

Hazchem or Emergency Action · 3W

Code:

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 2920

Transport Hazard Class: 8 Corrosive **Subrisk 1:** 8 Flammable liquid

Packing Group:

Proper Shipping Name or CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS

Technical Name: PHOSPHORODITHIOIC ACID, O,O-BIS(1-METHYLETHYL)ESTER, SODIUM

SALT AND METHYL ISOBUTYL CARBINOL)

IMDG EMS Fire: F-E IMDG EMS Spill: S-C

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 2920

Transport Hazard Class: 8 Corrosive

Subrisk 1: 3 Flammable Liquid

Packing Group:

Substance No: 000000053472

Product Name: DSP 050 Issued: 04/10/2017



Proper Shipping Name or Technical Name:

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS

PHOSPHORODITHIOIC ACID, O,O-BIS(1-METHYLETHYL)ESTER, SODIUM

SALT AND METHYL ISOBUTYL CARBINOL)

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia: HAZARDOUS CHEMICAL.

Classification of the chemical:

Flammable liquids - Category 3 Skin Corrosion - Sub-category 1B Skin Sensitisation - Category 1 Specific target organ toxicity (repeated exposure) - Category 2

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Oral Toxicity - Category 5 Acute Aquatic Toxicity - Category 2 Chronic Aquatic Toxicity - Category 2

Hazard Statement(s):

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: DSP 050 Issued: 04/10/2017 Substance No: 000000053472