

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **STEOL CS370/MB**

Recommended Use of the Chemical and Restrictions on Use Surfactant.
For industrial use only.

Supplier: Ixom Operations Pty Ltd
ABN: 51 600 546 512
Street Address: Level 8, 1 Nicholson Street
East Melbourne Victoria 3002
Australia

Telephone Number: +61 3 9906 3000
Emergency Telephone: **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Irritation - Category 2
Eye Damage - Category 1

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Aquatic Toxicity - Category 3
Chronic Aquatic Toxicity - Category 3

SIGNAL WORD: DANGER



Hazard Statement(s):

H315 Causes skin irritation.
H318 Causes serious eye damage.

Precautionary Statement(s):

Prevention:

P264 Wash hands thoroughly after handling.
P280 Wear protective gloves / protective clothing / eye protection / face protection.

Safety Data Sheet

**Response:**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

Storage:

No storage statements.

Disposal:

No disposal statements.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

| Components | CAS Number | Proportion | Hazard Codes |
|-------------------------------|------------|------------|----------------|
| Sodium lauryl ether sulphate | 9004-82-4 | 68-<72% | H315 H318 |
| Water | 7732-18-5 | 20-<30% | - |
| Alcohols, C12-14, ethoxylated | 68439-50-9 | 1-<3% | H302 H318 H400 |

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Safety Data Sheet



Unsuitable Extinguishing Media:

Solid water jet/stream may scatter and spread the fire.

Specific hazards arising from the chemical:

Non-combustible material. Environmentally hazardous.

Special protective equipment and precautions for fire-fighters:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes, including those of oxides of sulfur. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. If safe to do so, remove containers from path of fire.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Do not allow container or product to get into drains, sewers, streams or ponds. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. After cleaning, flush away any residual traces with water.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. When using do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.



Safety Data Sheet



Wear overalls, chemical goggles and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|------------------------------------|
| Physical state: | Viscous liquid |
| Colour: | Light Yellow |
| Odour: | Not specified |
| Specific Gravity: | 1.006 @25°C |
| Relative Vapour Density (air=1): | <1 (estimated) |
| Vapour Pressure (20 °C): | Not available |
| Flash Point (°C): | Not applicable |
| Flammability Limits (%): | Not applicable |
| Autoignition Temperature (°C): | Not available |
| Solubility in water (g/L): | Not available |
| Boiling Point/Range (°C): | >100 |
| Decomposition Point (°C): | Not available |
| pH: | 7-8.5 (10% aqueous) |
| Evaporation Rate: | Estimated slower than ethyl ether. |
| Freezing Point/Range (°C): | 6.11 |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Reactivity: | Non-reactive under normal conditions of use, storage and transport. |
| Chemical stability: | Stable under normal conditions. |
| Possibility of hazardous reactions: | No hazardous reactions when stored and handled correctly. |
| Conditions to avoid: | Avoid exposure to heat. |
| Incompatible materials: | Incompatible with strong oxidising agents. Incompatible with strong acids. |
| Hazardous decomposition products: | Oxides of sulfur. |

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

| | |
|------------------------|--|
| Ingestion: | No adverse effects expected, however, large amounts may cause nausea and vomiting. |
| Eye contact: | A severe eye irritant. Contamination of eyes can result in permanent injury. |
| Skin contact: | Contact with skin will result in irritation. |
| Inhalation: | Breathing in vapour, mists or aerosols may produce respiratory irritation. |
| Acute toxicity: | |

Product Name: STEOL CS370/MB
Substance No: 000000053537

Issued: 17/04/2018
Version: 1

Safety Data Sheet



Oral LD50 (rat): >2000 mg/kg
Dermal LD50 (rabbit): 2000-5000 mg/kg

Respiratory or skin sensitisation: Not expected to be a skin sensitizer.

Chronic effects: Not listed as carcinogenic according to the International Agency for Research on Cancer (IARC).

Specific Target Organ Toxicity (STOT) - single exposure: Not applicable.

Specific Target Organ Toxicity (STOT) - repeated exposure: Not applicable.

Aspiration hazard: Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Persistence/degradability: The material is readily biodegradable.

Bioaccumulative potential: No information available.

Mobility in soil: No information available.

Aquatic toxicity: Harmful to aquatic organisms. May cause long lasting harmful effects to aquatic life.

96hr LC50 (fish): 2.3 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Safety Data Sheet

**Classification of the chemical:**

Skin Irritation - Category 2

Eye Damage - Category 1

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Aquatic Toxicity - Category 3

Chronic Aquatic Toxicity - Category 3

Hazard Statement(s):

H315 Causes skin irritation.

H318 Causes serious eye damage.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Supplier Safety Data Sheet; 01/ 2016.

STEOL is a registered trademark of Stepan Company.

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.