

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: NAK Blend40

Recommended Use of the Chemical Food additive. and Restrictions on Use

Supplier: Ixom Operations Ptv Ltd

51 600 546 512 ABN:

Street Address: Level 8, 1 Nicholson Street

East Melbourne Victoria 3002

Australia

+61 3 9906 3000 **Telephone Number:**

Emergency Telephone: 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Corrosive to Metals - Category 1 Acute Oral Toxicity - Category 4 Skin Corrosion - Sub-category 1A Eye Damage - Category 1

SIGNAL WORD: DANGER





Hazard Statement(s):

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P234 Keep only in original container.

P260 Do not breathe mist, vapours, spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

Product Name: NAK Blend40 Issued: 20/02/2019 Substance No: 000000053713



Response:

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 Wash contaminated clothing before re-use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P390 Absorb spillage to prevent material damage.

Storage:

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): S6 Poison.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Sodium hydroxide	1310-73-2	10-<30%	H290 H314 H318
Potassium hydroxide	1310-58-3	10-<30%	H290 H302 H314 H318
Non hazardous component(s)	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. For all but the most minor symptoms arrange for patient to be seen by a doctor as soon as possible, either on site or at the nearest hospital.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eve Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Product Name: NAK Blend40 Issued: 20/02/2019 Substance No: 000000053713



Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the chemical:

Non-combustible material. Corrosive substance.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Neutralise residues with dilute acid. Collect and seal in properly labelled containers or drums for disposal. Caution - heat may be evolved on contact with water. After cleaning, flush away any residual traces with water.

7. HANDLING AND STORAGE

This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Keep out of reach of children. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Do not store in aluminium or galvanised containers nor use die-cast zinc or aluminium bungs; plastic bungs should be used. At temperatures greater than 40°C, tanks must be stress relieved. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Potassium hydroxide: Peak Limitation = 2 mg/m³ Sodium hydroxide: Peak Limitation = 2 mg/m³

Product Name: NAK Blend40 Issued: 20/02/2019 Substance No: 000000053713



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

Peak Limitation - a maximum or peak airborne concentration of a particular substance determined over the shortest analytically practicable period of time which does not exceed 15 minutes.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.













Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Colour:Golden AmberOdour:No specific odourSolubility:Miscible with water.

Specific Gravity:

Relative Vapour Density (air=1):

Vapour Pressure (20 °C):

Flash Point (°C):

Flammability Limits (%):

Autoignition Temperature (°C):

Boiling Point/Range (°C):

Plant (°C):

Not applicable

Not applicable

Not applicable

Not applicable

Not available

13.4 (1% w/v)

Product Name: NAK Blend40 Substance No: 000000053713 Issued: 20/02/2019 Version: 1



Freezing Point/Range (°C): -24

10. STABILITY AND REACTIVITY

Reactivity: Reacts violently with acids. Corrosive to aluminium, tin, and zinc.

No information available. **Chemical stability:**

Possibility of hazardous

reactions:

May react with ammonium salts liberating ammonia gas.

Conditions to avoid: Avoid contact with foodstuffs.

Incompatible materials: Incompatible with acids, ammonium salts, aluminium, tin, zinc.

Hazardous decomposition

products:

None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and Ingestion:

chemical burns to the gastrointestinal tract.

A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Eye contact:

Contamination of eyes can result in permanent injury.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin

burns.

Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product. For the constituent Potassium hydroxide:

Oral LD50 (rat): 273 mg/kg

Skin corrosion/irritation: Respiratory or skin

sensitisation:

Severe irritant (rabbit). No information available.

Chronic effects: No component contained in this material is listed as carcinogenic according to the International Agency for Research on Cancer (IARC).

No information available. **Aspiration hazard:**

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Persistence/degradability: No information available.

Bioaccumulative potential: No information available.

No information available. Mobility in soil:

Product Name: NAK Blend40 Issued: 20/02/2019 Substance No: 000000053713



13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No: 1719 **Transport Hazard Class:** 8 Corrosive

Packing Group:

CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE AND **Proper Shipping Name or**

POTASSIUM HYDROXIDE) **Technical Name:**

Hazchem or Emergency Action 2R

Code:

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea: DANGEROUS GOODS.

UN No: 1719

Transport Hazard Class: 8 Corrosive

Packing Group: Ш

Proper Shipping Name or CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE AND

Technical Name: POTASSIUM HYDROXIDE)

IMDG EMS Fire: F-A **IMDG EMS Spill:** S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1719

Transport Hazard Class: 8 Corrosive

Packing Group: Ш

Proper Shipping Name or CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE AND

Technical Name: POTASSIUM HYDROXIDE)

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Product Name: NAK Blend40 Issued: 20/02/2019 Substance No: 000000053713



Classification of the chemical:

Corrosive to Metals - Category 1 Acute Oral Toxicity - Category 4 Skin Corrosion - Sub-category 1A Eye Damage - Category 1

Hazard Statement(s):

H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage.

Poisons Schedule (SUSMP): S6 Poison.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

`Registry of Toxic Effects of Chemical Substances'. Ed. D. Sweet, US Dept. of Health & Human Services: Cincinatti, 2018.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: NAK Blend40 Issued: 20/02/2019 Substance No: 000000053713