

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** IMMUNITY (NO DYE)

**Recommended Use of the Chemical and Restrictions on Use** Sanitising hand cleaner.

**Supplier:** Ixom Operations Pty Ltd  
**ABN:** 51 600 546 512  
**Street Address:** Level 8, 1 Nicholson Street  
East Melbourne Victoria 3002  
Australia

**Telephone Number:** +61 3 9906 3000  
**Emergency Telephone:** 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

## 2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

### Classification of the chemical:

Flammable liquids - Category 2  
Eye Irritation - Category 2A

**SIGNAL WORD:** DANGER



### Hazard Statement(s):

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.

### Precautionary Statement(s):

#### Prevention:

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground or bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating, lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves / protective clothing / eye protection / face protection.

#### Response:

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P370+P378 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

#### Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

*Product Name:* IMMUNITY (NO DYE)  
*Substance No:* 000000053845

*Issued:* 17/02/2020  
*Version:* 1

# Safety Data Sheet

**Disposal:**

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

**Poisons Schedule (SUSMP):** None allocated.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Ethyl alcohol	64-17-5	>60%	H225 H319
Other ingredient(s)	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

**Inhalation:**

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

**Skin Contact:**

Not applicable.

**Eye Contact:**

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

**Ingestion:**

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Get to a doctor or hospital quickly.

**Indication of immediate medical attention and special treatment needed:**

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:**

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, fine water spray or water fog can be used.

**Hazchem or Emergency Action Code:** - 2YE

**Specific hazards arising from the chemical:**

Highly flammable liquid. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back. May form flammable vapour mixtures with air.

## Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon . Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use non-sparking tools. Collect and seal in properly labelled containers or drums for disposal. Wash area down with excess water.

## 7. HANDLING AND STORAGE

### Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Ethyl alcohol: 8hr TWA = 1880 mg/m<sup>3</sup> (1000 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

# Safety Data Sheet



## Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

## Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES.



Wear overalls and safety shoes. Always wash hands before smoking, eating, drinking or using the toilet.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Colour:</b>	Straw
<b>Odour:</b>	Ethereal
<b>Solubility:</b>	Miscible with water.
<b>Specific Gravity:</b>	ca. 0.8
<b>Relative Vapour Density (air=1):</b>	>1
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	21
<b>Flammability Limits (%):</b>	3.5-19 (for ethanol)
<b>Autoignition Temperature (°C):</b>	Not available
<b>Boiling Point/Range (°C):</b>	ca. 78
<b>pH:</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	No information available.
<b>Chemical stability:</b>	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
<b>Possibility of hazardous reactions:</b>	None known.
<b>Conditions to avoid:</b>	Avoid exposure to heat, sources of ignition, and open flame.
<b>Incompatible materials:</b>	Incompatible with oxidising agents.

# Safety Data Sheet



**Hazardous decomposition products:** Oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.

**Eye contact:** An eye irritant.

**Skin contact:** Not expected to be a skin irritant.

**Inhalation:** Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Acute toxicity:** No LD50 data available for the product.

**Respiratory or skin sensitisation:** No information available.

**Chronic effects:** No information available for the product.

**Mutagenicity:** No information available.  
**Carcinogenicity:** No information available.  
**Reproductive toxicity:** No information available.  
**Specific Target Organ Toxicity (STOT) - single exposure:** No information available.  
**Specific Target Organ Toxicity (STOT) - repeated exposure:** No information available.  
**Aspiration hazard:** No information available.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** Avoid contaminating waterways.

**Persistence/degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility in soil:** No information available.

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



**UN No:** 1170  
**Transport Hazard Class:** 3 Flammable Liquid  
**Packing Group:** II  
**Proper Shipping Name or Technical Name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**Hazchem or Emergency Action Code:** - 2YE

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 1170  
**Transport Hazard Class:** 3 Flammable Liquid  
**Packing Group:** II  
**Proper Shipping Name or Technical Name:** ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)  
**IMDG EMS Fire:** F-E  
**IMDG EMS Spill:** S-D

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 1170  
**Transport Hazard Class:** 3 Flammable Liquid  
**Packing Group:** II  
**Proper Shipping Name or Technical Name:** ETHYL ALCOHOL SOLUTION

## 15. REGULATORY INFORMATION

### **Classification:**

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

### **Classification of the chemical:**

Flammable liquids - Category 2

Eye Irritation - Category 2A

### **Hazard Statement(s):**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

**Poisons Schedule (SUSMP):** None allocated.

*Product Name:* IMMUNITY (NO DYE)

*Substance No:* 000000053845

*Issued:* 17/02/2020

*Version:* 1

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

### **Reason(s) for Issue:**

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.