

# SAFETY DATA SHEET



Revision date: 15-Aug-2022

Revision Number 1

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### Product identifier

Product Name BITUNAMEL 9052-1

Product Code(s) 000000054320

### Other means of identification

UN number 1999

Synonyms MANUFACTURER'S PRODUCT CODE: 220-5415

Pure substance/mixture Mixture

### Recommended use of the chemical and restrictions on use

Recommended use Potable primer for pipes and metal work.

Uses advised against No information available.

### Supplier

Bituminous Products Pty Ltd  
ABN No: 19 106 887 094  
33 Violet Street  
REVESBY NSW 2212

Business Phone: 02 9772 4433  
Facsimile: 02 9792 1016

### Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

## 2. HAZARDS IDENTIFICATION

### GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 3
Aspiration hazard	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

**SIGNAL WORD**

Danger

**Label elements**Flame  
Health hazard**Hazard statements**

H226 - Flammable liquid and vapor  
 H304 - May be fatal if swallowed and enters airways  
 H372 - Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements - Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical, ventilating, lighting equipment  
 Do not breathe fume, gas, mist, vapours, spray  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves / protective clothing / eye protection / face protection

**Precautionary Statements - Response**

Get medical advice/attention if you feel unwell  
 Specific treatment (see First aid on this SDS)  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Do NOT induce vomiting  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
 Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

**Other hazards which do not result in classification****General Hazards**

Poisons Schedule (SUSMP) 5

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixture**

Chemical name	CAS No.	Weight-%
Asphalt (Bitumen)	8052-42-4	40-<60
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	40-<60

**4. FIRST AID MEASURES****Description of first aid measures**

---

<b>General advice</b>	For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if symptoms occur.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician if symptoms occur.
<b>Ingestion</b>	Clean mouth with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** Aspiration risk: may cause lung damage if swallowed.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically. Product may be removed from skin using cotton wool pads soaked in castor oil or hand cleaner. Delayed pulmonary edema may occur.

**5. FIRE FIGHTING MEASURES****Suitable Extinguishing Media**

**Suitable Extinguishing Media** Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

**Specific hazards arising from the chemical** Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Pay attention to flashback. Flash back possible over considerable distance. Vapors can form explosive mixtures with air.

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Special protective actions for fire-fighters**

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**Hazchem code** 2W

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Evacuate personnel to safe areas. Avoid contact with skin, eyes, and clothing. Ensure

---

adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required. Wash thoroughly after handling. See section 8 for more information.

**Other information**

Ventilate the area.

**For emergency responders**

Use personal protection recommended in Section 8.

**Environmental precautions****Environmental precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up****Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up**

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Use non-sparking tools.

**7. HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Use personal protection equipment. Ensure adequate ventilation. Do not use pressure to empty drums.

**General hygiene considerations**

Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**Conditions for safe storage, including any incompatibilities****Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store away from foodstuffs. Keep container closed when not in use.

This material is a Scheduled Poison and must be stored, maintained and used in accordance with the relevant regulations.

**Incompatible materials**

Oxidizing agents.

**Poisons Schedule (SUSMP)**

5

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Limits**

No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Bitumen fumes: 8hr TWA = 5 mg/m<sup>3</sup>

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Appropriate engineering controls

#### **Engineering controls**

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

### Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



#### **Eye/face protection**

Glasses.

#### **Skin and body protection**

Wear suitable protective clothing. Overalls. Antistatic boots.

#### **Hand protection**

Impervious gloves.

#### **Respiratory protection**

If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

#### **Environmental exposure controls**

No information available.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Paint
<b>Color</b>	Black
<b>Odor</b>	Mineral turps Characteristic

**Odor threshold** No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	>149°C	None known
Flash point	38°C	CC (closed cup)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	7% volume	
Lower flammability or explosive limits	0.4% volume	
Vapor pressure	<3.3 kPa	None known
Vapor density	No data available	None known
Relative density	0.92 @25°C	None known
Water solubility	Immiscible in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	250°C	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

## 10. STABILITY AND REACTIVITY

Reactivity

**Reactivity** Reacts with strong oxidising agents.

Chemical stability

**Stability** Stable under normal conditions.

Explosion data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

Conditions to avoid

**Conditions to avoid** Heat, flames and sparks. Static discharge (electrostatic discharge).

Incompatible materials

**Incompatible materials** Oxidizing agents.

Hazardous decomposition products

**Hazardous decomposition products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity****Information on likely routes of exposure**

<b>Product Information</b>	No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:
<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.
<b>Eye contact</b>	May cause irritation.
<b>Skin contact</b>	May cause irritation.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Aspiration may cause pulmonary edema and pneumonitis.
<b>Symptoms</b>	Aspiration risk: may cause lung damage if swallowed.

**Numerical measures of toxicity - Product Information**

Refer to component information below.

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (Bitumen)	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 94.4 mg/m <sup>3</sup> ( Rat ) 4.5 h
Solvent naphtha (petroleum), medium aliphatic	> 25 mL/kg ( Rat )	> 3000 mg/kg ( Rabbit )	> 13 mg/L ( Rat ) 4 h

See section 16 for terms and abbreviations

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	No information available.
<b>Serious eye damage/eye irritation</b>	No information available.
<b>Respiratory or skin sensitization</b>	No information available.
<b>Germ cell mutagenicity</b>	Not classified.
<b>Carcinogenicity</b>	Not classified.
<b>Reproductive toxicity</b>	Not classified.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure. Classification is based on mixture calculation methods based on component data.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. Classification is based on mixture calculation methods based on component data.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity****Ecotoxicity** Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent naphtha (petroleum), medium aliphatic	EC50: =450mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =800mg/L (96h, Pimephales promelas)	-	EC50: >100mg/L (48h, Daphnia magna)

**Persistence and degradability****Persistence and degradability** No information available.**Bioaccumulative potential****Bioaccumulation** No information available.**Component Information**

Chemical name	Partition coefficient
Asphalt (Bitumen)	>6

**Mobility****Mobility in soil****Mobility** No information available.**Other adverse effects****13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. TRANSPORT INFORMATION****ADG**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

**UN number** 1999  
**Proper shipping name** TARS, LIQUID  
**Hazard class** 3  
**Packing group** III  
**Hazchem code** 2W

**IATA**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN number** 1999  
**UN proper shipping name** TARS, LIQUID



**Transport hazard class(es)** 3  
**Packing group** III

**IMDG**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN number** 1999  
**UN proper shipping name** TARS, LIQUID  
**Transport hazard class(es)** 3  
**Packing group** III  
**Marine pollutant** No

**15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

**Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)**

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)  
**Poisons Schedule (SUSMP)** 5

**Major hazard (accident/incident planning) regulation**

Verify that license requirements are met

**Hazardous chemical**

Liquids that meet the criteria for Class 3 Packing Group II or III

**Threshold quantity (T)**

50 000

**International Inventories****AIC**

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals or are exempt.

**Legend:**

**AIC - Australian Inventory of Industrial Chemicals**

**International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**16. OTHER INFORMATION**

Supplier Safety Data Sheet 02/ 2018

**Reason(s) For Issue:** First Issue Primary SDS

**Issuing Date:** 15-Aug-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

**Revision Note:**

The symbol (\*) in the margin of this SDS indicates that this line has been revised.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

**Key literature references and sources for data used to compile the SDS**

EPA (Environmental Protection Agency)  
 Acute Exposure Guideline Level(s) (AEGl(s))  
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
 U.S. Environmental Protection Agency High Production Volume Chemicals  
 Food Research Journal  
 Hazardous Substance Database  
 International Uniform Chemical Information Database (IUCLID)  
 Japan GHS Classification  
 Australian Industrial Chemicals Introduction Scheme (AICIS)  
 NIOSH (National Institute for Occupational Safety and Health)  
 National Library of Medicine's ChemID Plus (NLM CIP)  
 National Library of Medicine's PubMed database (NLM PUBMED)  
 National Toxicology Program (NTP)  
 New Zealand's Chemical Classification and Information Database (CCID)  
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
 Organization for Economic Co-operation and Development Screening Information Data Set  
 RTECS (Registry of Toxic Effects of Chemical Substances)  
 World Health Organization

**Disclaimer**

**This Safety Data Sheet has been compiled in accordance with GHS Guidance for the preparation of Safety Data Sheets and COP Preparation of SDS for Hazardous Chemicals Safe Work Australia.**

**Where applicable, specific chemical composition details are provided to allow the product to be classified according to UN Number, HAZCHEM coding etc. The information contained herein is based on the data available to BITUMINOUS PRODUCTS PTY LTD from both our suppliers and technical sources and from recognized published references and is believed to be both accurate and reliable. BITUMINOUS PRODUCTS PTY LTD has made no effort to censor or to conceal deleterious aspects of this product. Since we cannot anticipate or control the many different conditions under which this information and our products may be used, each user should review these recommendations in the specific context of the intended application and confirm whether they are appropriate.**

**Due care should be taken to make sure that the use or disposal of the product is in compliance with the appropriate Federal, State, and Local Government regulations.**

**End of Safety Data Sheet**