

SAFETY DATA SHEET



Revision date: 17-Aug-2022

Revision Number 1

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name HFK CUTTER
Product Code(s) 000000054332

Other means of identification

UN number 3082
CAS No. 64741-44-2
Synonyms MANUFACTURER'S PRODUCT CODE: 220-2220
Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Viscosity reduction of bitumen.
Uses advised against No information available.

Supplier

Bituminous Products Pty Ltd
ABN No: 19 106 887 094
33 Violet Street
REVESBY NSW 2212

Business Phone: 02 9772 4433
Facsimile: 02 9792 1016

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 4
Aspiration hazard	Category 1
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

SIGNAL WORD

Danger

Label elements

Environment
Health hazard
Exclamation mark

**Hazard statements**

H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Do not breathe fume, gas, mist, vapours, spray
Wash hands thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing
Avoid release to the environment

Precautionary Statements - Response

Specific treatment (see First aid on this SDS)
Get medical advice/attention if you feel unwell
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician
IF ON SKIN: Wash with plenty of soap and water
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Collect spillage

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

AUH066 - Repeated exposure may cause skin dryness or cracking

Poisons Schedule (SUSMP) 5

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical name	CAS No.	Weight-%
Distillates, petroleum, straight run middle	64741-44-2	100

4. FIRST AID MEASURES

Description of first aid measures

General advice	For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
Skin contact	Wash skin with soap and water. Call a physician if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention if symptoms occur.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes, and clothing. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms	Irritation. Erythema (skin redness). Vapors may cause drowsiness and dizziness. Aspiration risk: may cause lung damage if swallowed.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically. Delayed pulmonary edema may occur.
---------------------------	---

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media	Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.
-------------------------------------	---

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Combustible liquid. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3Z

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not breathe vapor or mist. Avoid contact with skin and eyes. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Do not touch or walk through spilled material. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Wash thoroughly after handling. See section 8 for more information.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not breathe vapor or mist. Avoid contact with skin and eyes. Ensure adequate ventilation. Remove all sources of ignition. Use personal protection equipment. Wash thoroughly after handling.

General hygiene considerations Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from

foodstuffs and sources of heat or ignition. Keep container closed when not in use.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison and must be stored, maintained and used in accordance with the relevant regulations.

Incompatible materials Oxidizing agents.

Poisons Schedule (SUSMP) 5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Oil mist, refined mineral: 8hr TWA = 5 mg/m³

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



Eye/face protection	Glasses.
Skin and body protection	Wear suitable protective clothing. Boots. Overalls.
Hand protection	Impervious gloves.
Respiratory protection	If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.
Environmental exposure controls	No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available.
Color	Colourless
Odor	Characteristic Kerosene
Odor threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	
Boiling point / boiling range	>149°C	
Flash point	>65°C	CC (closed cup)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	5% volume	
Lower flammability or explosive limits	0.7% volume	
Vapor pressure	<0.37 kPa	
Vapor density	No data available	
Relative density	0.81 @25°C	
Water solubility	Immiscible in water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	230°C	
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

10. STABILITY AND REACTIVITY

Reactivity

Reactivity Reacts with strong oxidising agents.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation. May cause drowsiness or dizziness. Harmful by inhalation.

Eye contact May cause irritation.

Skin contact Causes skin irritation. Prolonged skin contact may defat the skin and produce dermatitis. Repeated exposure may cause skin dryness or cracking.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Aspiration may cause pulmonary edema and pneumonitis.

Symptoms Irritation. Erythema (skin redness). Vapors may cause drowsiness and dizziness. Aspiration risk: may cause lung damage if swallowed.

Numerical measures of toxicity - Product Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates, petroleum, straight run middle	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 1.78 mg/L (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not classified.
Reproductive toxicity	Not classified.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Ecotoxicity Keep out of waterways. Toxic to aquatic life with long lasting effects.

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Distillates, petroleum, straight run middle	3.9 - 6

Mobility

Mobility in soil No information available.

Other adverse effects**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**ADG**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

UN number	3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS DISTILLATES (PETROLEUM), STRAIGHT RUN MIDDLE)
Hazard class	9
Packing group	III
Hazchem code	•3Z

IATA

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS DISTILLATES (PETROLEUM), STRAIGHT RUN MIDDLE)
Transport hazard class(es)	9
Packing group	III

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS DISTILLATES (PETROLEUM), STRAIGHT RUN MIDDLE) MARINE POLLUTANT
Transport hazard class(es)	9
Packing group	III
IMDG EMS Fire	F-A
IMDG EMS Spill	S-F
Marine pollutant	Yes

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****Australia**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the provisions of the Australian Code for the Transport of Dangerous Goods by Road and Rail when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs.

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule (SUSMP) 5

International Inventories

AIIC This material is listed on the Australian Inventory of Industrial Chemicals.

Legend:

AIIC - Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Supplier Safety Data Sheet 02/ 2018

Reason(s) For Issue: First Issue Primary SDS

Issuing Date: 17-Aug-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australian Industrial Chemicals Introduction Scheme (AICIS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
RTECS (Registry of Toxic Effects of Chemical Substances)
World Health Organization

Disclaimer

This Safety Data Sheet has been compiled in accordance with GHS Guidance for the preparation of Safety Data Sheets and COP Preparation of SDS for Hazardous Chemicals Safe Work Australia.

Where applicable, specific chemical composition details are provided to allow the product to be classified according to UN Number, HAZCHEM coding etc. The information contained herein is based on the data available to BITUMINOUS PRODUCTS PTY LTD from both our suppliers and technical sources and from recognized published references and is believed to be both accurate and reliable. BITUMINOUS PRODUCTS PTY LTD has made no effort to censor or to conceal deleterious aspects of this product. Since we cannot anticipate or control the many different conditions under which this information and our products may be used, each user should review these recommendations in the specific context of the intended application and confirm whether they are appropriate.

Due care should be taken to make sure that the use or disposal of the product is in compliance with the appropriate Federal, State, and Local Government regulations.

End of Safety Data Sheet