

SAFETY DATA SHEET



Revision date: 01-Aug-2024

Revision Number 3

Section 1: Identification

Product identifier

Product Name BLACKJACK TROWELABLE PUTTY

Product Code(s) 000000054335

Other means of identification

UN number or ID number 1999

Synonyms MANUFACTURER'S PRODUCT CODE: 220-5010; Blackjack QD Trowel Grade; 220-5635; 220-563501.

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Anti-corrosive, insulating and waterproofing paint.

Uses advised against No information available.

Details of manufacturer or importer

Supplier

Bituminous Products Pty Ltd
ABN No: 19 106 887 094
33 Violet Street
REVESBY NSW 2212

Business Phone: 02 9772 4433
Facsimile: 02 9792 1016

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

Section 2: Hazard identification

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

GHS Classification

Flammable liquids	Category 3
Aspiration hazard	Category 1
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A

Specific target organ toxicity (repeated exposure)	Category 2
----------------------------------------------------	------------

Label elements

Flame

Health hazard

**Signal word**

DANGER

Hazard statements

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H320 - Causes eye irritation

H340 - May cause genetic defects

H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Use explosion-proof electrical/ ventilating / lighting/ .? / equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands and face thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/clothing and eye/face protection.

Use personal protective equipment as required.

Avoid release to the environment.

Precautionary Statements - Response

Get medical advice/attention if you feel unwell.

Specific treatment (see First aid on this SDS).

IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use CO2, dry chemical, or foam for extinction.

Collect spillage.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Other hazards which do not result in classification

Repeated exposure may cause skin dryness or cracking.

Causes mild skin irritation.

Harmful to aquatic life with long lasting effects.

Section 3: Composition and information on ingredients

Chemical name	CAS No.	Weight-%
Asphalt (Bitumen)	8052-42-4	20-<60
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	10-<30
Solvent naphtha (petroleum), light aromatic	64742-95-6	1-<10
Other component(s)	-	to 100

Section 4: First aid measures**Description of first aid measures**

General advice	For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if symptoms occur.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. (Call a physician if symptoms occur).
Ingestion	Clean mouth with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Irritation. May cause redness and tearing of the eyes. Erythema (skin redness). Aspiration risk: may cause lung damage if swallowed.

Effects of Exposure No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. Aspiration may cause pulmonary edema and pneumonitis. Delayed pulmonary edema may occur.

Section 5: Firefighting measures**Suitable Extinguishing Media**

Suitable extinguishing media Dry chemical, CO2, water spray or regular foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Flammable. Risk of ignition. Keep product and empty container away from heat and sources of ignition. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Pay attention to flashback. Flash back possible over considerable distance. Vapors can form explosive mixtures with air. Environmentally hazardous.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code 2W

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required. Wash thoroughly after handling. See section 8 for more information.

Other information Ventilate the area.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Use non-sparking tools.

Section 7: Handling and storage

Precautions for safe handling

Advice on safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Ensure adequate ventilation. Use personal protection equipment. Wash thoroughly after handling. Do not use pressure to empty drums.

General hygiene considerations Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store away from foodstuffs. Keep container closed when not in use.

This material is a Scheduled Poison and must be stored, maintained and used in accordance with the relevant regulations.

Incompatible materials Oxidizing agents.

Section 8: Exposure controls and personal protection**Control parameters**

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Chemical name	Australia	New Zealand	ACGIH TLV
Asphalt (Bitumen) 8052-42-4	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 0.5 mg/m ³ Benzene-soluble aerosol fume, inhalable particulate matter

Chemical name	European Union	United Kingdom	Germany DFG
Asphalt (Bitumen) 8052-42-4	-	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 1.5 mg/m ³ Peak: 3 mg/m ³ Sk*

Chemical name	Australia	ACGIH	European Union
Asphalt (Bitumen) 8052-42-4	-	2.5 µg/L	-

Bitumen fumes: 8hr TWA = 5 mg/m³

Mineral turpentine: 8hr TWA = 480 mg/m³

Oil mist, refined mineral: 8hr TWA = 5 mg/m³

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the

physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.



Eye/face protection	Goggles.
Skin and body protection	Wear suitable protective clothing. Overalls. Antistatic boots.
Hand protection	Impervious gloves.
Respiratory protection	If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.
Environmental exposure controls	No information available.
Thermal hazards	No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available
Color	Black
Odor	Characteristic
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash point	38°C	CC (closed cup)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

Section 10: Stability and reactivity

Reactivity

Reactivity Reacts with strong oxidising agents.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Static discharge (electrostatic discharge).

Incompatible materials

Incompatible materials Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂).

Section 11: Toxicological information

Information on likely routes of exposure

Product Information No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage.

Eye contact Causes eye irritation.

Skin contact Causes mild skin irritation. Repeated exposure may cause skin dryness or cracking.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.

Symptoms Irritation. May cause redness and tearing of the eyes. Erythema (skin redness). Aspiration risk: may cause lung damage if swallowed.

Acute toxicity

Numerical measures of toxicity - Product Information

No information available

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (Bitumen)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Naphtha (petroleum), hydrodesulfurized heavy	> 5000 mg/kg (Rat)	> 4 mL/kg (Rat)	-
Solvent naphtha (petroleum), light aromatic	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes mild skin irritation. Classification is based on mixture calculation methods based on component data.
Serious eye damage/eye irritation	Causes eye irritation. Classification is based on mixture calculation methods based on component data.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	May cause genetic defects. Classification is based on mixture calculation methods based on component data.
Carcinogenicity	May cause cancer. Classification is based on mixture calculation methods based on component data. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Asphalt (Bitumen) - 8052-42-4	-	-	Group 2B
Naphtha (petroleum), hydrodesulfurized heavy - 64742-82-1	Carc. 1B	Carc. 1B	-
Solvent naphtha (petroleum), light aromatic - 64742-95-6	Carc. 1A	Carc. 1B	-

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure. Classification is based on mixture calculation methods based on component data.
Aspiration hazard	May be fatal if swallowed and enters airways. Classification is based on mixture calculation methods based on component data.

Section 12: Ecological information**Ecotoxicity**

Aquatic ecotoxicity Keep out of waterways. Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Solvent naphtha (petroleum), light aromatic	-	LC50: =9.22mg/L (96h, Oncorhynchus mykiss)	-	EC50: =6.14mg/L (48h, Daphnia magna)

Terrestrial ecotoxicity There is no data for this product.

Chemical name	Earthworm	Avian	Honeybees
Solvent naphtha (petroleum), light aromatic	-	Acute Oral Toxicity: LD50 > 2250 mg/kg (Colinus virginianus) Source: IUCLID Dietary Toxicity: LC50 > 6500 ppm (Colinus virginianus 5 Days) Source: IUCLID	-

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Asphalt (Bitumen)	6

Mobility

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.

See section 8 for more information

Section 14: Transport information

ADG Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number or ID number 1999
Proper shipping name TARS, LIQUID
Transport hazard class(es) 3
Packing group III
Hazchem code 2W

IATA Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 1999
UN proper shipping name TARS, LIQUID
Transport hazard class(es) 3
Packing group III

IMDG Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 1999
UN proper shipping name TARS, LIQUID
Transport hazard class(es) 3
Packing group III
Marine pollutant Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as a hazardous substance in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).
 Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)
Poison Schedule Number 5

Australian Industrial Chemicals Introduction Scheme (AICIS)

Contact supplier for inventory compliance status

Chemical name	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Asphalt (Bitumen) - 8052-42-4	Present	-
Naphtha (petroleum), hydrodesulfurized heavy - 64742-82-1	Present	-

Chemical name	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Solvent naphtha (petroleum), light aromatic - 64742-95-6	Present	-

Illicit Drug Precursors/Reagents

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III

Threshold quantity (T)

50 000

International Inventories

AIIC	All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals or are exempt.
NZIoC	Contact supplier for inventory compliance status.
TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
IECSC	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.

Legend:

AIIC- Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Other information

Reason(s) For Issue:	Revised Primary SDS Addition/Change of synonymous name(s)
Prepared By	This Safety Data Sheet has been prepared by IXOM Operations Pty Ltd (Toxicology and SDS Services).
Revision date:	01-Aug-2024

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend**

SVHC: Substances of Very High Concern for Authorization:
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
 STOT: Specific Target Organ Toxicity
 ATE: Acute Toxicity Estimate
 LC50: 50% Lethal Concentration
 LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGl(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 Australian Industrial Chemicals Introduction Scheme (AICIS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Disclaimer

This Safety Data Sheet has been compiled in accordance with GHS Guidance for the preparation of Safety Data Sheets and COP Preparation of SDS for Hazardous Chemicals Safe Work Australia.

Where applicable, specific chemical composition details are provided to allow the product to be classified according to UN Number, HAZCHEM coding etc. The information contained herein is based on the data available to BITUMINOUS PRODUCTS PTY LTD from both our suppliers and technical sources and from recognized published references and is believed to be both accurate and reliable. BITUMINOUS PRODUCTS PTY LTD has made no effort to censor or to conceal deleterious aspects of this product. Since we cannot anticipate or control the many different conditions under which this information and our products may be used, each user should review these recommendations in the specific context of the intended application and confirm whether they are appropriate.

Due care should be taken to make sure that the use or disposal of the product is in compliance with the appropriate Federal, State, and Local Government regulations.

End of Safety Data Sheet