

SAFETY DATA SHEET



Revision date: 14-Dec-2022

Revision Number 1

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name CUTBACK AMC00H

Product Code(s) 000000054346

Other means of identification

Synonyms MANUFACTURER'S PRODUCT CODE: 220-1055

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Primer.

Uses advised against No information available.

Supplier

Bituminous Products Pty Ltd
ABN No: 19 106 887 094
33 Violet Street
REVESBY NSW 2212

Business Phone: 02 9772 4433
Facsimile: 02 9792 1016

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Not classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 4
Aspiration hazard	Category 1
Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3

SIGNAL WORD

Danger

Label elements

Health hazard
Exclamation mark



Hazard statements

H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Avoid breathing dust / fume / gas / mist / vapours / spray
Wash hands thoroughly after handling
Use only outdoors or in a well-ventilated area
Wear protective gloves / protective clothing / eye protection / face protection

Precautionary Statements - Response

Specific treatment (see First aid on this SDS)
IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

AUH066 - Repeated exposure may cause skin dryness or cracking
Harmful to aquatic life with long lasting effects

General Hazards

Poisons Schedule (SUSMP) 5

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS No.	Weight-%
Asphalt (Bitumen)	8052-42-4	40-<60
Kerosene	8008-20-6	40-<60

4. FIRST AID MEASURES

Description of first aid measures

General advice	For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if symptoms occur.
Skin contact	IF ON SKIN: Wash with plenty of soap and water. Call a physician if symptoms occur.
Ingestion	Clean mouth with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms	Aspiration risk: may cause lung damage if swallowed.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically. Product may be removed from skin using cotton wool pads soaked in castor oil or hand cleaner. Aspiration may cause pulmonary edema and pneumonitis. Delayed pulmonary edema may occur.
---------------------------	---

5. FIRE FIGHTING MEASURES**Suitable Extinguishing Media**

Suitable Extinguishing Media	Dry chemical, CO ₂ , water spray or regular foam.
-------------------------------------	--

Unsuitable extinguishing media	No information available.
---------------------------------------	---------------------------

Specific hazards arising from the chemical

Specific hazards arising from the chemical	Combustible liquid. May form flammable vapour mixtures with air. Environmentally hazardous.
---	---

Hazardous combustion products	Carbon monoxide. Carbon dioxide (CO ₂).
--------------------------------------	---

Special protective actions for fire-fighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions	Evacuate personnel to safe areas. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch or walk
-----------------------------	--

through spilled material. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required. Wash thoroughly after handling. See section 8 for more information.

Other information

Ventilate the area.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. Remove ignition sources. Provide adequate ventilation. Do not touch or walk through spilled material. Dike far ahead of spill; use dry sand to contain the flow of material. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use personal protective equipment as required. Use non-sparking tools.

7. HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Use personal protection equipment. Ensure adequate ventilation.

General hygiene considerations

Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep in a dry, cool and well-ventilated place. Store away from foodstuffs and sources of heat or ignition. Keep container closed when not in use.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison and must be stored, maintained and used in accordance with the relevant regulations.

Incompatible materials

Oxidizing agents.

Poisons Schedule (SUSMP)

5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Limits**

No value assigned for this specific material by Safe Work Australia. However, Workplace

Exposure Standard(s) for constituent(s):

Bitumen fumes: 8hr TWA = 5 mg/m³

Oil mist, refined mineral: 8hr TWA = 5 mg/m³

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls**Engineering controls**

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

**Eye/face protection**

Glasses.

Skin and body protection

Wear suitable protective clothing. Overalls. Antistatic boots.

Hand protection

Impervious gloves.

Respiratory protection

If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator or an air supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls

No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	Paint
Color	Black
Odor	Kerosene Characteristic
Odor threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	>149°C	None known
Flash point	>65°C	CC (closed cup)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	<3.3 kPa	None known
Vapor density	No data available	None known
Relative density	0.94 @25°C	None known
Water solubility	Immiscible in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	>250°C	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information**10. STABILITY AND REACTIVITY**Reactivity

Reactivity Reacts with strong oxidising agents.

Chemical stability

Stability Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Acute toxicity**Information on likely routes of exposure**

Product Information	No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:
Inhalation	Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Aspiration into lungs can produce severe lung damage.
Eye contact	May cause irritation.
Skin contact	Causes skin irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Aspiration may cause pulmonary edema and pneumonitis.
Symptoms	Aspiration risk: may cause lung damage if swallowed.

Numerical measures of toxicity - Product Information

Refer to component information below.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (Bitumen)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Kerosene	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes skin irritation. Classification is based on mixture calculation methods based on component data.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	May cause drowsiness or dizziness. Classification is based on mixture calculation methods based on component data.
STOT - repeated exposure	No information available.
Aspiration hazard	May be fatal if swallowed and enters airways. Classification is based on mixture calculation

methods based on component data.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Keep out of waterways. Harmful to aquatic life with long lasting effects.

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Asphalt (Bitumen)	6

Mobility

Mobility in soil

Mobility No information available.

Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. TRANSPORT INFORMATION

ADG

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

IATA

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

IMDG

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Not classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule (SUSMP) 5

International Inventories

AIIC

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.

Legend:

AIIC- Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Supplier Safety Data Sheet 02/ 2018

Reason(s) For Issue: First Issue Primary SDS

Issuing Date: 14-Dec-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australian Industrial Chemicals Introduction Scheme (AICIS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
RTECS (Registry of Toxic Effects of Chemical Substances)
World Health Organization

Disclaimer

This Safety Data Sheet has been compiled in accordance with GHS Guidance for the preparation of Safety Data Sheets and COP Preparation of SDS for Hazardous Chemicals Safe Work Australia.

Where applicable, specific chemical composition details are provided to allow the product to be classified according to UN Number, HAZCHEM coding etc. The information contained herein is based on the data available to BITUMINOUS PRODUCTS PTY LTD from both our suppliers and technical sources and from recognized published references and is believed to be both accurate and reliable. BITUMINOUS PRODUCTS PTY LTD has made no effort to censor or to conceal deleterious aspects of this product. Since we cannot anticipate or control the many different conditions under which this information and our products may be used, each user should review these recommendations in the specific context of the intended application and confirm whether they are appropriate.

Due care should be taken to make sure that the use or disposal of the product is in compliance with the appropriate Federal, State, and Local Government regulations.

End of Safety Data Sheet