

SAFETY DATA SHEET



Revision date: 26-Sep-2022

Revision Number 1

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier

Product Name DETERGE X
Product Code(s) 000000054402

Other means of identification

UN number 3266

Recommended use of the chemical and restrictions on use

Recommended use Cleaning agent.
Uses advised against No information available.

Supplier

Ixom Operations Pty Ltd
ABN: 51 600 546 512
Level 8, 1 Nicholson Street
Melbourne 3000
Australia

Telephone Number: +61 3 9906 3000

Emergency telephone number

Emergency telephone number **1 800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1

SIGNAL WORD

Danger

Label elements

Corrosion

**Hazard statements**

H314 - Causes severe skin burns and eye damage

Precautionary Statements - Prevention

Do not breathe fume, gas, mist, vapours, spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves / protective clothing / eye protection / face protection

Precautionary Statements - Response

Specific treatment (see First aid on this SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

Poisons Schedule (SUSMP) 6

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Chemical name	CAS No.	Weight-%
Sodium hydroxide	1310-73-2	<10
Disodium trioxosilicate	6834-92-0	<10
Xylene	1330-20-7	<10
Sodium polyethylene phosphate ester	39464-69-2	<10
Non hazardous component(s)	-	to 100

4. FIRST AID MEASURES**Description of first aid measures****General advice**

For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. Call a physician if symptoms occur.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician.

Ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water.

Get immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms Irritation/Corrosion. Erythema (skin redness). Burning.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES**Suitable Extinguishing Media**

Suitable Extinguishing Media Dry chemical, CO2, water spray or regular foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Corrosive hazard. Wear protective gloves/clothing and eye/face protection.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code 2X

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Evacuate personnel to safe areas. Avoid contact with skin, eyes and inhalation of vapors. Ensure adequate ventilation. Stop leak if you can do it without risk. Use personal protective equipment as required.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Avoid contact with skin and eyes. Do not breathe vapor or mist. Keep out of reach of children. Use personal protection equipment. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from foodstuffs. Keep container closed when not in use.

This material is a Scheduled Poison and must be stored, maintained and used in accordance with the relevant regulations.

Incompatible materials Acids. Aluminium. Tin. Zinc. Die cast metals.

Poisons Schedule (SUSMP) 6

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters**

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Sodium hydroxide: Peak Limitation = 2 mg/m³

Xylene (o-, m-, p- isomers): 8hr TWA = 350 mg/m³ (80 ppm), 15 min STEL = 655 mg/m³ (150 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

Peak Limitation - a maximum or peak airborne concentration of a particular substance determined over the shortest analytically practicable period of time which does not exceed 15 minutes.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Ensure that eyewash stations and safety showers are close to the workstation location. Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the

physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Eye/face protection	Tight sealing safety goggles. If splashes are likely to occur:. Face protection shield.
Skin and body protection	Boots. Apron. Overalls.
Hand protection	Impervious gloves.
Respiratory protection	If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.
Environmental exposure controls	No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available.
Color	No information available.
Odor	Xylene
Odor threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	13.4 ± 0.2	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash point	Not applicable	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	Not applicable	
Lower flammability or explosive limits	Not applicable	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.045 @20°C	None known
Water solubility	Miscible in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	Not applicable	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

10. STABILITY AND REACTIVITYReactivity**Reactivity** Reacts with strong acids.Chemical stability**Stability** Stable under normal conditions.Explosion data**Sensitivity to mechanical impact** None.**Sensitivity to static discharge** None.Possibility of hazardous reactions**Possibility of hazardous reactions** Contact with metals may evolve flammable hydrogen gas.Conditions to avoid**Conditions to avoid** Do not contaminate food or feed stuffs.Incompatible materials**Incompatible materials** Acids. Aluminium. Tin. Zinc. Die cast metals.Hazardous decomposition products**Hazardous decomposition products** Carbon oxides. Nitrogen oxides.**11. TOXICOLOGICAL INFORMATION**Acute toxicityInformation on likely routes of exposure**Product Information** No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:**Inhalation** May cause irritation.**Eye contact** Causes serious eye damage.**Skin contact** Contact causes severe skin irritation and possible burns.**Ingestion** Can burn mouth, throat, and stomach.**Symptoms** Irritation/Corrosion. Erythema (skin redness). Burning.Numerical measures of toxicity - Product Information

Refer to component information below.

Numerical measures of toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Sodium hydroxide	-	= 1350 mg/kg (Rabbit)	-

Disodium trioxosilicate	= 1153 mg/kg (Rat)	-	-
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 29.08 mg/L (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes burns. Classification is based on mixture calculation methods based on component data.
Serious eye damage/eye irritation	Causes serious eye damage. Classification is based on mixture calculation methods based on component data.
Respiratory or skin sensitization	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not classified.
Reproductive toxicity	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified.
Aspiration hazard	Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity Keep out of waterways.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Sodium hydroxide	-	LC50: =45.4mg/L (96h, Oncorhynchus mykiss)	-	-
Disodium trioxosilicate	-	LC50: =210mg/L (96h, Brachydanio rerio)	-	EC50: =216mg/L (96h, Daphnia magna)
Xylene	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

		promelas) LC50: =780mg/L (96h, Cyprinus carpio)		
--	--	---	--	--

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Xylene	2.77 - 3.15

Mobility

Mobility in soil No information available.

Other adverse effects**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**ADG**

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number 3266
Proper shipping name CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM HYDROXIDE)
Hazard class 8
Packing group II
Hazchem code 2X

IATA

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 3266
UN proper shipping name CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM HYDROXIDE)
Transport hazard class(es) 8
Packing group II

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 3266
UN proper shipping name CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM HYDROXIDE)

Transport hazard class(es)	8
Packing group	II
IMDG EMS Fire	F-A
IMDG EMS Spill	S-B
Marine pollutant	No

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule (SUSMP) 6

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Xylene - 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed isomers

International Inventories

AiIC

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals or are exempt.

Legend:

AiIC - Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Reason(s) For Issue: First Issue Primary SDS

Issuing Date: 26-Sep-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheetLegend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AEGl(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 Japan GHS Classification
 Australian Industrial Chemicals Introduction Scheme (AICIS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 RTECS (Registry of Toxic Effects of Chemical Substances)
 World Health Organization

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet