# **SAFETY DATA SHEET**



Revision date: 19-Jun-2023

**Revision Number** 1

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product identifier** 

DODECYLTRIMETHYL AMMONIUM CHLORIDE 50% **Product Name** 

000000054471 Product Code(s)

Other means of identification

**UN** number 2920

**DTAC 50% Synonyms** 

Recommended use of the chemical and restrictions on use

Recommended use Mining chemical.

For industrial use only.

Uses advised against No information available

Supplier

Ixom Operations Pty Ltd ABN: 51 600 546 512 Level 8, 1 Nicholson Street Melbourne 3000

Australia

Telephone Number: +61 3 9906 3000

### Emergency telephone number

Emergency telephone number 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

### 2. HAZARDS IDENTIFICATION

### **GHS Classification**

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 3
Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1

Revision Number 1

#### SIGNAL WORD

Danger

#### Label elements

Corrosion

Flame

**Exclamation mark** 

Environment



#### **Hazard statements**

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

H313 - May be harmful in contact with skin

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

#### **Precautionary Statements - Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Do not breathe fume, gas, mist, vapours, spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves / protective clothing / eye protection / face protection

Avoid release to the environment

### **Precautionary Statements - Response**

Specific treatment (see First aid on this SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN: Wash with plenty of soap and water

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet to extinguish.

Collect spillage

### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

### Other hazards which do not result in classification

Poisons Schedule (SUSMP)

Revision Number 1

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### <u>Mixture</u>

Chemical name	CAS No.	Weight-%
1-Dodecanaminium, N,N,N-trimethyl-, chloride	112-00-5	50-60
Ethyl alcohol (Ethanol)	64-17-5	30-40
Other component(s)	-	to 100

### 4. FIRST AID MEASURES

Description of first aid measures

General advice For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New

Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.

**Inhalation** Remove to fresh air. Call a physician if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Call a physician immediately.

**Skin contact** IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off

immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention

immediately if symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting.

Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Do not breathe fume, gas, mist, vapours, spray. Avoid

contact with skin, eyes, and clothing. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information.

Most important symptoms and effects, both acute and delayed

Symptoms Irritation/Corrosion. May cause redness and tearing of the eyes. Erythema (skin redness).

Burning.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically. Can cause corneal burns.

### 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media** 

Suitable Extinguishing Media Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal

protein foam can be used.

Unsuitable extinguishing media High volume water jet.

Specific hazards arising from the chemical

Specific hazards arising from the Flammable. Risk of ignition. May form flammable vapour mixtures with air. Keep product

YL AMMONIUM Revision date: 19-Jun-2023

Revision Number 1

**chemical** and empty container away from heat and sources of ignition. Fire residues and

contaminated fire extinguishing water must be disposed of in accordance with local

regulations.

Hazardous combustion products Carbon oxides. Nitrogen oxides.

Special protective actions for fire-fighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

Hazchem code •3V

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes, and clothing. Do not breathe vapor or mist. Ensure adequate

ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Use personal protective equipment as required. See

section 8 for more information.

For emergency responders In the case of vapor formation use a respirator with an approved filter. Remove all sources

of ignition.

**Environmental precautions** 

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes. Do not breathe vapor or mist. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Keep in an area equipped with sprinklers. Take precautionary measures against static discharges. Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof. Use personal protection equipment. Wash thoroughly after handling.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Revision Number 1

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct

sunlight. Protect from moisture. Store away from foodstuffs and sources of heat or ignition. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep out of the reach of children. Keep container closed when

not in use.

This material is a Scheduled Poison and must be stored, maintained and used in

accordance with the relevant regulations.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents. Strong reducing agents.

Poisons Schedule (SUSMP) 6

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

**Exposure Limits** No value assigned for this specific material by Safe Work Australia. However, Workplace

Exposure Standard(s) for constituent(s):

Chemical name	Australia	ACGIH TLV
Ethyl alcohol (Ethanol)	8hr TWA: 1880 mg/m³ (1000 ppm)	
64-17-5		

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

#### **Appropriate engineering controls**

#### **Engineering controls**

Ensure that eyewash stations and safety showers are close to the workstation location. Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

#### Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.

Revision Number 1

Revision date: 19-Jun-2023











Tight sealing safety goggles. If splashes are likely to occur:. Face protection shield. Eye/face protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Skin and body protection

Antistatic boots.

Hand protection Elbow-length impervious gloves.

If determined by a risk assessment an inhalation risk exists, wear an organic Respiratory protection

vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

No information available. **Environmental exposure controls** 

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

**Appearance** No information available Color Colourless to Pale Yellow

Odor Characteristic

**Odor threshold** No information available

**Property** Remarks • Method Values

5.0-9.0 (1% aqueous solution) pН

No data available None known pH (as aqueous solution) Melting point / freezing point No data available None known Boiling point / boiling range No data available None known Flash point ca. 27°C CC (closed cup) **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air

None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

No data available None known Vapor pressure

Vapor density No data available Relative density No data available Water solubility Miscible in water

Solubility(ies) No data available None known Partition coefficient No data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

Other information

### 10. STABILITY AND REACTIVITY

**CHLORIDE 50%** 

Revision date: 19-Jun-2023

**Revision Number** 1

Reactivity

Reactivity No information available.

**Chemical stability** 

Stable under normal ambient and anticipated storage and handling conditions of Stability

temperature and pressure.

**Explosion data** 

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

**Conditions to avoid** 

**Conditions to avoid** Heat, flames and sparks. Static discharge (electrostatic discharge). Direct sunlight.

Extremes of temperature.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Strong reducing agents.

**Hazardous decomposition products** 

Hazardous decomposition products Carbon oxides. Nitrogen oxides.

### 11. TOXICOLOGICAL INFORMATION

### **Acute toxicity**

### Information on likely routes of exposure

**Product Information** No adverse health effects expected if the chemical is handled in accordance with this

Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the

chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation.

Eye contact Causes serious eye damage.

Skin contact Causes burns.

Ingestion Can burn mouth, throat, and stomach.

**Symptoms** Irritation/Corrosion. May cause redness and tearing of the eyes. Erythema (skin redness).

Burning.

#### Numerical measures of toxicity - Product Information

Refer to component information below.

#### **Component Information**

Revision Number 1

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl alcohol (Ethanol)	= 7060 mg/kg ( Rat )	-	= 124.7 mg/L ( Rat ) 4h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes burns. Classification is based on mixture calculation methods based on component

data.

Serious eye damage/eye irritation Causes serious eye damage. Classification is based on mixture calculation methods based

on component data.

**Respiratory or skin sensitization** No information available.

Germ cell mutagenicity No information available.

**Carcinogenicity** No information available.

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

**Ecotoxicity** Keep out of waterways. Very toxic to aquatic life. Very toxic to aquatic life with long lasting

effects.

Persistence and degradability

Persistence and degradability Biodegradable.

Bioaccumulative potential

**Bioaccumulation** No information available.

**Component Information** 

Chemical name	Partition coefficient
Ethyl alcohol (Ethanol)	-0.32

**Mobility** 

Mobility in soil No information available.

Other adverse effects

### 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused Should not be released into the environment. Dispose of in accordance with local

products regulations. Dispose of waste in accordance with environmental legislation.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld Contaminated packaging

containers. Empty containers should be taken to an approved waste handling site for

**Revision Number** 1

recycling or disposal.

## 14. TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and

Rail: DANGEROUS GOODS.

**UN** number

Proper shipping name CORROSIVE LIQUID, FLAMMABLE, N.O.S. (CONTAINS DODECYLTRIMETHYL

AMMONIUM CHLORIDE AND ETHANOL)

**Hazard class** 3 Subsidiary hazard class Packing group Ш Hazchem code •3W

**IATA** 

**UN** number 2920

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (CONTAINS DODECYLTRIMETHYL **UN proper shipping name** 

AMMONIUM CHLORIDE AND ETHANOL)

Transport hazard class(es) 3 Subsidiary hazard class **Packing group** Ш

**IMDG** 

**UN** number

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (CONTAINS DODECYLTRIMETHYL **UN proper shipping name** 

AMMONIUM CHLORIDE AND ETHANOL) MARINE POLLUTANT

Transport hazard class(es) Subsidiary hazard class 3 Ш Packing group **IMDG EMS Fire** F-E **IMDG EMS Spill** S-C Marine pollutant Yes

### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **National regulations**

#### Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

**Revision Number** 1

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule (SUSMP)

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical Threshold quantity (T)

Liquids that meet the criteria for Class 3 Packing Group II or III

50 000

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Ethyl alcohol (Ethanol) - 64-17-5	10 tonne/yr Threshold category 1

**International Inventories** 

All the constituents of this material are listed on the Australian Inventory of Industrial

Chemicals.

Legend:

**AIIC- Australian Inventory of Industrial Chemicals** 

**International Regulations** 

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

### 16. OTHER INFORMATION

Supplier Safety Data Sheet, not dated.

Reason(s) For Issue: First Issue Primary SDS

Issuing Date: 19-Jun-2023

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

**Revision Note:** 

The symbol (\*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

C Carcinogen

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

**Revision Number** 1

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian Industrial Chemicals Introduction Scheme (AICIS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their lxom representative or lxom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**End of Safety Data Sheet**