

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** DSP 1611

**Recommended Use of the Chemical and Restrictions on Use** Mineral flotation collector.

**Supplier:** Ixom Operations Pty Ltd  
**ABN:** 51 600 546 512  
**Street Address:** Level 8, 1 Nicholson Street  
Melbourne 3000  
Australia

**Telephone Number:** +61 3 9665 7111  
**Facsimile:** +61 3 9665 7937  
**Emergency Telephone:** 1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

## 2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

### Classification of the chemical:

Skin Corrosion - Sub-category 1B  
Skin Sensitisation - Category 1

**SIGNAL WORD:** DANGER



### Hazard Statement(s):

H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.

### Precautionary Statement(s):

#### Prevention:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.  
P264 Wash hands thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves / protective clothing / eye protection / face protection.

# Safety Data Sheet



## Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before re-use.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## Storage:

P405 Store locked up.

## Disposal:

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## Other Hazards:

AUH032 Contact with acids liberates very toxic gas.

**Poisons Schedule (SUSMP):** None allocated.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Phosphorodithioic acid, O,O-bis(2-methylpropyl)ester, sodium salt	53378-51-1	30-60%	H314
O-Isopropyl ethyl thiocarbamate	141-98-0	10-<30%	H317 H412
Phosphorothioic acid, O,O-bis(2-methylpropyl)ester, sodium salt	53378-52-2	10-<30%	H314
Methyl isobutyl carbinol	108-11-2	<10%	H226 H335
Other ingredient(s)	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

### Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

### Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Product Name: DSP 1611  
Substance No: 00000055050

Issued: 14/04/2014  
Version: 1

# Safety Data Sheet



## Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

## Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

## 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem or Emergency Action Code:** 2R

### Specific hazards arising from the chemical:

Non-combustible material.

### Special protective equipment and precautions for fire-fighters:

Decomposes on heating emitting toxic fumes, including those of hydrogen sulfide, oxides of sulfur, and oxides of phosphorus. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Neutralise with dilute acid. Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

### Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

### Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Methyl isobutyl carbinol: 8hr TWA = 104 mg/m<sup>3</sup> (25 ppm), 15 min STEL = 167 mg/m<sup>3</sup> (40 ppm), Sk

# Safety Data Sheet



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

'Sk' (skin) Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

## Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Liquid  
**Colour:** Yellow to Dark Brown  
**Odour:** Solvent  
**Solubility:** Miscible with water.

Product Name: DSP 1611  
Substance No: 000000055050

Issued: 14/04/2014  
Version: 1

# Safety Data Sheet



<b>Specific Gravity:</b>	1.078 to 1.096
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	Not available
<b>Flammability Limits (%):</b>	Not available
<b>Autoignition Temperature (°C):</b>	Not available
<b>Boiling Point/Range (°C):</b>	Not available
<b>pH:</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Contact with acids liberates very toxic gas.
<b>Chemical stability:</b>	No information available.
<b>Possibility of hazardous reactions:</b>	Reacts with mineral acids evolving flammable and toxic hydrogen sulfide gas.
<b>Conditions to avoid:</b>	None known.
<b>Incompatible materials:</b>	Incompatible with strong acids , oxidising agents , copper , and brass .
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of nitrogen. Hydrogen sulfide. Oxides of sulfur. Oxides of phosphorus.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
<b>Eye contact:</b>	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
<b>Skin contact:</b>	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
<b>Inhalation:</b>	Breathing in vapour may produce respiratory irritation.
<b>Acute toxicity:</b>	No LD50 data available for the product. For the main ingredient: Oral LD50 (rat): 2800 mg/kg
<b>Respiratory or skin sensitisation:</b>	A skin sensitiser (guinea pig).
<b>Chronic effects:</b>	No information available for the product.

This product may liberate carbon disulfide on contact with moist skin. Chronic exposure to carbon disulfide may produce central and peripheral nervous system, cardiovascular, gastrointestinal kidney and eye disorders.

## 12. ECOLOGICAL INFORMATION

# Safety Data Sheet



**Ecotoxicity**

Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Decontamination and destruction of containers should be considered.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



**UN No:** 3267  
**Transport Hazard Class:** 8 Corrosive  
**Packing Group:** II  
**Proper Shipping Name or Technical Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT AND PHOSPHOROTHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT)  
**Hazchem or Emergency Action Code:** 2R

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 3267  
**Transport Hazard Class:** 8 Corrosive  
**Packing Group:** II  
**Proper Shipping Name or Technical Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT AND PHOSPHOROTHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT)  
**IMDG EMS Fire:** F-A  
**IMDG EMS Spill:** S-B

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 3267  
**Transport Hazard Class:** 8 Corrosive  
**Packing Group:** II  
**Proper Shipping Name or Technical Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS PHOSPHORODITHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT AND PHOSPHOROTHIOIC ACID, O,O-BIS(2-METHYLPROPYL)ESTER, SODIUM SALT)

Product Name: DSP 1611  
Substance No: 000000055050

Issued: 14/04/2014  
Version: 1

## 15. REGULATORY INFORMATION

**Classification:**

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

**Classification of the chemical:**

Skin Corrosion - Sub-category 1B

Skin Sensitisation - Category 1

**Hazard Statement(s):**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

**Poisons Schedule (SUSMP):** None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

**Reason(s) for Issue:**

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.