SAFETY DATA SHEET

Revision date: 31-May-2022



Revision Number 5

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product identifier	
Product Name	D-LIMONENE (UNTREATED GRADE)
Product Code(s)	000033914301
Other means of identification	
UN number	2319
CAS No.	5989-27-5
Synonyms	d-Limonene (untreated grade); 4-Isopropenyl-1-methylcyclohexene; Limonene, d-; d-Limonene Technical; Cyclohexene, 1-methyl-4-(1-methylethenyl)-,(R)
Recommended use of the chemical	and restrictions on use
Recommended use	Additive for washing and cleaning products, solvents, degreasing agents, base for rubber and plastic chemicals, polishes and waxes, adhesives and sealants, coating products, filters, plasters, laboratory chemicals, paints, inks and toners.
Uses advised against	Not for use as a food ingredient.
Supplier Ixom Operations Pty Ltd ABN: 51 600 546 512 Level 8, 1 Nicholson Street Melbourne 3000 Australia	
Telephone Number: +61 3 9906 3000	
Emergency telephone number	

Emergency telephone number

1 800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Flammable liquids	Category 3
Aspiration hazard	Category 1
Skin corrosion/irritation	Category 2

Skin sensitization	Category 1
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1

SIGNAL WORD Danger

Label elements

Flame Exclamation mark Health hazard Environment



Hazard statements

- H226 Flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways

H315 - Causes skin irritation

- H317 May cause an allergic skin reaction
- H410 Very toxic to aquatic life with long lasting effects

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves / protective clothing / eye protection / face protection Avoid breathing dust / fume / gas / mist / vapours / spray Contaminated work clothing should not be allowed out of the workplace Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof electrical, ventilating, lighting equipment Avoid release to the environment **Precautionary Statements - Response** Specific treatment (see First aid on this SDS) If skin irritation or rash occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam to extinguish Collect spillage **Precautionary Statements - Storage** Store locked up Store in a well-ventilated place. Keep cool **Precautionary Statements - Disposal** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

General Hazards

Poisons Schedule (SUSMP) None allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical name	CAS No.	Weight-%
d-Limonene	5989-27-5	92.0-97.0
Impurities	-	to 100

4. FIRST AID MEASURES

Description of first aid measures

General advice	For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor. Show this safety data sheet to the doctor in attendance.	
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.	
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.	
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes, and clothing.	
Most important symptoms and effects, both acute and delayed		
Symptoms	May cause allergic skin reaction. Redness. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances. May cause sensitization by skin contact.	

5. FIRE FIGHTING MEASURES	
Suitable Extinguishing Media	
Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Foam.

Unsuitable extinguishing media	Water.	
Specific hazards arising from the chemical		
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Pay attention to flashback. Vapors can form explosive mixtures with air. In the event of fire, cool tanks with water spray. Environmentally hazardous. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.	
Hazardous combustion products	Carbon oxides.	
Special protective actions for fire-fig	<u>ghters</u>	
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	
Hazchem code	3Y	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.	
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.	
For emergency responders	Use personal protection recommended in Section 8.	
Environmental precautions		
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.	
Methods and material for conta	inment and cleaning up	
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.	
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. After cleaning, flush away traces with water and detergent.	

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof

General hygiene considerations	equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep at temperatures between -10 °C and 27 °C. Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.	
Incompatible materials	Oxidizing agents. Acidic clays. Mineral acids. Vinyl chloride. lodine pentafluoride.	
Poisons Schedule (SUSMP)	None allocated	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits No value assigned for this specific material by Safe Work Australia.

Appropriate engineering controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.



Respiratory protection	If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.
Environmental exposure controls	No information available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties Physical state

Appearance Color Odor Odor threshold	Clear Colourless to Pale Yellow Orange Sweet Pleasant Fruity No information available.	
Property	Values	Remarks • Method
рН	Not applicable	None known
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	-74.35°C	
Boiling point / boiling range	176°C @102.6 kPa	
Flash point	52.5°C	CC (closed cup)
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	6.1% @262°C	
Lower flammability or explosive	0.7% @150°C	
limits		
Vapor pressure	1.864 hPa	@ 25 °C
Vapor density	ca. 4.7 (air=1)	
Relative density	0.832-0.847	@ 25 °C
Water solubility	0.0138 g/L	@ 25 °C
Solubility(ies)	Negligible	
Partition coefficient	log Pow = 2.78-4.88	
Autoignition temperature	235°C @101.2 kPa	
Decomposition temperature	No data available	None known
Kinematic viscosity	1.17 mm²/s @20°C	None known
Dynamic viscosity	No data available	None known

Other information

10. STABILITY AND REACTIVITY

Reactivity	
Reactivity	No information available.
Chemical stability	
Stability	Stable under normal conditions.
Explosion data Sensitivity to mechanical impac	t None.
Sensitivity to static discharge	Yes.
Possibility of hazardous reactions	
Possibility of hazardous reactions	None under normal processing.

Hazardous polymerization	Hazardous polymerization does not occur.	
Conditions to avoid		
Conditions to avoid	Heat, flames and sparks.	
Incompatible materials		
Incompatible materials	Oxidizing agents. Acidic clays. Mineral acids. Vinyl chloride. Iodine pentafluoride.	

Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information	No adverse health effects expected if the chemical is handled in accordance with this Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the chemical is mishandled and overexposure occurs are:
Inhalation	Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation.
Eye contact	May cause irritation.
Skin contact	Causes skin irritation. May cause sensitization by skin contact. Repeated exposure may cause skin dryness or cracking.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.
Symptoms	May cause allergic skin reaction. Redness. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity - Product Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
d-Limonene	= 5200 mg/kg (Rat) = 4400 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	No information available.

Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity

Keep out of waterways. Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
d-Limonene	-	LC50: 0.619 - 0.796mg/L	-	-
		(96h, Pimephales		
		promelas) LC50:		
		=35mg/L (96h,		
		Oncorhynchus mykiss)		

Persistence and degradability

Persistence and degradability Readily biodegradable.

Bioaccumulative potential

Bioaccumulation

This chemical shows a high bioaccumulation potential.

Chemical name	Partition coefficient
d-Limonene	4.23

Mobility

Mobility in soil

Harmful to the soil environment.

Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Do not reuse empty containers.

14. TRANSPORT INFORMATION

<u>ADG</u>

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and

Rail; DANGEROUS GOODS.	
UN number	2319
Proper shipping name	TERPENE HYDROCARBONS, N.O.S. (CONTAINS D-LIMONENE)
Hazard class	3
Packing group	
Environmental hazard	Yes
Hazchem code	3Y

<u>IATA</u>

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number	2319
UN proper shipping name	TERPENE HYDROCARBONS, N.O.S. (CONTAINS D-LIMONENE)
Transport hazard class(es)	3
Packing group	III

IMDG

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number	2319
UN proper shipping name	TERPENE HYDROCARBONS, N.O.S. (CONTAINS D-LIMONENE)
Transport hazard class(es)	3
Packing group	
IMDG EMS Fire	F-E
IMDG EMS Spill	S-D
Marine pollutant	Yes

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

See section 8 for national exposure control parameters

Poisons Schedule (SUSMP) None allocated

Major hazard (accident/incident planning) regulation

Verify that license requirements are met <u>Hazardous chemical</u> Liquids that meet the criteria for Class 3 Packing Group II or III

Threshold quantity (T) 50 000

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
d-Limonene - 5989-27-5	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total

25 tonne/yr Threshold category 1a total
400 tonne/yr Threshold category 2a total
2000 tonne/yr Threshold category 2b total

International Inventories AIIC NZIoC

This material is listed on the Australian Inventory of Industrial Chemicals. This material is listed on the New Zealand Inventory of Chemicals.

Legend: AIIC - Australian Inventory of Industrial Chemicals NZIoC - New Zealand Inventory of Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Supplier Safety Data Sheet 05/ 2021

Reason(s) For Issue: 5 Yearly Revised Primary SDS

Issuing Date: 31-May-2022

This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and SDS Services).

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION			
TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
С	Carcinogen		

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s)) U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act U.S. Environmental Protection Agency High Production Volume Chemicals Food Research Journal Hazardous Substance Database International Uniform Chemical Information Database (IUCLID) Japan GHS Classification Australian Industrial Chemicals Introduction Scheme (AICIS) NIOSH (National Institute for Occupational Safety and Health) National Library of Medicine's ChemID Plus (NLM CIP) National Library of Medicine's PubMed database (NLM PUBMED) National Toxicology Program (NTP) New Zealand's Chemical Classification and Information Database (CCID) Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set RTECS (Registry of Toxic Effects of Chemical Substances) World Health Organization

Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet