

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: EPOXY RESIN YDF-170

Other name(s): Diglycidyl ether of bisphenol F.

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)
NZBN: 9429041465226
Street Address: 166 Totara Street
Mt Maunganui South
New Zealand

Telephone Number: +64 9 368 2700
Facsimile: +64 9 368 2710
Emergency Telephone: 0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: WARNING

Subclasses:

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006
Approval Number: HSR002503



Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P260 Do not breathe mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

**Response:**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).
P362 Take off contaminated clothing before re-use.
P363 Wash contaminated clothing before re-use.
P391 Collect spillage.

Storage:

No storage statements.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	9003-36-5	100%	H315 H317 H411

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 3Z

Specific hazards arising from the substance or mixture:

Combustible liquid.

Safety Data Sheet



Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon . Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Colour: Light Yellow
Odour: Odourless

Product Name: EPOXY RESIN YDF-170
Substance No: 00000016119

Issued: 06/08/2015
Version: 3

Safety Data Sheet



Solubility:	Slightly miscible with water.
Specific Gravity:	1.18 - 1.22
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	1 mmHg
Flash Point (°C):	230
Boiling Point/Range (°C):	>260
Decomposition Point (°C):	Not available
pH:	Not available
Freezing Point/Range (°C):	-20.6

10. STABILITY AND REACTIVITY

Reactivity:	No information available.
Chemical stability:	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with acids, amines, anhydrides, oxidising agents, chloroform, chloroform acid.
Hazardous decomposition products:	Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	No adverse effects expected, however, large amounts may cause nausea and vomiting.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin will result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
Inhalation:	Breathing in mists or aerosols may produce respiratory irritation.
Acute toxicity:	
Oral LD50 (rat):	>2000 mg/kg
Dermal LD50 (rat):	>2000 mg/kg
Respiratory or skin sensitisation:	A skin sensitizer (guinea pig).
Chronic effects:	Not listed as carcinogenic according to IARC.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
--------------------	--------------------------------

Product Name: EPOXY RESIN YDF-170
Substance No: 000000016119

Issued: 06/08/2015
Version: 3

Safety Data Sheet



Aquatic toxicity: Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.

48hr EC50 (Daphnia magna): 3.5 mg/L

96hr LC50 (rainbow trout): 5.7 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



UN No: 3082
Transport Hazard Class: 9 Miscellaneous Dangerous Goods
Packing Group: III
Proper Shipping Name or Technical Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIGLYCIDYL ETHER OF BISPHENOL F)
Hazchem or Emergency Action Code: 3Z

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 3082
Transport Hazard Class: 9 Miscellaneous Dangerous Goods
Packing Group: III
Proper Shipping Name or Technical Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIGLYCIDYL ETHER OF BISPHENOL F)
IMDG EMS Fire: F-A
IMDG EMS Spill: S-F

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 3082
Transport Hazard Class: 9 Miscellaneous Dangerous Goods
Packing Group: III
Proper Shipping Name or Technical Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIGLYCIDYL ETHER OF BISPHENOL F)

15. REGULATORY INFORMATION

Product Name: EPOXY RESIN YDF-170
Substance No: 000000016119

Issued: 06/08/2015
Version: 3

Safety Data Sheet

**Classification:**

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses:

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006

Approval Number: HSR002503

Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

16. OTHER INFORMATION

Supplier Material Safety Data Sheet; 03/ 2013.

Reason(s) for Issue:

Reissue of an obsolete SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.