

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LUTENSOL XL60

Recommended Use of the Chemical Raw material for the chemical-technical industry.

and Restrictions on Use For industrial use only.

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)

NZBN: 9429041465226 Street Address: 166 Totara Street Mt Maunganui South

New Zealand

+64 9 368 2700 **Telephone Number:** Facsimile: +64 9 368 2710

Emergency Telephone: 0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: DANGER

Subclasses:

Subclass 6.1 Category D - Substances which are acutely toxic.

Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.

Subclass 9.1 Category D - Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal

action.

Polymers (Subsidiary Hazard) Group Standard 2006

Approval Number: HSR002644





Hazard Statement(s):

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H401 Toxic to aquatic life.

Precautionary Statement(s):

Prevention:

P102 Keep out of reach of children.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Product Name: LUTENSOL XL60 Issued: 11/04/2017 Substance No: 000000017588



Response:

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

Storage:

No storage statements.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
C10-alcohol, ethoxylated, propoxylated	166736-08-9	100%	H302 H318

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre. Continue to wash with large amounts of water until medical help is available.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns. No known specific antidote.

FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the chemical:

Combustible liquid.

Product Name: LUTENSOL XL60 Issued: 11/04/2017 Substance No: 000000017588



Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Shut off all possible sources of ignition. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. For large amounts: Dike spillage. Pump off product.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Protect from temperatures above 70°C. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority.

Appropriate engineering controls:

Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.







Wear overalls, chemical goggles and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Product Name: LUTENSOL XL60 Issued: 11/04/2017 Substance No: 000000017588



Physical state:

Colour:

Colourless

Odour:

Product specific

Miscible in water.

Specific Gravity:

Relative Vapour Density (air=1):

Vapour Pressure (20 °C):

Flash Point (°C):

Liquid

Colourless

Miscible in water.

Authorized

Miscible in water.

Ca. 1 @20°C

Not available

<0.1 hPa

ca. 150

Flammability Limits (%): The lower explosion point may be 5-15°C below the flash point.

Autoignition Temperature (°C): Not applicable

Boiling Point/Range (°C): >250 Decomposition Point (°C): >350

pH: ca. 7 (water, 5% (m)) **Viscosity:** ca. 55 mPa.s @23°C

Freezing Point/Range (°C): <5

10. STABILITY AND REACTIVITY

Reactivity: Hygroscopic: absorbs moisture or water from surrounding air.

Chemical stability: Stable at ambient temperatures.

Possibility of hazardous

reactions:

No hazardous reactions when stored and handled correctly.

Conditions to avoid: Avoid exposure to moisture.

Incompatible materials: Incompatible with acids, alkalis, caustics, halogens, reactive chemicals.

Hazardous decomposition

products:

Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing may result in irritation of the gastrointestinal tract.

Eye contact: A severe eye irritant. Contamination of eyes can result in permanent injury.

Skin contact: Contact with skin may result in irritation.

Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product. For a compositionally similar material:

Oral LD50 (rat): >300-2000 mg/kg

Substance No: 000000017588

Skin corrosion/irritation: Non-irritant (rabbit).
Serious eye damage/irritation: Severe irritant (rabbit).

Respiratory or skin Not a skin sensitiser (guinea pig).

sensitisation:

Chronic effects: Non-mutagenic in bacteria.

Product Name: LUTENSOL XL60 Issued: 11/04/2017



12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Persistence/degradability: The material is readily biodegradable.

Bioaccumulative potential: Not expected to bioaccumulate.

48hr EC50 (Daphnia magna): >1-<10 mg/L

>10-100 mg/L (Zebra fish) 96hr LC50 (fish):

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses:

Subclass 6.1 Category D - Substances which are acutely toxic.

Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.

Subclass 9.1 Category D - Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action.

Polymers (Subsidiary Hazard) Group Standard 2006

Approval Number: HSR002644

Hazard Statement(s):

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H401 Toxic to aquatic life.

16. OTHER INFORMATION

Supplier Safety Data Sheet; 11/2016.

LUTENSOL is a registered trademark of BASF.

Product Name: LUTENSOL XL60 Issued: 11/04/2017 Substance No: 000000017588



This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

Reissue of an obsolete SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: LUTENSOL XL60 Issued: 11/04/2017 Substance No: 000000017588