The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015	Print Date 31.12.2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	: Shell Heat Transfer Oil S2	
Product code	: 001D8388	
CAS-No. Manufacturer or supplier's c	: 64742-65-0 details	
Supplier	 Ixom Operations Pty Ltd (NZBN – 9429041465226) 166 Totara Street, Mt Maunganui South, New Zealand 	
Telephone Telefax	: +64 9 3682700 : +64 9 3682710	
Emergency telephone number	: 0800 734 607 (ALL HOURS	5)
_		

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001., Not classified as Dangerous Goods for transport, according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Hazard classification

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).

GHS Label element

Hazard pictograms	No Hazard Symbol required	
Signal word	No signal word	
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS crit 	teria.
Precautionary statements		

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2

Revision Date 30.12.2015

Print Date 31.12.2015

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Substance
Chemical nature	:	Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.

Hazardous components

SECTION 4	. FIRST-AID	MEASURES
------------------	-------------	----------

General advice	Not expected to be a health hazard when used under no conditions.	ormal
If inhaled	No treatment necessary under normal conditions of use If symptoms persist, obtain medical advice.	
In case of skin contact	Remove contaminated clothing. Flush exposed area wit water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.	h
In case of eye contact	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.	
If swallowed	In general no treatment is necessary unless large quant are swallowed, however, get medical advice.	ities
Most important symptoms and effects, both acute and delayed	Oil acne/folliculitis signs and symptoms may include for of black pustules and spots on the skin of exposed area Ingestion may result in nausea, vomiting and/or diarrhoe	IS.
Protection of first-aiders	When administering first aid, ensure that you are wearing	ig the

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015 Print Date 31.12.2	
	appropriate personal protective equipment according to the incident, injury and surroundings.	;
Notes to physician	: Treat symptomatically.	
SECTION 5. FIRE-FIGHTING MEA	SURES	
Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates a gases (smoke). Carbon monoxide may be evolved if incomplete combustio occurs. Unidentified organic and inorganic compounds. 	
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contain Breathing Apparatus must be worn when approaching a fire a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).	ed

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015 Print Date 31.12.2015
	suitable material and dispose of properly.
Additional advice	 For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.
SECTION 7. HANDLING AND S	TORAGE
General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	: Strong oxidising agents.
Product Transfer	: This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage	
Other data	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
Packaging material	 Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2	Revision Da	ate 30.12.2015	Print Da	te 31.12.2015
		exposure)	Permissible concentration	
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	New Zealand. Workplace Exposure Standards for Atmospheric Contaminant s
Oil mist, mineral	Not Assigned	(Mist)	10 mg/m3	New Zealand. Workplace Exposure Standards for Atmospheric Contaminant s

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. 	
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.	

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015	Print Date 31.12.2015
	General Information: Define procedures for safe handling a controls.	and maintenance of
	Educate and train workers in the haze measures relevant to normal activities product.	
	Ensure appropriate selection, testing equipment used to control exposure, equipment, local exhaust ventilation.	
	Drain down system prior to equipmer maintenance.	nt break-in or
	Retain drain downs in sealed storage subsequent recycle.	pending disposal or
	Always observe good personal hygie washing hands after handling the ma drinking, and/or smoking. Routinely protective equipment to remove conta contaminated clothing and footwear t Practice good housekeeping.	terial and before eating, wash work clothing and aminants. Discard

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection :	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].
Hand protection	
Remarks :	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015	Print Date 31.12.2015
	For continuous contact we recombreakthrough time of more than 2 for > 480 minutes where suitable short-term/splash protection we recognize that suitable gloves off may not be available and in this of time maybe acceptable so long a and replacement regimes are foll a good predictor of glove resistant dependent on the exact compositi Glove thickness should be typication depending on the glove make and	240 minutes with preference gloves can be identified. For ecommend the same, but ering this level of protection case a lower breakthrough s appropriate maintenance owed. Glove thickness is not nee to a chemical as it is tion of the glove material. Ily greater than 0.35 mm
Eye protection	: If material is handled such that it protective eyewear is recommend	
Skin and body protection	: Skin protection is not ordinarily re work clothes. It is good practice to wear chemic	
Thermal hazards	: Not applicable	
Environmental exposure con	trols	
General advice	: Take appropriate measures to ful relevant environmental protection contamination of the environment Chapter 6. If necessary, prevent being discharged to waste water. treated in a municipal or industria before discharge to surface water Local guidelines on emission limi must be observed for the dischar vapour.	a legislation. Avoid t by following advice given in undissolved material from Waste water should be al waste water treatment plant r. ts for volatile substances
SECTION 9. PHYSICAL AND CHE	MICAL PROPERTIES	
Appearance	: Liquid at room temperature.	
Colour	: amber	
Odour	: Slight hydrocarbon	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: -12 °C / 10 °FMethod: ISO 3016	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value	:(S)
Flash point	: 220 °C / 428 °F Method: ISO 2592	

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015	Print Date 31.12.2015
	208 °C / 406 °F Method: ISO 2719	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Data not available	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Relative density	: 0.857 (20 °C / 68 °F)	
Density	: 857 kg/m3 (20 °C / 68 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: Pow: > 6(based on information or	ו similar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 29 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104	
	5.1 mm2/s (100 °C / 212 °F) Method: ISO 3104	
	1.4 mm2/s (200 °C / 392 °F) Method: ISO 3104	
	270 mm2/s (0 °C / 32 °F) Method: ISO 3104	
Explosive properties	: Not classified	

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015	Print Date 31.12.2015
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be	e a static accumulator.
Decomposition temperature	: Data not available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	The product does not pose any further reactivity addition to those listed in the following sub-parage	
Chemical stability	Stable.	
Possibility of hazardous reactions	Reacts with strong oxidising agents.	
Conditions to avoid	Extremes of temperature and direct sunlight.	
Incompatible materials	Strong oxidising agents.	
Hazardous decomposition products	Hazardous decomposition products are not expe during normal storage.	cted to form

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.
Acute toxicity	
Product:	
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg
	Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	: LC 50 Rat: > 5 mg/l
	Exposure time: 4 h Remarks: Low toxicity by inhalation.
	Temarka. Low toxicity by initialation.
Acute dermal toxicity	: Rabbit:
	Remarks: Low toxicity: LD50 > 5000 mg/kg
Skin corrosion/irritation	
Due du etc	

Product:

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2

Revision Date 30.12.2015

Print Date 31.12.2015

Remarks: Not irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be non-irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2

Revision Date 30.12.2015

Print Date 31.12.2015

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

	Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Eco	otoxicity		
	Product:		
	Toxicity to fish (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
	Toxicity to crustacean (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
	Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
	Toxicity to fish (Chronic	:	Remarks: NOEC/NOEL expected to be > 10 - <= 100 mg/l
	toxicity) Toxicity to crustacean (Chronic toxicity)	:	Remarks: NOEC/NOEL expected to be > 10 - <= 100 mg/l
	Toxicity to microorganisms	:	Remarks: Expected to be practically non toxic:

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015 Print Date 31.12.2015
(Acute toxicity)	LL/EL/IL50 > 100 mg/l
Persistence and degradability	
Product:	
Biodegradability	: Remarks: Expected to be inherently biodegradable.
Bioaccumulative potential	
Product:	
Bioaccumulation	: Remarks: Has the potential to bioaccumulate.
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on information on similar products)
Mobility in soil	
Product:	
Mobility	 Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile. Remarks: Floats on water.
Other adverse effects	
no data available <u>Product:</u>	
Additional ecological information	 Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities., Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential. Films formed on water may affect oxygen transfer and damage organisms., May cause physical fouling of aquatic organisms. Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2

Revision Date 30.12.2015

Print Date 31.12.2015 to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

Land Transport Rule: Dangerous Goods 2012 -NZS 5433 Not regulated as a dangerous good

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions	 Not applicable Not applicable Not applicable Not applicable Not applicable
Special precautions for user	
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15. REGULATORY INFORMATION

Safety, health and environme mixture	ental regulations/leg	islation specific for the substance or
R-phrase(s)	:	Not classified.
S-phrase(s)	:	Not classified.

New Zealand Workplace Exposure Limits 2002 (WES). New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

Other international regulations

The components of this product are reported in the following inventories:

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

Shell Heat Transfer Oil S2

Version 1.2	Revision Date 30.12.2015	Print Date 31.12.2015
EINECS TSCA	All components listed or polymer eAll components listed.	exempt.

SECTION 16. OTHER INFORMATION

Abbreviations and Acronyms	:	The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
Further information		
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.