The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version 1.0	Revision Date 19.01.2016	Print Date 20.01.2016
SECTION 1. PRODUCT AND COMP	PANY IDENTIFICATION	
Product name :	DF Hydro 46	
Product code :	001C8855	
Manufacturer or supplier's de Supplier : Telephone Telefax	tails Ixom Operations Pty Ltd (NZBN – 9429041465226) 166 Totara Street, Mt Maunganui South, New Zealand : +64 9 3682700 : +64 9 3682710	
Emergency telephone number	: 0800 734 607 (ALL HOURS)	
Recommended use of the che Recommended use :		

SECTION 2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001., Not classified as Dangerous Goods for transport, according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Hazard classification

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).

GHS label elements

Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:

Prevention:

No precautionary phrases.

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version 1.0

Revision Date 19.01.2016

Print Date 20.01.2016

Response: No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.High-pressure injection under the skin may cause serious damage including local necrosis.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature	:	Highly refined mineral oils and additives.
		The highly refined mineral oil contains <3% (w/w) DMSO-
		extract, according to IP346.

Hazardous components

SECTION 4. FIRST-AID MEASURES

General advice	Not expected to be a health hazard when used under conditions.	er normal
If inhaled	No treatment necessary under normal conditions of If symptoms persist, obtain medical advice.	use.
In case of skin contact	Remove contaminated clothing. Flush exposed area water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention	
	When using high pressure equipment, injection of pr under the skin can occur. If high pressure injuries of casualty should be sent immediately to a hospital. D for symptoms to develop. Obtain medical attention even in the absence of app wounds.	ccur, the to not wait
In case of eye contact	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention	n.
If swallowed	In general no treatment is necessary unless large qu	uantities

DF Hydro 46

Version 1.0		Revision Date 19.01.2016	Print Date 20.01.2016
		are swallowed, however, get medica	al advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and sympto of black pustules and spots on the s Ingestion may result in nausea, vom	kin of exposed areas.
		Local necrosis is evidenced by delatissue damage a few hours following	
Protection of first-aiders	:	When administering first aid, ensure appropriate personal protective equincident, injury and surroundings.	
Notes to physician	:	Treat symptomatically.	
		High pressure injection injuries requiintervention and possibly steroid the damage and loss of function. Because entry wounds are small an seriousness of the underlying dama determine the extent of involvement anaesthetics or hot soaks should be can contribute to swelling, vasospas surgical decompression, debrideme foreign material should be performe anaesthetics, and wide exploration i	erapy, to minimise tissue d do not reflect the ge, surgical exploration to may be necessary. Local avoided because they am and ischaemia. Prompt nt and evacuation of d under general

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

DF Hydro 46

Version 1.0	Revision Date 19.01.2016	Print Date 20.01.2016
	relevant Standards (e.g. Europe: EN	1 469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Product Transfer :	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Storage

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version 1.0	Revisi	on Date 19.01.2016	Print Date 20.01.2016
Other data	: Keep container tightly closed and in a cool, well-ventila		
	place. Use pr	operly labeled and closable con	itainers.
	Store a	at ambient temperature.	
Packaging material	steel o	e material: For containers or co r high density polyethylene. able material: PVC.	ntainer linings, use mild
Container Advice		nylene containers should not be ratures because of possible risk	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	New Zealand. Workplace Exposure Standards for Atmospheric Contaminant s
Oil mist, mineral	Not Assigned	(Mist)	10 mg/m3	New Zealand. Workplace Exposure Standards for Atmospheric Contaminant s

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version	10	
1011	1.0	

Revision Date 19.01.2016

Print Date 20.01.2016

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

conditions o In accordan precautions If engineerir concentratio health, selec	ry protection is ordinarily required under normal f use. ce with good industrial hygiene practices, should be taken to avoid breathing of material. Ig controls do not maintain airborne ns to a level which is adequate to protect worker ct respiratory protection equipment suitable for the ditions of use and meeting relevant legislation.
--	---

DF Hydro 46

sion 1.0	Revision Date 19.01.2016 Print Date 20.01.201
	Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].
Hand protection	
Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective han care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is no a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye protection	: If material is handled such that it could be splashed into eyes protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Thermal hazards	: Not applicable
Environmental exposure co	ontrols
Conoral advisa	. Take environments measures to fulfill the requirements of

relev cont Chaj bein treat befo Loca	e appropriate measures to fulfill the requirements of vant environmental protection legislation. Avoid amination of the environment by following advice given in oter 6. If necessary, prevent undissolved material from g discharged to waste water. Waste water should be ed in a municipal or industrial waste water treatment plant re discharge to surface water. al guidelines on emission limits for volatile substances t be observed for the discharge of exhaust air containing
--	---

DF Hydro 46

Version 1.0	Revision Date 19.01.2016	Print Date 20.01.2016
	vapour.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-30 °C / -22 °FMethod: ISO 3016
Initial boiling point and boiling range	:	> 280 °C / 536 °Festimated value(s)
Flash point	:	230 °C / 446 °F Method: ISO 2592
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	:	> 1estimated value(s)
Relative density	:	0.879 (15 °C / 59 °F)
Density	:	879 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n- octanol/water	:	Pow: > 6(based on information on similar products)
Auto-ignition temperature	:	> 320 °C / 608 °F
Viscosity		
-		Data not available
Viscosity, dynamic	•	

DF Hydro 46

Version 1.0 Viscosity, kinematic	Revision Date 19.01.2016 : 46 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	Print Date 20.01.2016
	6.7 mm2/s (100 °C / 212 °F) Method: ASTM D445	
	580 mm2/s (0 °C / 32 °F) Method: ASTM D445	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity Decomposition temperature	This material is not expected to be aData not available	static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	The product does not pose any further reactivity hazard addition to those listed in the following sub-paragraph.	s in
Chemical stability	Stable.	
Possibility of hazardous reactions	Reacts with strong oxidising agents.	
Conditions to avoid	Extremes of temperature and direct sunlight.	
Incompatible materials	Strong oxidising agents.	
Hazardous decomposition products	Hazardous decomposition products are not expected to during normal storage.	form

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version 1.0	Revision Date 19.01.2016	Print Date 20.01.2016
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Expected to be of low to	oxicity:
Acute inhalation toxicity	: Remarks: Not considered to be ar normal conditions of use.	inhalation hazard under
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Expected to be of low to	oxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Information given is based on a knowledge of the compone and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous tes extract).	
--	--

Ecotoxicity

Product:

DF Hydro 46

Toxicity to fish (Acute toxicity)	: Remarks: Expected to be practic		
	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxicity to crustacean (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxicity to fish (Chronic toxicity)	: Remarks: Data not available		
Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available		
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available		
Persistence and degradability			
Product:			
Biodegradability	: Remarks: Expected to be not re- constituents are expected to be contains components that may p	inherently biodegradable, but	
Bioaccumulative potential			
Product:			
Bioaccumulation	: Remarks: Contains components bioaccumulate.	with the potential to	
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on inf	formation on similar products)	
Mobility in soil			
Product:			
Mobility	 Remarks: Liquid under most enventers soil, it will adsorb to soil p mobile. Remarks: Floats on water. 		
Other adverse effects			
no data available Product:			
Additional ecological information	 Product is a mixture of non-volate expected to be released to air in Not expected to have ozone dependence of the photochemical ozone creation periodential. Poorly soluble mixture., May cau organisms. 	any significant quantities., oletion potential, otential or global warming use physical fouling of aquatic	
	Mineral oil is not expected to car	use any chronic effects to	

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version 1.0	Revision Date 19.01.2016	Print Date 20.01.2016
aquatic organisms at concentrations less than 1 mg/l.		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues :	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

Land Transport Rule: Dangerous Goods 2012 -NZS 5433 Not regulated as a dangerous good

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions Special precautions for user	 Not applicable Not applicable Not applicable Not applicable
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

The content and format of this SDS is in accordance with HSNO Approved Code of Practice (No. HSNO CoP 8-1 09-06): Preparation of Safety Data Sheets.

DF Hydro 46

Version 1.0	Revision Date 19.01.2016		Print Date 20.01.2016	
SECTION 15. REGULATO	RY INFORMATION			
Safety, health and er mixture	vironmental regulat	tions/legislation specif	fic for the substance or	
R-phrase(s)	:	Not classified	1.	
S-phrase(s)	:	Not classified	i.	
New Zealand Workpla Transport of Dangerou		2002 (WES). New Zealar	nd Standard 5433:2012	
Other international re	egulations			
The components of t	this product are rep	orted in the following i	nventories:	
EINECS TSCA	All components listed or polymer exempt.All components listed.			
SECTION 16. OTHER INFORMATION				
Abbreviations and Acr	documer	ndard abbreviations and nt can be looked up in re dictionaries) and/or wel	eference literature (e.g.	
Further information				
Other information		I bar () in the left margin previous version.	n indicates an amendment	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.