

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: JET-SAN

Recommended Use of the Chemical and Restrictions on Use Surface sanitiser, fungicide. Dairy industry: Sanitising all types of processing equipment, pipelines, and storage vessels. Active ingredient in footbaths. Food processing. Brewing industries: Sanitising.

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)
NZBN: 9429041465226
Street Address: 166 Totara Street
Mt Maunganui South
New Zealand

Telephone Number: +64 9 368 2700
Facsimile: +64 9 368 2710
Emergency Telephone: 0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

SIGNAL WORD: DANGER

Subclasses:

Subclass 6.1 Category D - Substances which are acutely toxic.
Subclass 6.5 Category A - Substances that are respiratory sensitisers.
Subclass 6.5 Category B - Substances that are contact sensitisers.
Subclass 6.9 Category B - Substances that are harmful to human target organs or systems.
Subclass 8.2 Category C - Substances that are corrosive to dermal tissue.
Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.
Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.
Subclass 9.3 Category C - Substances that are harmful to terrestrial vertebrates.

Cleaning Products (Corrosive) Group Standard 2017
Approval Number: HSR002526



Hazard Statement(s):

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H433 Harmful to terrestrial vertebrates.

Safety Data Sheet



Precautionary Statement(s):

Prevention:

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).

P363 Wash contaminated clothing before re-use.

P314 Get medical advice/attention if you feel unwell.

P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P304+P341 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P391 Collect spillage.

Storage:

P405 Store locked up.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Notice 2017. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Non hazardous component(s)	-	>90%	-
Benzyl alkyl dimethyl ammonium chloride (Benzalkonium chloride)	8001-54-5	<10%	H302 H312 H314 H400

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Safety Data Sheet



Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the chemical:

Non-combustible material. Corrosive chemical. Environmentally hazardous.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Do not allow container or product to get into drains, sewers, streams or ponds. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols. When using do not eat, drink or smoke. Wash hands thoroughly after handling. Launder contaminated clothing before reuse. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Safety Data Sheet



Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority.

Appropriate engineering controls:

Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear Liquid
Colour:	Blue - Purple
Odour:	Not specified
Solubility:	Miscible in water.
Specific Gravity:	1.0 @20°C
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not available
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
Boiling Point/Range (°C):	Not available
pH:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	No information available.
Chemical stability:	No information available.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Avoid contact with foodstuffs.
Incompatible materials:	None known.

Safety Data Sheet



Hazardous decomposition products: None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

- Ingestion:** Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
- Eye contact:** A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
- Skin contact:** Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
- Inhalation:** Breathing in mists or aerosols may produce respiratory irritation. A respiratory sensitiser. Can cause possible allergic reactions, producing asthma-like symptoms.

Acute toxicity: No LD50 data available for the product. For the constituent Benzalkonium chloride :
Oral LD50 (rat): 240 mg/kg

Chronic effects: May cause damage to organs through prolonged or repeated exposure.

12. ECOLOGICAL INFORMATION

- Ecotoxicity** Avoid contaminating waterways.
- Aquatic toxicity:** Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



- UN No:** 1719
Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS ALKYLDIMETHYLBENZYL AMMONIUM CHLORIDE)

Product Name: JET-SAN
Substance No: 000000050945

Issued: 17/01/2018
Version: 2

Safety Data Sheet



Hazchem or Emergency Action Code: 2R

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1719
Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS ALKYLDIMETHYLBENZYL AMMONIUM CHLORIDE)
IMDG EMS Fire: F-A
IMDG EMS Spill: S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1719
Transport Hazard Class: 8 Corrosive
Packing Group: III
Proper Shipping Name or Technical Name: CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS ALKYLDIMETHYLBENZYL AMMONIUM CHLORIDE)

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

Subclasses:

Subclass 6.1 Category D - Substances which are acutely toxic.
Subclass 6.5 Category A - Substances that are respiratory sensitisers.
Subclass 6.5 Category B - Substances that are contact sensitisers.
Subclass 6.9 Category B - Substances that are harmful to human target organs or systems.
Subclass 8.2 Category C - Substances that are corrosive to dermal tissue.
Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.
Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.
Subclass 9.3 Category C - Substances that are harmful to terrestrial vertebrates.

Cleaning Products (Corrosive) Group Standard 2017
Approval Number: HSR002526

Hazard Statement(s):

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H433 Harmful to terrestrial vertebrates.

16. OTHER INFORMATION

Product Name: JET-SAN
Substance No: 00000050945

Issued: 17/01/2018
Version: 2

Safety Data Sheet



This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

5 Yearly Revised Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.