

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: IXOM SURFACTANT 170

Recommended Use of the Chemical Surfactant. and Restrictions on Use

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)

Street Address: 166 Totara Street

Mt Maunganui South

New Zealand

+64 9 368 2700 **Telephone Number:** Facsimile: +64 9 368 2710

Emergency Telephone: 0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: DANGER

Subclasses:

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006

Approval Number: HSR002503



Hazard Statement(s):

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P102 Keep out of reach of children.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

Product Name: IXOM SURFACTANT 170 Issued: 14/01/2015 Substance No: 000000051969



Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing before re-use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P391 Collect spillage.

Storage:

No storage statements.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Product Description: 100% Polyoxyalkylene alkylether.

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Substance No: 000000051969

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

Hazchem or Emergency Action Code: 3Z

Specific hazards arising from the substance or mixture:

Combustible liquid.

Product Name: IXOM SURFACTANT 170 Issued: 14/01/2015



Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Shut off all possible sources of ignition. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.







Wear overalls, chemical goggles and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Odour: Light Fatty Alcohol

Product Name: IXOM SURFACTANT 170

Issued: 14/01/2015 Substance No: 000000051969 Version: 1



Miscible in water. Solubility: **Specific Gravity:** Not available Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): Not available Flash Point (°C): >170 (Closed cup) Flammability Limits (%): Not available **Autoignition Temperature (°C):** Not available **Boiling Point/Range (°C):** Not available 5-7 (1%) :Ha

10. STABILITY AND REACTIVITY

No information available. Reactivity:

Chemical stability: Stable under normal ambient and anticipated storage and handling conditions of

temperature and pressure.

Possibility of hazardous

reactions:

None known.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame.

Incompatible with strong oxidising agents. Incompatible materials:

Hazardous decomposition

products:

Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

No adverse effects expected, however, large amounts may cause nausea and Ingestion:

vomiting.

A severe eye irritant. Contamination of eyes can result in permanent injury. Eye contact:

Skin contact: Contact with skin will result in irritation.

Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways. **Ecotoxicity**

Aquatic toxicity: Toxic to aquatic organisms. May cause long term adverse effects in the aquatic

environment.

13. DISPOSAL CONSIDERATIONS

Product Name: IXOM SURFACTANT 170 Issued: 14/01/2015 Substance No: 000000051969



Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



UN No: 3082

Transport Hazard Class: 9 Miscellaneous Dangerous Goods

Packing Group:

Proper Shipping Name or ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: (POLYOXYALKYLENE ALKYLETHER)

Hazchem or Emergency Action

Code:

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea: DANGEROUS GOODS.

UN No: 3082

Transport Hazard Class: 9 Miscellaneous Dangerous Goods

Packing Group: Ш

Proper Shipping Name or ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: (POLYOXYALKYLENE ALKYLETHER)

IMDG EMS Fire: F-A **IMDG EMS Spill:** S-F

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 3082

9 Miscellaneous Dangerous Goods **Transport Hazard Class:**

Packing Group: Ш

Proper Shipping Name or ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: (POLYOXYALKYLENE ALKYLETHER)

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Product Name: IXOM SURFACTANT 170 Issued: 14/01/2015 Substance No: 000000051969



Subclasses:

Subclass 6.3 Category A - Substances that are irritating to the skin.

Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006

Approval Number: HSR002503

Hazard Statement(s):

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

16. OTHER INFORMATION

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: IXOM SURFACTANT 170 Issued: 14/01/2015 Substance No: 000000051969