

# **1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Product Name:

### HIGH TC GEOTHERMAL GROUT-

**Recommended use of the chemical** Grout. and restrictions on use:

Supplier: NZBN: Street Address:	Ixom Operations Pty Ltd (Incorporated in Australia) 9429041465226 166 Totara Street Mt Maunganui South New Zealand
Telephone Number:	+64 9 368 2700
Facsimile:	+64 9 368 2710
Emergency Telephone:	<b>0 800 734 607 (ALL HOURS)</b>

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

# 2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

#### SIGNAL WORD: DANGER

#### Subclasses:

Subclass 6.5 Category B - Substances that are contact sensitisers. Subclass 6.7 Category A - Substances that are known or presumed human carcinogens. Subclass 6.9 Category A - Substances that are toxic to human target organs or systems.

Additives, Process Chemicals and Raw Materials (Toxic [6.7]) Group Standard 2006 Approval Number: HSR002512



Hazard Statement(s): H317 May cause an allergic skin reaction. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.

#### **Precautionary Statement(s):**

#### **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.

Product Name: HIGH TC GEOTHERMAL GROUT-Substance No: 000000053046

Issued: 19/06/2015 Version: 1

#### **Response:**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).
P363 Wash contaminated clothing before re-use.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.

#### Storage:

P405 Store locked up.

#### Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS Number	Proportion	Hazard Codes
Trade secret	-	<30%	-
Crystalline silica (Quartz)	14808-60-7	Not specified by supplier	H350 H372
Other ingredient(s)	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

### Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

### Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

#### Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

### Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

### **5. FIRE FIGHTING MEASURES**

### Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Extinguishing media appropriate to surrounding fire conditions.

ІХОП



### Specific hazards arising from the substance or mixture:

Non-combustible material.

### Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition. Keep containers cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

#### **Emergency procedures/Environmental precautions:**

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in dust. Vacuum solid spills instead of sweeping. After cleaning, flush away any residual traces with water.

### 7. HANDLING AND STORAGE

**Precautions for safe handling:** Avoid skin and eye contact and breathing in dust. Avoid handling which leads to dust formation. Keep out of reach of children.

**Conditions for safe storage, including any incompatibilities:** Store in a cool, dry, well ventilated place. Store away from foodstuffs. Keep containers closed when not in use - check regularly for spills.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Workplace Exposure Standards:** No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority. However, Workplace Exposure Standard(s) for constituent(s):

Silica-Crystalline Quartz: WES-TWA = 0.2 mg/m<sup>3</sup> (respirable dust), 6.7A Known or presumed human carcinogen Particulates not otherwise classified: 8hr WES-TWA 10 mg/m<sup>3</sup> (inhalable dust) or 3 mg/m<sup>3</sup> (respirable dust)

As published by the New Zealand Workplace Health & Safety Authority.

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

Carcinogen Category 6.7A - Known or presumed human carcinogen.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.



### Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

### Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.



Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Powder
Colour:	Various
Odour:	Odourless
Solubility:	Negligible solubility in water.
Specific Gravity:	2.53 (estimated)
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	0.00355 Pa (estimated)
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not available
Melting Point/Range (°C):	Not available
pH:	7-9

# **10. STABILITY AND REACTIVITY**

Reactivity:	No information available.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Avoid dust generation.



Incompatible materials:None known.Hazardous decomposition<br/>products:None known.

# 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	No adverse effects expected, however, large amounts may cause nausea and vomiting.
Eye contact:	May be an eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.
Skin contact:	Contact with skin may result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
Inhalation:	Breathing in dust may result in respiratory irritation.
Acute toxicity:	

Oral LD50 (rat): >85000 mg/kg (estimated) Inhalation LC50 (rat): 920 mg/L (estimated)

Respiratory or skin	A skin sensitiser.
sensitisation:	

Chronic effects: Causes damage to organs through prolonged or repeated exposure.

Crystalline silica has been shown to cause silicosis and lung cancer. Crystalline silica only causes these conditions when inhaled.

For crystalline silica (inhaled in the form of respirable quartz or cristobalite from occupational sources): This material has been classified by the International Agency for Research on Cancer (IARC) as a Group 1 agent. Group 1 - the agent is carcinogenic to humans.

The toxicity of crystalline silica is directly proportional to the ability of any particle to reach the lower respiratory tract. Quartz particles with an aerodynamic diameter below 10um are likely to be most harmful to humans, as they reach the lower respiratory tract and are less readily removed by the lungs.

Increases in lung cancer have been attributed to the inhalation of crystalline silica in a number of industries, including; ore mining, quarrying and granite works, ceramics, pottery, refractory brick and diatomaceous earth industries and in foundry workers.

The International Agency for Research on Cancer has classified crystalline silica as a Type 1 Carcinogen - Carcinogenic to Humans, based on sufficient evidence in humans and animals.

Increasing in vitro and in vivo evidence suggests that lung carcinomas in rats are a result of marked and persistent inflammation and epithelial proliferation.

Crystalline silica also causes a range of non-neoplastic pulmonary effects, including; inflammation, silicosis, lymph node fibrosis, airways disease, emphysema and increased permeability of the airspace epithelium.

## **12. ECOLOGICAL INFORMATION**



### Ecotoxicity

Avoid contaminating waterways.

48hr EC50 (Daphnia magna): 96hr LC50 (fish): 84120 mg/L (estimated) 18447 mg/L (estimated)

### **13. DISPOSAL CONSIDERATIONS**

### **Disposal methods:**

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

### **14. TRANSPORT INFORMATION**

### Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

#### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

# **15. REGULATORY INFORMATION**

### **Classification:**

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

#### Subclasses:

Subclass 6.5 Category B - Substances that are contact sensitisers. Subclass 6.7 Category A - Substances that are known or presumed human carcinogens. Subclass 6.9 Category A - Substances that are toxic to human target organs or systems.

Additives, Process Chemicals and Raw Materials (Toxic [6.7]) Group Standard 2006 Approval Number: HSR002512

#### Hazard Statement(s):

H317 May cause an allergic skin reaction.H350 May cause cancer.H372 Causes damage to organs through prolonged or repeated exposure.

## **16. OTHER INFORMATION**

Supplier Safety Data Sheet; 07/ 2011. HIGH TC GEOTHERMAL GROUT- is a trademark.

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

### Reason(s) for Issue:

First Issue Primary SDS



This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.