

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **CARBOSET PL3127**

Recommended Use of the Chemical and Restrictions on Use Acrylic copolymer.

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)
NZBN: 9429041465226
Street Address: 166 Totara Street
Mt Maunganui South
New Zealand

Telephone Number: +64 9 368 2700
Facsimile: +64 9 368 2710
Emergency Telephone: **0 800 734 607 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: WARNING

Subclasses:

Subclass 6.3 Category B - Substances that are mildly irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye.

Subclass 9.1 Category C - Substances that are harmful in the aquatic environment.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006
Approval Number: HSR002503



Hazard Statement(s):

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P103 Read label before use.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

Response:

P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Product Name: CARBOSET PL3127

Substance No: 000000053430

Issued: 27/06/2017

Version: 1

Safety Data Sheet

**Storage:**

No storage statements.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Product Description:

Polyether phosphate (CAS number 9046-01-9), 1-5%

Sodium sulfonate, 0.5-1%

Non-hazardous component(s), to 100%

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with soap and water. If irritation occurs, seek medical advice.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the chemical:

Non-combustible material. Containers may rupture or explode in heat of fire.

Special protective equipment and precautions for fire-fighters:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Product Name: CARBOSET PL3127

Substance No: 000000053430

Issued: 27/06/2017

Version: 1

Safety Data Sheet



Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Wash area down with detergent and excess water.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols. When using do not eat, drink or smoke. Wash hands thoroughly after handling. Stir well before use. Minimize contact with air to reduce contamination with mould, fungus, or other organisms which could cause decomposition or spoilage.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from incompatible materials described in Section 10. Protect from freezing. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.



Wear overalls, chemical goggles and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Opaque
Odour:	Slight Acrylate
Solubility:	Dispersible in water.
Specific Gravity:	0.96 @20°C
Relative Vapour Density (air=1):	Not available

Product Name: CARBOSET PL3127
Substance No: 000000053430

Issued: 27/06/2017
Version: 1

Safety Data Sheet



Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
Boiling Point/Range (°C):	Not available
pH:	8-9
Viscosity:	40-400 mPa.s @25°C

10. STABILITY AND REACTIVITY

Reactivity:	No information available.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerisation will not occur.
Conditions to avoid:	Avoid exposure to air. Do not allow product to freeze.
Incompatible materials:	Incompatible with strong oxidising agents.
Hazardous decomposition products:	Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing may result in nausea, vomiting, and abdominal pain.
Eye contact:	An eye irritant.
Skin contact:	Contact with skin will result in mild irritation.
Inhalation:	Breathing in mists or aerosols may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.
For Sodium sulfonate: Repeated overexposure (oral) may cause liver and kidney effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
Aquatic toxicity:	Harmful to aquatic organisms. May cause long lasting harmful effects to aquatic life.
48hr EC50 (Daphnia magna):	13.9 mg/L (for Sodium sulfonate)
96hr LC50 (rainbow trout):	0.42 mg/L (for Sodium sulfonate)

13. DISPOSAL CONSIDERATIONS

Safety Data Sheet



Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses:

Subclass 6.3 Category B - Substances that are mildly irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye.

Subclass 9.1 Category C - Substances that are harmful in the aquatic environment.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006
Approval Number: HSR002503

Hazard Statement(s):

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

16. OTHER INFORMATION

Supplier Safety Data Sheet; 07/ 2016.
CARBOSET is a registered trademark.

This safety data sheet has been prepared by Ixom Operations Pty Ltd Toxicology & SDS Services.

Reason(s) for Issue:

First Issue Primary SDS

Safety Data Sheet



This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.