

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **KLEAN 30**

Recommended Use of the Chemical and Restrictions on Use CIP (cleaning in process) and manual cleaning of stainless steel equipment.

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)
NZBN: 9429041465226
Street Address: 166 Totara Street
Mt Maunganui South
New Zealand

Telephone Number: +64 9 368 2700
Facsimile: +64 9 368 2710
Emergency Telephone: **0 800 734 607 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

SIGNAL WORD: DANGER

Subclasses:

Subclass 6.1 Category D - Substances which are acutely toxic.
Subclass 8.1 Category A - Substances that are corrosive to metals.
Subclass 8.2 Category B - Substances that are corrosive to dermal tissue.
Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.
Subclass 9.1 Category D - Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action.

Cleaning Products (Corrosive) Group Standard 2017
Approval Number: HSR002526



Hazard Statement(s):

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H313 May be harmful in contact with skin.
H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P102 Keep out of reach of children.
P103 Read label before use.
P260 Do not breathe mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Product Name: KLEAN 30
Substance No: 000000053630

Issued: 24/09/2018
Version: 1

Safety Data Sheet



Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).

P363 Wash contaminated clothing before re-use.

P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

Storage:

P405 Store locked up.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Notice 2017. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Sodium hydroxide	1310-73-2	30-60%	H290 H314 H318
Non hazardous component(s)	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. For all but the most minor symptoms arrange for patient to be seen by a doctor as soon as possible, either on site or at the nearest hospital.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Safety Data Sheet



Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the chemical:

Non-combustible material.

Special protective equipment and precautions for fire-fighters:

Not combustible, however following evaporation of aqueous component residual material can decompose if involved in a fire, emitting toxic fumes. Contact with metals may liberate hydrogen gas which is extremely flammable. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Caution - heat may be evolved on contact with water.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Do not store in aluminium or galvanised containers nor use die-cast zinc or aluminium bungs; plastic bungs should be used. At temperatures greater than 40°C, tanks must be stress relieved. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority. However, Workplace Exposure Standard(s) for constituent(s):

Sodium hydroxide: Ceiling 2 mg/m³

As published by the New Zealand Workplace Health & Safety Authority.

WES - Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded during any part of the working day.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Safety Data Sheet



Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear to Slightly Turbid Liquid
Colour:	Light Amber
Odour:	Not available
Solubility:	Miscible with water.
Specific Gravity:	1.33
Relative Vapour Density (air=1):	Not available
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not applicable
Boiling Point/Range (°C):	Not available
pH:	>12

10. STABILITY AND REACTIVITY

Reactivity: Reacts violently with acids. Reacts exothermically on dilution with water.

Chemical stability: Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Safety Data Sheet



Possibility of hazardous reactions:	Corrosive to aluminium, tin, and zinc, liberating flammable hydrogen gas. Reacts readily with various reducing sugars (i.e. fructose, galactose, maltose, dry whey solids) to produce carbon monoxide. Take precautions including monitoring the tank atmosphere for carbon monoxide to ensure safety of personnel before vessel entry.
Conditions to avoid:	Avoid contact with foodstuffs.
Incompatible materials:	Incompatible with acids , ammonium salts , aluminium , tin , zinc .
Hazardous decomposition products:	None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
Eye contact:	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
Skin contact:	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.
Inhalation:	Breathing in mists or aerosols may produce respiratory irritation.
Acute toxicity:	No LD50 data available for the product. For the constituent Sodium hydroxide :
Skin corrosion/irritation:	Severe irritant (rabbit).
Respiratory or skin sensitisation:	No information available.
Chronic effects:	No information available for the product.
Aspiration hazard:	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
Persistence/degradability:	No information available.
Bioaccumulative potential:	No information available.
Mobility in soil:	No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



UN No: 1719
Transport Hazard Class: 8 Corrosive
Packing Group: II
Proper Shipping Name or Technical Name: CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)
Hazchem or Emergency Action Code: 2R

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1719
Transport Hazard Class: 8 Corrosive
Packing Group: II
Proper Shipping Name or Technical Name: CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)
IMDG EMS Fire: F-A
IMDG EMS Spill: S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1719
Transport Hazard Class: 8 Corrosive
Packing Group: II
Proper Shipping Name or Technical Name: CAUSTIC ALKALI LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE)

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

Safety Data Sheet



Subclasses:

Subclass 6.1 Category D - Substances which are acutely toxic.

Subclass 8.1 Category A - Substances that are corrosive to metals.

Subclass 8.2 Category B - Substances that are corrosive to dermal tissue.

Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.

Subclass 9.1 Category D - Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action.

Cleaning Products (Corrosive) Group Standard 2017

Approval Number: HSR002526

Hazard Statement(s):

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H313 May be harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

16. OTHER INFORMATION

'Registry of Toxic Effects of Chemical Substances'. Ed. D. Sweet, US Dept. of Health & Human Services: Cincinnati, 2018.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.