

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: KE-445-T

Recommended Use of the Chemical Silicone rubber compound. and Restrictions on Use

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)

NZBN: 9429041465226 Street Address: 166 Totara Street Mt Maunganui South

New Zealand

+64 9 368 2700 **Telephone Number:** Facsimile: +64 9 368 2710

Emergency Telephone: 0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

SIGNAL WORD: WARNING

Subclasses:

Subclass 3.1 Category D (low hazard) - Flammable Liquids.

Subclass 6.4 Category A - Substances that are irritating to the eye.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 6.7 Category B - Substances that are suspected human carcinogens.

Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017

Approval Number: HSR002679





Hazard Statement(s):

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

Product Name: KE-445-T Issued: 22/03/2019 Substance No: 000000053719



Precautionary Statement(s):

Prevention:

P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).

P363 Wash contaminated clothing before re-use.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet for extinction.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Notice 2017. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Methyl ethyl ketoxime	96-29-7	ca. 1%	H351 H312 H318 H317
Other component(s)	=	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Inaestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Seek medical advice.

 Product Name:
 KE-445-T
 Issued: 22/03/2019

 Substance No:
 000000053719
 Version: 1



Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the chemical:

Combustible paste.

Special protective equipment and precautions for fire-fighters:

Decomposes on heating emitting toxic fumes, including those of oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Shut off all possible sources of ignition. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour, mists and aerosols. Wash hands thoroughly after handling. Do not reuse container.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority.

Appropriate engineering controls:

Use in well ventilated areas. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Product Name: KE-445-T Issued: 22/03/2019 Substance No: 000000053719









Wear overalls, chemical goggles and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Colour: Milky white Odour: Oxime

Solubility: Insoluble in water. **Specific Gravity:** 1.05 @25°C

Relative Vapour Density (air=1): >1

Vapour Pressure (20 °C): Negligible Flash Point (°C): >62 (Closed cup) Flammability Limits (%): Not available **Autoignition Temperature (°C):** Not available **Boiling Point/Range (°C):** Not applicable Not applicable pH:

10. STABILITY AND REACTIVITY

No information available. Reactivity:

Chemical stability: Stable.

Possibility of hazardous

reactions:

None known.

Conditions to avoid: Avoid contact with water. Avoid exposure to moisture.

Incompatible materials: Incompatible with water, moisture.

Hazardous decomposition

products:

Oxides of carbon. Silicon dioxide. Oxides of nitrogen. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, and gastrointestinal

irritation.

Eye contact: An eye irritant.

Skin contact: Contact with skin may result in irritation. A skin sensitiser. Repeated or prolonged

skin contact may lead to allergic contact dermatitis.

Product Name: KE-445-T Issued: 22/03/2019 Substance No: 000000053719



Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product.

Chronic effects: Suspected of causing cancer.

Aspiration hazard: No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

The material is not readily biodegradable. Persistence/degradability:

Bioaccumulative potential: No information available.

Mobility in soil: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

Subclasses:

Subclass 3.1 Category D (low hazard) - Flammable Liquids.

Subclass 6.4 Category A - Substances that are irritating to the eye.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 6.7 Category B - Substances that are suspected human carcinogens.

Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017

Approval Number: HSR002679

Product Name: KE-445-T Issued: 22/03/2019 Substance No: 000000053719



Hazard Statement(s):

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

16. OTHER INFORMATION

Supplier Safety Data Sheet; 03/2015.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: KE-445-T Issued: 22/03/2019 Substance No: 000000053719