

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** REFLUX S800 (NZ)

**Recommended Use of the Chemical and Restrictions on Use** Dairy, food and beverage industries: Sanitising processing equipment.  
Available chlorine = 10 - 15%.

**Supplier:** Ixom Operations Pty Ltd (Incorporated in Australia)  
**NZBN:** 9429041465226  
**Street Address:** 166 Totara Street  
Mt Maunganui South  
New Zealand

**Telephone Number:** +64 9 368 2700  
**Facsimile:** +64 9 368 2710  
**Emergency Telephone:** **0 800 734 607 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

## 2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

**SIGNAL WORD:** DANGER

**Subclasses:**

Subclass 8.2 Category C - Substances that are corrosive to dermal tissue.

Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Approval Number: HSR004692



**Hazard Statement(s):**

H314 Causes severe skin burns and eye damage.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statement(s):**

**Prevention:**

P260 Do not breathe mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

Product Name: REFLUX S800 (NZ)

Issued: 28/03/2019

Substance No: 000000053727

Version: 1

# Safety Data Sheet



## Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).  
P363 Wash contaminated clothing before re-use.  
P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P391 Collect spillage.

## Storage:

P405 Store locked up.

## Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Notice 2017. This may also include any method of disposal that must be avoided.

## Other Hazards:

Contact with acids liberates toxic gas.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Water	7732-18-5	>60%	-
Sodium hypochlorite	7681-52-9	10-<30%	H314 H318 H335 H410
Sodium hydroxide	1310-73-2	<1%	H290 H314 H318 H335

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

### Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

### Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre. Continue to wash with large amounts of water until medical help is available.

### Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Product Name: REFLUX S800 (NZ)

Issued: 28/03/2019

Substance No: 000000053727

Version: 1

# Safety Data Sheet



## Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns. Delayed pulmonary oedema may result.

## 5. FIRE FIGHTING MEASURES

### Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem or Emergency Action Code:** 2X

### Specific hazards arising from the chemical:

Non-combustible material. Corrosive chemical. Environmentally hazardous.

### Special protective equipment and precautions for fire-fighters:

Decomposes on heating emitting toxic fumes, including those of chlorine. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Do not allow container or product to get into drains, sewers, streams or ponds. If contamination of sewers or waterways has occurred advise local emergency services.

### Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. For small amounts, in case of spillage flush with large quantities of water.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Avoid skin and eye contact and breathing in vapour, mists and aerosols. Keep out of reach of children.

**Conditions for safe storage, including any incompatibilities:** Store in a cool, dry, well ventilated place. Store away from foodstuffs. Store away from acids. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Workplace Exposure Standards:** No value assigned for this specific material by the New Zealand Workplace Health & Safety Authority. However, Workplace Exposure Standard(s) for constituent(s) and decomposition product(s):

Sodium hydroxide: Ceiling 2 mg/m<sup>3</sup>

Chlorine: WES-TWA 0.5 ppm, 1.5 mg/m<sup>3</sup>; WES-STEL 1 ppm, 2.9 mg/m<sup>3</sup>

# Safety Data Sheet



As published by the New Zealand Workplace Health & Safety Authority.

**WES - TWA (Workplace Exposure Standard - Time Weighted Average)** - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

**WES - STEL (Workplace Exposure Standard - Short Term Exposure Limits)** - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight-hour, time-weighted average exposures should be determined.

**WES - Ceiling (Workplace Exposure Standard - Ceiling)**. A concentration that should not be exceeded during any part of the working day.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

## Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, CHEMICAL GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.



Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear an air supplied respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Liquid  
**Colour:** Pale Yellow - Green

Product Name: REFLUX S800 (NZ)

Issued: 28/03/2019

Substance No: 000000053727

Version: 1

# Safety Data Sheet



<b>Odour:</b>	Chlorine
<b>Solubility:</b>	Miscible in water.
<b>Specific Gravity:</b>	1.2 @20°C
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	Not applicable
<b>Flammability Limits (%):</b>	Not applicable
<b>Autoignition Temperature (°C):</b>	Not available
<b>Boiling Point/Range (°C):</b>	Not available
<b>pH:</b>	12.5 (1% w/w)

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Contact with acids liberates toxic gas.
<b>Chemical stability:</b>	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. The amount of available chlorine diminishes over time.
<b>Possibility of hazardous reactions:</b>	Hazardous polymerisation will not occur. Reacts exothermically with acids . Reacts with ammonia, amines, or ammonium salts to produce chloramines. Decomposes on heating to produce chlorine gas.
<b>Conditions to avoid:</b>	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame. Avoid exposure to light. Avoid contact with other chemicals. Avoid contact with acids .
<b>Incompatible materials:</b>	Incompatible with acids , metals , metal salts , peroxides , reducing agents , ethylene diamine tetraacetic acid , methanol , aziridine , urea . Incompatible with ammonia and ammonium compounds such as amines and ammonium salts.
<b>Hazardous decomposition products:</b>	Chlorine.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.
<b>Eye contact:</b>	A severe eye irritant. Corrosive to eyes; contact can cause corneal burns. Contamination of eyes can result in permanent injury.
<b>Skin contact:</b>	Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.
<b>Inhalation:</b>	Breathing in mists or aerosols may produce respiratory irritation. Delayed (up to 48 hours) fluid build up in the lungs may occur.
<b>Acute toxicity:</b>	No LD50 data available for the product. For the constituent SODIUM HYPOCHLORITE: Oral LD50 (mice): 5800 mg/kg
<b>Serious eye damage/irritation:</b>	Moderate irritant (rabbit). Standard Draize test

Product Name: REFLUX S800 (NZ)

Issued: 28/03/2019

Substance No: 000000053727

Version: 1

# Safety Data Sheet



**Respiratory or skin sensitisation:** No information available.

**Chronic effects:** No information available for the product.

**Aspiration hazard:** No information available.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

**Persistence/degradability:** This material is biodegradable.

**Bioaccumulative potential:** Does not bioaccumulate.

**Mobility in soil:** No information available.

**Aquatic toxicity:** Very toxic to aquatic organisms.

96hr LC50 (fish): 0.065 mg/L (for sodium hypochlorite)

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of material through a licensed waste contractor. Decontamination and destruction of containers should be considered.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



**UN No:** 1791  
**Transport Hazard Class:** 8 Corrosive  
**Packing Group:** III  
**Proper Shipping Name or Technical Name:** HYPOCHLORITE SOLUTION  
**Hazchem or Emergency Action Code:** 2X

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 1791  
**Transport Hazard Class:** 8 Corrosive  
**Packing Group:** III  
**Proper Shipping Name or Technical Name:** HYPOCHLORITE SOLUTION

Product Name: REFLUX S800 (NZ)

Issued: 28/03/2019

Substance No: 000000053727

Version: 1

# Safety Data Sheet



IMDG EMS Fire: F-A  
IMDG EMS Spill: S-B

## Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1791  
Transport Hazard Class: 8 Corrosive  
Packing Group: III  
Proper Shipping Name or  
Technical Name: HYPOCHLORITE SOLUTION

## 15. REGULATORY INFORMATION

### **Classification:**

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

### **Subclasses:**

Subclass 8.2 Category C - Substances that are corrosive to dermal tissue.  
Subclass 8.3 Category A - Substances that are corrosive to ocular tissue.  
Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Approval Number: HSR004692

### **Hazard Statement(s):**

H314 Causes severe skin burns and eye damage.  
H411 Toxic to aquatic life with long lasting effects.

## 16. OTHER INFORMATION

'Registry of Toxic Effects of Chemical Substances'. Ed. D. Sweet, US Dept. of Health & Human Services: Cincinnati, 2018.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

### **Reason(s) for Issue:**

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: REFLUX S800 (NZ)

Issued: 28/03/2019

Substance No: 000000053727

Version: 1