

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:

SILICON BRIQUETTE

Recommended Use of the Chemical General chemical. and **Restrictions on Use**

Supplier: NZBN: Street Address:	Ixom Operations Pty Ltd (Incorporated in Australia) 9429041465226 166 Totara Street Mt Maunganui South New Zealand
Telephone Number:	+64 9 368 2700
Facsimile:	+64 9 368 2710
Emergency Telephone:	0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

SIGNAL WORD: WARNING

Subclasses: Subclass 6.1 Category E - Substances which are acutely toxic.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017 Approval Number: HSR002503

Hazard Statement(s): H303 May be harmful if swallowed.

Precautionary Statement(s):

Prevention: P102 Keep out of reach of children.

Response:

No response statements.

Storage: No storage statements.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Notice 2017. This may also include any method of disposal that must be avoided.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes	
Product Name: SILICON BRIOLIETTE			Issued: 28/02/2020	



Silicon 7440-21-3 >=97% -

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with soap and water. If irritation occurs, seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Never give anything by the mouth to an unconscious patient. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Water fog (or if unavailable fine water spray).

Specific hazards arising from the chemical:

Combustible solid. On burning will emit toxic fumes, including those of oxides of silicon.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Shut off all possible sources of ignition. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. Use non-sparking tools.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in dust. Take precautionary measures against static discharges. When using do not eat, drink or smoke. Wash hands thoroughly after handling.



Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Protect from moisture. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Silicon: WES-TWA 10 mg/m³

As published by the New Zealand Workplace Health & Safety Authority.

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The average airborne concentration of a substance calculated over an eight-hour working day.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.



Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Colour: Odour: Solubility: Solid Briquettes Black Grey Not specified Insoluble in water.

Product Name: SILICON BRIQUETTE Substance No: 00000053848 Issued: 28/02/2020 Version: 1



Specific Gravity:3.5Relative Vapour Density (air=1):Not availableVapour Pressure (20 °C):Not availableFlash Point (°C):Not availableFlammability Limits (%):Not availableAutoignition Temperature (°C):780Melting Point/Range (°C):1410pH:Not applicable

10. STABILITY AND REACTIVITY

Reactivity:	Reacts with water.
Chemical stability:	Stable.
Possibility of hazardous reactions:	Can react with alkali-metal carbonates when heated. Can react explosively with water.
Conditions to avoid:	Avoid exposure to heat, sources of ignition, and open flame. Avoid exposure to moisture. Avoid dust generation.
Incompatible materials:	Incompatible with oxidising agents, chlorine, fluorine, calcium carbide, alkali carbonates, fluoride, rubidium carbide, manganese trifluoride.
Hazardous decomposition products:	Oxides of silicon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	No adverse effects expected, however, large amounts may cau vomiting.	ise nausea and
Eye contact:	May be an eye irritant. Exposure to the dust may cause discomparticulate nature. May cause physical irritation to the eyes.	fort due to
Skin contact:	Contact with skin may result in irritation.	
Inhalation:	Breathing in dust may result in respiratory irritation.	
Acute toxicity: Oral LD50 (rat): 3160 mg/kg		
Skin corrosion/irritation: Serious eye damage/irritation: Respiratory or skin sensitisation:	May cause mechanical irritation. May cause mechanical irritation. No information available.	
Chronic effects: No information a	available for the product.	
Mutagenicity: Carcinogenicity: Reproductive toxicity:	No information available. No information available. No information available.	
Product Name: SILICON BRIQUETTE Issued		lssued: 28/02/20



Specific Target Organ Toxicity
(STOT) - single exposure:No information available.Specific Target Organ Toxicity
(STOT) - repeated exposure:No information available.Aspiration hazard:No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Persistence/degradability: No information available.

Bioaccumulative potential: No information available.

Mobility in soil: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

Subclasses:

Subclass 6.1 Category E - Substances which are acutely toxic.

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017 Approval Number: HSR002503

Hazard Statement(s):

H303 May be harmful if swallowed.

16. OTHER INFORMATION

Supplier Material Safety Data Sheet; 11/2015.



Reason(s) for Issue:

First Issue Primary SDS

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.