# SAFETY DATA SHEET



Revision date: 22-May-2023

Revision Number 1

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product identifier** 

Product Name MAC GLIDE SPRAY 400mL (Premium Conveyor Lubricant Aerosol)

**Product Code(s)** 000000054459

Other means of identification

UN number 1950

Synonyms CIXGLIDE4A-400ML

Recommended use of the chemical and restrictions on use

**Recommended use**Glide Spray is a non-silicone lubricant and surface protective coating, suitable for a wide

range of industrial and domestic applications. Glide Spray remains stable in a wide range of temperatures, odourless, colourless and non-staining. The low surface tension of Glide Spray readily wets clean surfaces to impart water repellancy, corrosion protection and release characteristics. Glide Spray is insoluble in organic liquids other than active solvents

and is non-rancidifying, it is essentially non-irritating and non-toxic.

A lubricating and release agent for use where staining, heat or chemical attack are a problem and Glide Spray is useful where finishing operations such as painting or gluing

mean that a non-silicone release agent/lubricant is essential.

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier

Ixom Operations Pty Ltd (Incorporated in Australia) NZBN: 9429041465226 Address: 166 Totara Street

Mt Maunganui South

New Zealand

Telephone Number: +64 9 368 2700

Facsimile: +64 9 368 2710

For further information, please contact

Contact Point Product Safety Department

Emergency telephone number

Emergency Telephone 0 800 734 607 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

### 2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433 Transport of Dangerous Goods on Land; DANGEROUS GOODS.

Classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

00000054459 - MAC GLIDE SPRAY 400mL (Premium Conveyor Lubricant Aerosol)

Revision date: 22-May-2023

**Revision Number** 1

#### GHS Classification

### **SIGNAL WORD**

Warning

Aerosols (Flammable) Group Standard 2020

Approval Number: HSR002515

Flammable aerosols Category 1

#### Label elements



#### **Hazard statements**

H223 - Flammable aerosol

### **Precautionary Statements - Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Other hazards which do not result in classification

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Mixture**

Chemical name	CAS No.	Weight-%
Propane	74-98-6	30-60
Butane	106-97-8	30-60
Non hazardous component(s)	-	to 100

### 4. FIRST AID MEASURES

# Description of first aid measures

General advice For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New

Zealand 0800 764 766) or a doctor.

**Emergency telephone number** Poisons Information Center, New Zealand: 0800 764 766

Poisons Information Center, Australia: 13 11 26

**Inhalation** Remove to fresh air. Call a physician if symptoms occur.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

00000054459 - MAC GLIDE SPRAY 400mL (Premium Conveyor Lubricant Aerosol)

Revision date: 22-May-2023

Revision Number 1

Consult a physician.

**Skin contact** Wash off immediately with plenty of water. Call a physician if symptoms occur.

**Ingestion** Clean mouth with water. Do NOT induce vomiting. Get medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

### 5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Fine water spray. Carbon dioxide (CO2). Foam. Dry chemical.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the

chemical

Highly flammable. Containers may explode when heated. May form explosive mixtures with air. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

**Hazardous combustion products** Carbon oxides. Hydrocarbons.

Special protective actions for fire-fighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Contents under pressure. Do not puncture or incinerate cans. ELIMINATE all ignition

sources (no smoking, flares, sparks or flames in immediate area). Do not breathe fume, gas, mist, vapours, spray. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as

required.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

This product is a gas. Contents under pressure. Do not puncture or incinerate cans. Pick up

Revision Number 1

and transfer to properly labelled containers. Do not flush residues with water. Retain as contaminated waste. Use personal protective equipment as required.

#### Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Keep out of reach of children. Contents under pressure. Do not puncture or incinerate cans.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Ensure adequate ventilation.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from

foodstuffs and sources of heat or ignition. Keep at temperatures below 50°C / 122°F.

Incompatible materials Acids. Alkalis. Oxidizing agents. Alkaline earth metals. Finely powdered metals.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Limits No value assigned for this specific material by the New Zealand Workplace Health & Safety

Authority. However, Workplace Exposure Standard(s) for constituent(s):

Butane: WES-TWA 800 ppm, 1,900 mg/m<sup>3</sup>

Propane: Simple asphyxiant-may present an explosion hazard

As published by the New Zealand Workplace Health & Safety Authority.

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

Asphyxiant - gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Appropriate engineering controls

**Engineering controls** Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded,

**Revision Number** 1

the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

#### Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



Eye/face protection Glasses.

Hand protection Impervious gloves.

Skin and body protection Overalls. Protective shoes or boots. (for industrial handling).

Respiratory protection If determined by a risk assessment an inhalation risk exists, wear an organic

vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

No information available. **Environmental exposure controls** 

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Gas, Aerosol

**Appearance** No information available

Color Colourless

Slight . Ethereal -like Odor **Odor threshold** No information available

Remarks • Method **Property** Values

No data available Ha None known No data available None known Melting point / freezing point Boiling point / boiling range No data available None known Flash point <20°C (Propellant) None known **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

No data available

Upper flammability or explosive

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available None known >1 (air=1) Vapor density None known Relative density 0.80-0.82 None known Water solubility No data available None known Solubility(ies) Dispersible in water None known

000000054459 - MAC GLIDE SPRAY 400mL (Premium

**Conveyor Lubricant Aerosol)** 

Revision date: 22-May-2023

**Revision Number** 1

Partition coefficientNo data availableNone knownAutoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Other information

# 10. STABILITY AND REACTIVITY

Reactivity

Reactivity No information available.

**Chemical stability** 

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical impact None.

Possibility of hazardous reactions

Sensitivity to static discharge

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

None.

Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Direct sunlight. Contact

with foodstuffs.

Incompatible materials

Incompatible materials Acids. Alkalis. Oxidizing agents. Alkaline earth metals. Finely powdered metals.

**Hazardous decomposition products** 

Hazardous decomposition products Carbon oxides. Hydrocarbons.

# 11. TOXICOLOGICAL INFORMATION

### **Acute toxicity**

Information on likely routes of exposure

**Product Information**No adverse health effects expected if the chemical is handled in accordance with this

Safety Data Sheet and the chemical label. Symptoms or effects that may arise if the

chemical is mishandled and overexposure occurs are:

Inhalation May cause irritation. Breathing in high concentrations can produce central nervous system

depression, which can lead to loss of coordination, impaired judgement and if exposure is

prolonged, unconsciousness.

**Eye contact** May cause irritation.

**Skin contact** May cause irritation.

00000054459 - MAC GLIDE SPRAY 400mL (Premium Conveyor Lubricant Acrosol)

Conveyor Lubricant Aerosol)

Revision Number 1

Revision date: 22-May-2023

**Ingestion** Not an expected route of exposure.

**Symptoms** No information available.

**Acute toxicity** 

#### Numerical measures of toxicity

Refer to component information below.

**Component Information** 

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propane	-	-	> 800000 ppm (Rat) 15 min
Butane	-	-	= 658 g/m <sup>3</sup> (Rat) 4 h

See section 16 for terms and abbreviations

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**No information available.

Serious eye damage/eye irritation No information available.

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

Reproductive toxicity No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

**Ecotoxicity** Keep out of waterways.

**Terrestrial ecotoxicity** There is no data for this product.

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

**Bioaccumulation** No information available.

**Revision Number** 1

**Mobility** 

Mobility in soil No information available.

**Component Information** 

Chemical name	Partition coefficient
Propane	2.3
Butane	2.89

Other adverse effects

Other adverse effects No information available.

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Waste from residues/unused products

Dispose of product in packaging/container in a way that is consistent with the Hazardous Substances (Disposal) Notice 2017 and the Act, and Hazardous Substances (Amendments and Revocations) Notice 2020. Treat the chemical using a method that changes the characteristics or composition of the chemical so that the chemical is no longer a hazardous chemical; or export the chemical from New Zealand as waste. Class 2, 3 and 4 chemicals - may not be disposed of into or onto a landfill or sewage facility. They may only be burnt in certain situations. Class 2.1.1, 3.1 and 4.1.1 chemicals may only be discharged into the environment as waste if the substance will not at any time come into contact with class 1 or class 5 substances; and there will be no ignition source in the vicinity of the disposal site at any time and if the substance were to ignite, no person, or place where a person may legally be, would be exposed to an unsafe level of heat radiation.

Contaminated packaging

Packages may only be reused or recycled if the package has been treated to remove any residual contents of the hazardous chemical (class 1, 2, 3, 4, or 5); or the contents of the residue in the package are below the threshold for the chemical to be classified as hazardous (class 6, 8, or 9 chemical).

# 14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT Classified as a Dangerous Good according to NZS 5433 Transport of Dangerous Goods on

Land; DANGEROUS GOODS.

UN number 1950

Proper shipping name AEROSOLS

Hazard class 2.1

IATA Classified as Dangerous Goods by the criteria of the International Air Transport Association

(IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN number 1950

UN proper shipping name AEROSOLS, FLAMMABLE

Transport hazard class(es) 2.1

<u>IMDG</u> Classified as Dangerous Goods by the criteria of the International Maritime Dangerous

Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN number 1950

UN proper shipping name AEROSOLS

Transport hazard class(es) 2.1
IMDG EMS Fire F-D
IMDG EMS Spill S-U

**Revision Number** 1

Marine pollutant No

### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

**New Zealand** 

National regulations See section 8 for national exposure control parameters

.

International Inventories

**NZIoC** Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. **TSCA** DSL/NDSL Contact supplier for inventory compliance status. **EINECS/ELINCS** Contact supplier for inventory compliance status. **ENCS** Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. **IECSC** Contact supplier for inventory compliance status. **KECL PICCS** Contact supplier for inventory compliance status. AIIC Contact supplier for inventory compliance status.

Legend:

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AIIC- Australian Inventory of Industrial Chemicals** 

### **International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

# 16. OTHER INFORMATION

Supplier Safety Data Sheet 09/2020

Prepared By This Safety Data Sheet has been prepared by Ixom Operations Pty Ltd (Toxicology and

SDS Services).

Issuing Date: 22-May-2023

Reason(s) For Issue: First Issue Primary SDS

**Revision Number** 1

#### **Revision Note:**

The symbol (\*) in the margin of this SDS indicates that this line has been revised.

# Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

C Carcinogen

#### Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian Industrial Chemicals Introduction Scheme (AICIS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

#### **Disclaimer**

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their lxom representative or lxom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**End of Safety Data Sheet**