

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DIETHYLENE GLYCOL, DEG

Recommended Use of the Chemical and Restrictions on Use Multi-use chemical.

Supplier: Ixom Operations Pty Ltd (Incorporated in Australia)
NZBN: 9429041465226
Street Address: 166 Totara Street
Mt Maunganui South
New Zealand

Telephone Number: +64 9 368 2700
Facsimile: +64 9 368 2710
Emergency Telephone: **0 800 734 607 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

SIGNAL WORD: WARNING

Subclasses:

Subclass 6.1 Category E - Substances which are acutely toxic.

Subclass 6.9 Category B - Substances that are harmful to human target organs or systems.

Approval Number: HSR002709



Hazard Statement(s):

H303 May be harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s):

Prevention:

P260 Do not breathe mist/vapours/spray.

Response:

P314 Get medical advice/attention if you feel unwell.

Storage:

No storage statements.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Notice 2017. This may also include any method of disposal that must be avoided.

Product Name: DIETHYLENE GLYCOL, DEG
Substance No: 000030122901

Issued: 04/07/2019
Version: 6

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
2,2'-Oxybis(ethanol) (Diethylene glycol)	111-46-6	100%	H302 H373

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with soap and water. If irritation occurs, seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical advice. Never give anything by the mouth to an unconscious patient.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the chemical:

Combustible liquid. May form flammable vapour mixtures with air. Vapour may travel a considerable distance to source of ignition and flash back.

Special protective equipment and precautions for fire-fighters:

On burning will emit toxic fumes, including those of oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Safety Data Sheet



Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in vapour. Keep out of reach of children. When using do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated place. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Diethylene glycol: WES-TWA 23 ppm, 101 mg/m³

As published by the New Zealand Workplace Health & Safety Authority.

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



Safety Data Sheet



Wear overalls, safety glasses and impervious gloves. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Colourless
Odour:	Slight
Odour Threshold:	Not available
Molecular Formula:	C4H10O3
Solubility:	Miscible in water.
Specific Gravity:	1.118 @ 25°C
Relative Vapour Density (air=1):	3.66
Vapour Pressure (20 °C):	<0.008 hPa
Flash Point (°C):	143 (Closed cup)
Flammability Limits (%):	1.7-12.3 (V)
Autoignition Temperature (°C):	372
Boiling Point/Range (°C):	245
pH:	5.0-8 (500 g/L, 20°C)
Evaporation Rate:	<1 (n-Butyl acetate=1)
Freezing Point/Range (°C):	-10

10. STABILITY AND REACTIVITY

Reactivity:	Hygroscopic: absorbs moisture or water from surrounding air. May form unstable peroxides in storage.
Chemical stability:	Stable under normal conditions of use.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Excessive heat will lead to accelerated oxidative degradation. Avoid exposure to moisture.
Incompatible materials:	Incompatible with strong oxidising agents , strong acids , zinc .
Hazardous decomposition products:	Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, headaches, dizziness, gastrointestinal irritation, and central nervous system depression. Swallowing large amounts may result in muscle tremors, central nervous system depression, convulsions and coma.
Eye contact:	May be an eye irritant.

Safety Data Sheet



Skin contact: Contact with skin may result in irritation.
Inhalation: Breathing in vapour may produce respiratory irritation.

Acute toxicity:
Oral LD50 (rat): 12000 mg/kg
Dermal LD50 (rabbit): 11890 mg/kg

Respiratory or skin sensitisation: Not a skin sensitiser (guinea pig).

Chronic effects: Available evidence from animal studies indicate that repeated or prolonged exposure to this material could result in effects on the liver and kidneys .

Mutagenicity: Non-mutagenic in AMES test. No evidence of mutagenic effects.
Carcinogenicity: Not listed as carcinogenic according to the International Agency for Research on Cancer (IARC).
Reproductive toxicity: No information available.
Specific Target Organ Toxicity (STOT) - single exposure: No information available.
Specific Target Organ Toxicity (STOT) - repeated exposure: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard: No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.
Persistence/degradability: The material is biodegradable.
Bioaccumulative potential: No information available.
Mobility in soil: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:
Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2012 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Product Name: DIETHYLENE GLYCOL, DEG
Substance No: 000030122901

Issued: 04/07/2019
Version: 6

Safety Data Sheet

**Classification:**

Classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and the Hazardous Substances (Classification) Notice 2017.

Subclasses:

Subclass 6.1 Category E - Substances which are acutely toxic.

Subclass 6.9 Category B - Substances that are harmful to human target organs or systems.

Approval Number: HSR002709

Hazard Statement(s):

H303 May be harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

16. OTHER INFORMATION

Supplier Safety Data Sheet; 06/ 2018.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

5 Yearly Revised Primary SDS

Change in Hazardous Chemical Classification

Update in Toxicological Information

Change in Physical Properties

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ixom Operations Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Ixom representative or Ixom Operations Pty Ltd at the contact details on page 1.

Ixom Operations Pty Ltd's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.